

48. CHANGE REQUISITN - REVISION 002

48.0 Overview


This chapter describes the Business Service Request named CHANGE REQUISITN, the Verb being CHANGE and the Noun being REQUISITN.

The purpose of the CHANGE REQUISITN Business Service Request is to communicate changes to an existing request for goods or services. This change must refer to the original document and/or item requested. The change processing assumes replacement of fields sent, with the exception of:

REQUISTNID
REQLINENUM


If any of the Field Identifiers above require changing, that constitutes a cancellation of the request and/or the addition of another Requisition.

This BSR usually causes updates to occur and may be used as part of a larger integration scenario or as a single tool for communicating demand. The picture below visualizes a possible use of this BSR.



48.1 CHANGE REQUISITN

The CHANGE REQUISITN Business Object Document consists of the following components:



The Business Service Request **CHANGE REQUISITN** uses six Data Types:

1. **REQHEADER** - Information that applies to the Requisition. This Data Type is required.
2. **PARTNER** - Partner information, i.e., name, currency, payment method, etc. This Data Type is optional.
3. **ADDRESS** - Partner location information. This Data Type is optional.
4. **CONTACT** - Name, telephone and other information to contact people associated with the **PARTNER**. This Data Type is optional.
5. **REQLINE** - Information that describes the requested item and its attributes. This Data type is optional.

6. **REQSUBLINE** - Used if the item on the REQLINE needs to be divided into smaller units such as sub-components or subassemblies. This Data Type is optional.

48.2 REQHEADER

The Data Type, “**REQHEADER**”, is the first Type the Business Service Request “**CHANGE REQUISITN**” uses. This Data Type is required.

Listed are all the Field Identifiers and Segments that are valid for use within the REQHEADER Data Type. The first column of the table indicates the name. Segment names also include the Qualifier in parenthesis.

The second column indicates in which OAGIS Appendix the data is described, basically if the data is a Field Identifier or a Segment. Details of the Field Identifiers can be located in Appendix C, and details of the Segments can be located in Appendix D.

The first table represents required data.

REQUIRED REQHEADER DATA	
NAME	APPENDIX
REQUISTNID	C

Processing Notes:

REQUISTNID is the link that ties back to an origination of the document. It is the identifier of an original transaction or document. This is the singular field that refers to an audit record. Together with the Sender information in the Control Area of the BOD, the REQUISTNID is part of the referencing system, which will enable drill back audit trail functionality.

The second table describes data that is optional.

OPTIONAL REQHEADER DATA	
NAME	APPENDIX
APPROVED	C
BUYERID	C
CONTRACTB	C
CONTRACTS	C
COSTCENTER	C

OPTIONAL REQHEADER DATA	
NAME	APPENDIX
DATETIME(DOCUMENT)	D
DELIVERTO	C
DESCRIPTN	C
DOCKID	C
FUND	C
GLENTITYS	C
GLNOMACCT	C
HDRSTATUS	C
NOTES	C
OPERAMT(EXTENDED)(T)	D
OPRAMTAUTH	C
PLANNERID	C
POENTITY	C
REASONCODE	C
REQUESTER	C
SALESORDID	C
SITELEVEL1 - SITELEVEL9	C
USERAREA	C

48.3 PARTNER

The Data Type “**PARTNER**” represents the business partner. Several examples of PARTNERS are those business partners that products are sold to, bought from, or delivered by. For each REQHEADER, it is optional to have one occurrence of the Data Type that represents the business partner that the goods or services are purchased from (**Supplier**).

Listed are all the Field Identifiers and Segments that are valid for use within the PARTNER Data Type.

The first table represents required data.

REQUIRED PARTNER DATA	
NAME	APPENDIX
NAME1	C
PARTNRID	C
PARTNRTYPE	C

Processing Note:

Either the NAME1 is required or the PARTNRID and PARTNRTYPE are required.

The second table describes data that is optional.

OPTIONAL PARTNER DATA	
NAME	APPENDIX
CURRENCY	C
DESCRIPTN	C
NAME2 - NAME9	C
PARTNRIDX	C
TAXEXEMPT	C
TAXID	C
USERAREA	C

48.4 ADDRESS

The Data Type “**ADDRESS**” represents the data concerning the location of the business partner. Listed are all the Field Identifiers and Segments that are valid for use within the ADDRESS Data Type. All data for the ADDRESS Data Type is optional.

OPTIONAL ADDRESS DATA	
NAME	APPENDIX
ADDRLINE1 - ADDRLINE9	C
ADDRTYPE	C
CITY	C
COUNTRY	C
COUNTY	C
DESCRIPTN	C
FAX1 - FAX9	C
POSTALCODE	C
REGION	C
STATEPROVN	C
TAXJRSDCTN	C
TELEPHONE1 - TELEPHONE9	C
URL	C
USERAREA	C

48.5 CONTACT

The Data Type “**CONTACT**” represents people associated with the PARTNER and various ways to contact them, such as telephone or fax. The CONTACT is an optional Data Definition Area that must follow the partner that it is associated with. Listed are all the Field Identifiers and Segments that are valid for use within the CONTACT Data Type.

The first table represents required data.

REQUIRED CONTACT DATA	
NAME	APPENDIX
NAME1	C

The second table describes data that is optional.

OPTIONAL CONTACT DATA	
NAME	APPENDIX
DESCRIPTN	C
EMAIL	C
FAX1 - FAX9	C
NAME2 - NAME9	C
TELEPHONE1 - TELEPHONE9	C
USERAREA	C

48.6 REQLINE

The Data Type, “**REQLINE**”, is the second Data Type the Business Service Request “**CHANGE REQUISITN**” uses. This Data Type is optional.

Listed are all the Field Identifiers and Segments that are valid for use within the REQLINE Data Type. The first column of the table indicates the name. Segment names also include the Qualifier in parenthesis.

The second column indicates in which OAGIS Appendix the data is described, basically if the data is a Field Identifier or a Segment. Details of the Field Identifiers can be located in Appendix C, and details of the Segments can be located in Appendix D.

The first table represents required data.

REQUIRED REQLINE DATA	
NAME	APPENDIX
REQLINENUM	C

The second table describes data that is optional.

OPTIONAL REQLINE DATA	
NAME	APPENDIX
APPROVED	C
BUYERID	C
COMMODITY1 - COMMODITY3	C
CONTRACTB	C
CONTRACTS	C
COSTCENTER	C
DATETIME(REQUIRED)	D
DELIVERTO	C
DESCRIPTN	C
DOCKID	C
DRAWING	C
FRGHTCLS	C
FUND	C
GLENTITYS	C
GLNOMACCT	C
HAZRDMATL	C
ITEM	C
ITEMRV	C
ITEMTYPE	C
ITEMX	C
NOTES	C
OPERAMT(UNIT)(T)	D
PLANNERID	C
POENTITY	C
PROPERTY1 - PROPERTY99	C
QUANTITY(ORDERED)	D
REASONCODE	C
REQLNSTAT	C
REQUESTER	C
SALESORDID	C
SERIALNUM	C

OPTIONAL REQLINE DATA	
NAME	APPENDIX
SITELEVEL1 - SITELEVEL9	C
UPC	C
USERAREA	C

48.7 REQSUBLINE

The Data Type “**REQSUBLINE**” represents the any additional information concerning the product on the REQLINE. The REQSUBLINE can be used to describe a specific configuration of the ordered item.

The REQSUBLINE is an optional Data Type. Listed are all the Field Identifiers and Segments that are valid for use within the REQSUBLINE Data Type. The first table represents required data.

REQUIRED REQSUBLINE DATA	
NAME	APPENDIX
DESCRIPTN	C
ITEM	C
ITEMX	C
UPC	C

Processing Notes:

Of the following required fields, at least one is required.

- 1) ITEM or,
- 2) DESCRIPTN or,
- 3) ITEMX or,
- 4) UPC

REQSUBLINE usage is further defined by its position in the Requisition structure. For example, each REQSUBLINE Data Type that follows a REQLINE Data Type is inferred to be associated with the REQLINE Data Type.

The second table describes data that is optional.

OPTIONAL REQSUBLINE DATA	
NAME	APPENDIX
DRAWING	C
ITEMRV	C
ITEMRVX	C
NOTES	C
PROPERTY1 - PROPERTY99	C
QUANTITY(ITEM)	D
REASONCODE	C
RQSLINENUM	C
USERAREA	C