



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.0.1

### STANDARD ST.32

#### RECOMMENDATION FOR THE MARKUP OF PATENT DOCUMENTS USING SGML (STANDARD GENERALIZED MARKUP LANGUAGE)

*Revision adopted by the PCIPi Executive Coordination Committee  
at its seventeenth session on November 24, 1995*

#### TABLE OF CONTENTS

RECOMMENDATION FOR THE MARKUP OF PATENT DOCUMENTS USING SGML.....	1
RECOMMENDATION FOR THE MARKUP OF PATENT DOCUMENTS USING SGML.....	1
INTRODUCTION.....	1
DEFINITIONS .....	2
CHARACTER SETS .....	3
REFERENCES.....	4
REQUIREMENTS OF THE RECOMMENDATION.....	4
PART 1: SGML MARKUP FOR COMMON TEXT .....	6
GENERAL TEXT .....	6
TABLE OF SGML TAGS.....	6
SGML TAGS: DESCRIPTION AND USAGE .....	9
DOCUMENT STRUCTURE .....	9
<PATDOC> : PATent DOCument .....	9
<SDOxx> : Sub-DOCument tags .....	9
<CHG> : CHanGe.....	11
<BCHG> : Beginning of a CHanGe .....	11
<ECHG> : End of CHanGe.....	11
<H> : Headings .....	12
<P> : Paragraphs.....	12
<PC> : Paragraph Continuation .....	12
  : BReak .....	13
<FOO> : FOOtnotes .....	13
<FOR> : FOOtnote Reference .....	14
TEXT 'HIGHLIGHTING' MARKUP .....	14
<B> : Bold.....	14
<BAI> : BAIkaku.....	14
<HAN> : HANkaku .....	15
<I> : Italic .....	15
<O> : 'Over' embellishments .....	15
<U> : Under embellishments .....	16
<SB> : SuBscript.....	16
<SP> : SuPerscript.....	17
MISCELLANEOUS.....	17
<CHF> : CHaracter Fraction constructs.....	17
<CHFBR> : CHaracter Fraction BReak.....	17
<FLA> : FLoating Accents.....	18
<FLAC> : FLoating ACcent .....	18
<LTL> : LiTeraL text.....	19
PAGE STRUCTURE TAGS .....	19



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.0.2

<TXF> : TeXt Frame .....	19
<DP> : Document Page .....	20
<PCL> : Page CoLumn .....	20
<PLN> : Page LiNe .....	21
LISTS .....	23
TABLE OF SGML TAGS AND ATTRIBUTES .....	23
SGML TAGS: DESCRIPTION AND USAGE .....	23
<DL> : Definition List .....	23
<DT> : Definition Term .....	24
<DD> : Definition Description .....	24
<OL> : Ordered List .....	24
<SL> : Simple List .....	25
<UL> : Unordered List .....	25
<LI> : List Item .....	25
IMAGES .....	28
TABLE OF SGML TAGS AND ATTRIBUTES .....	28
SGML TAGS: DESCRIPTION AND USAGE .....	28
<EMI> : EMbedded Image .....	28
<ELE> : EMbedded image LEgend .....	30
<EMR> : EMbedded image Reference .....	31
<RTI> : Replacement of Text by Image .....	31
<GAI> : GAIji .....	32
TABLES .....	33
TABLE OF SGML TAGS AND ATTRIBUTES .....	33
SGML TAGS: DESCRIPTION AND USAGE .....	33
<TAB> : TABular material .....	33
<TTI> : Table TItle .....	34
<TCH> : Table Column Header .....	35
<TSH> : Table Sub-Header .....	35
<TSB> : Table StuB line .....	36
<ROW> : ROW .....	36
<CEL> : CELI .....	37
CHEMICAL FORMULAE .....	43
TABLE OF TAGS AND ATTRIBUTES .....	43
SGML TAGS: DESCRIPTION AND USAGE .....	43
<CHE> : CHEmical formula .....	43
<CHR> : CHemical Reaction .....	43
<CRF> : Chemical ReFeRence .....	44
TABLE OF SGML TAGS AND ATTRIBUTES .....	44
SGML TAGS: DESCRIPTION AND USAGE .....	46
FORMULA AND FORMULA REFERENCE .....	46
<F> : inline Formula .....	46
<DF> : Display Formula .....	46
<DFG> : Display Formula Group .....	47
<DFREF> : mathematical Formula REFeRence .....	47
FORMULA CONTENT .....	48
<MARK> : MARK .....	48
<MARKREF> : MARK REFeRence .....	48
<BREAK> : BREAK .....	49
<BOX> : BOXes .....	49
<OV> : 'OVer' embellishments .....	49
<TENSOR> : TENSORS .....	50
<ITALIC> : ITALIC .....	50
<ROMAN> : ROMAN .....	50



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.0.3

<FRAC> : FRACtions.....	50
<OVER> : OVER (fraction denominator).....	51
<SUP> : SUPerscript.....	51
<SUB> : SUBscript.....	52
<PILE> : PILEs.....	52
<ABOVE> : ABOVE.....	53
<FENCE> : FENCEs.....	53
<MIDDLE> : MIDDLE (post).....	54
<PLEX> : PLEX and <OPERATOR>: OPERATOR.....	54
<SUM> : SUMmation.....	55
<INTEGRAL> : INTEGRAL.....	55
<PRODUCT> : PRODUCT.....	55
<FROM> : Operator for "limits".....	55
<OF> : Operator for "limits".....	55
<TO> : Operator for "limits".....	56
<SQRT> : SQuare RooT.....	56
<SQUARE> : SQUARE.....	56
<ROOT> : ROOT.....	57
<POWER> : POWER.....	57
<VEC> : VECtors.....	58
<MATRIX> : MATRIces.....	58
<COL> : COLumn(s) in a matrix.....	58
CITATIONS, NAMES AND ADDRESSES.....	58
TABLE OF SGML TAGS.....	59
CIT.....	59
Citation.....	59
Patent Document Citations.....	59
Non-Patent Document Citations.....	59
ARTCIT.....	59
Article information, citation.....	59
ARTCIT.....	59
Article information, citation.....	59
BOOKCIT.....	59
Book Information, citation.....	59
DBASECIT.....	60
Database Information Group, citation.....	60
Author Group.....	60
BOOKID.....	60
Book Identification.....	60
Document Identification.....	60
Individual or Organization Data.....	61
General Name.....	61
ADR.....	61
Address.....	61
DATE.....	61
Date.....	61
PART 2: SGML MARKUP FOR PATENT BIBLIOGRAPHIC DATA.....	62
PATENT BIBLIOGRAPHIC DATA.....	63
TABLE OF SGML TAGS.....	63
B000 Office Specific System/File Information.....	63
B100 Document Identification.....	63



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.0.4

---

B200 Domestic Filing Data .....	63
B300 Priority Data .....	64
B400 Public Availability Dates .....	64
B500 Technical Information .....	65
B600 References to other legally or procedurally related domestic patent documents .....	66
B700 Parties Concerned with the Document .....	67
B800 International Convention Data other than the Paris Convention .....	68
B900 Miscellaneous data .....	68
 ANNEX A: SGML DECLARATION FOR PATENT DOCUMENTS .....	 72
 ANNEX B: DOCUMENT TYPE DEFINITION FOR PATENT DOCUMENTS .....	 74
 ANNEX C: PATENT CHARACTER ENTITY REFERENCES (NON-ISO) .....	 93



## STANDARD ST.32

### RECOMMENDATION FOR THE MARKUP OF PATENT DOCUMENTS USING SGML (STANDARD GENERALIZED MARKUP LANGUAGE)

*Revision adopted by the PCIP Executive Coordination Committee  
at its seventeenth session on November 24, 1995*

#### INTRODUCTION

1. This Recommendation is an application of International Standard ISO 8879:1986, *Information Processing – Text and Office Systems – Standard Generalized Markup Language (SGML)*; which is under review.
2. This Recommendation provides for the exchange of patent documents in machine-readable form on any exchange medium in a hardware-, software- and layout-independent format. Such independence of the representation of the contents of a document from their intended uses is achieved by using International Standard ISO 8879:1986, *Information processing – Text and office systems – Standard Generalized Markup Language (SGML)*, to define generic identifiers which are in turn used to mark the logical structure of each patent document.
3. International Standard ISO 8879:1986 cannot be used *per se* as the basis for document processing. That is not the intention of the standard. Instead, ISO 8879 “standardizes the application of generic coding and generalized markup concepts. It provides a coherent and unambiguous *syntax* for describing whatever a user chooses to identify within a document” (ISO 8879:1986 page 2). The choice of tags, that is, the *semantics* to which the syntax applies, is left to the user.
4. Therefore, this Recommendation defines generic identifiers or “tags” for marking the logical elements of a patent document. The logical elements of a patent document are of two types: common text and patent-specific content.
5. Under the terms of International Standard ISO 8879:1986 any tags may be used in a particular document so long as the semantics are defined in an accompanying document type definition (DTD). It is conceivable that a patent issuing authority may choose different tags than those specified in this Recommendation. So long as the tags were defined in the accompanying DTD, the document could be presented to a user on a system designed to read SGML documents. However, documents which use a DTD that differs from that specified below cannot be considered to be in compliance with this Recommendation even if they are in compliance with ISO 8879:1986.
6. Markup in compliance with this Recommendation is independent of layout and formatting. Decisions regarding layout and formatting must be made at the time a document is presented for reading, either on a display screen or on paper. It is at the time of presentation that, for example, text which has been marked as emphasized (bold, italic, etc.) is rendered in an available font which has more or less the desired appearance. It is at the time of presentation that the size of the display page (screen or paper) is determined. Many such decisions which map the generic identifiers in a document to the capabilities of a particular physical display device (whether screen or paper) determine, for example, how many characters will fit on one line or how much text will fit on a display page. As a result, the document may not have exactly the same physical appearance when it is presented on different display devices. This Recommendation does not address issues concerned with mapping generic identifiers to a particular display device. It can be expected that in the future two standards may be applied in this area: Standard Page Description Language (SPDL) ISO/IEC DIS 10180 and Document Style Semantics and Specification Language (DSSSL) ISO/IEC DIS 10179.
7. Markup in compliance with this Recommendation should facilitate importing large sets of documents into a database. In fact, the extensive list of tags for patent bibliographic data will make it possible for database vendors to more easily distinguish various information elements with higher precision than has been possible in the past. This Recommendation does not address issues concerned with mapping generic identifiers to database fields.
8. This revision of ST.32 shall be referenced as version 3 (1995). This is to distinguish it from previous versions, which may still be used for data exchange but, if so, **must** be referenced as: version 1 (October 1987) or version 2 (September 1990). The relevant DTD may then be applied to a specific version for processing, parsing, etc. In addition it is possible to reference the DTD to be used as an attribute to any patent document, the default being the latest version of ST.32. It is, of course, recommended to update files to this latest version of ST.32 for data exchange.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.2

### DEFINITIONS

9. The expression **patent document** includes patents for invention, plant patents, design patents, utility certificates, utility models, documents of addition thereto and published applications therefor. (Refer also to WIPO ST.16: *Recommended Standard Code for the Identification of Different Kinds of Patent Documents*)

10. **Common text** refers to logical elements that could occur in any type of industrial property information or in any kind of document, for example, paragraphs, footnotes, subscripts, special characters, lists, embedded images, tables, chemical formulae, mathematical formulae, etc. Tags for common text data are specified and described in Part 1 (the DTD is in Annex B).

11. **Patent-specific content** refers to logical elements that ordinarily occur only in patent documents, for example, inventor's name, patent number, issuing authority, priority data, classification symbols, etc. In short, any of the information elements identified in WIPO Standard ST.9, *Recommendation Concerning Bibliographic Data on and Relating to Patents and SPCs*, as well as some others. Tags for patent bibliographic data are specified and described in Part 2 (the DTD is in Annex B).

12. **Markup** is defined as text that is added to the content of a document and that describes the structure and other attributes of the document in a non-system-specific manner, independently of any processing that may be performed on it. Markup includes document type definitions (DTDs), entity references, and descriptive markup (tags).

13. A **document type definition (DTD)** formally defines:

- the names of all the logical elements that are allowed in documents of a particular type;
- how often each logical element may appear;
- the permissible contents for each logical element;
- attributes (parameters) that may be used with each logical element;
- the correct sequence of logical elements;
- the names of all external and pre-defined entities that may be referenced in a document;
- the hierarchical structure of a document;
- the features used from the SGML standard.

A DTD defines the vocabulary of the markup for which SGML defines the syntax. The complete set of tags that may be found in a particular document are listed and formally defined in its DTD which must accompany the document. Each document in a large set of documents which share the same DTD, that is, documents which are of the same type, usually incorporates the DTD by reference.

14. An **entity** is content that is not part of the text stream in a document but which is incorporated into the text stream by reference to its name. In patent documents, for example, images are external entities. Entity references can also be used to code instances of characters not found in the 'declared' character set (see Character Sets below: paragraph 3)

15. **Tags** define a document's logical structure by labelling elements of the document's content using the generic identifiers declared in the DTD.

16. The **hierarchy** of SGML tags used in this Recommendation follows the general structure of a patent document. The level in the hierarchy is indicated by the appropriate SGML tag describing a generic logical element. A generic logical element is a component of the text such as the entire document, a specific sub-document, a paragraph, a list, etc. Each generic logical element is described by a start tag and end tag.

level	sgml tag (example)
Document	<PATDOC>
. Sub-document	<SDOXX>
. . Text Component (Paragraph)	<P>
. . . Text Element (Subscript)	<SB>
. . . . Character	
. . . End	</SB>
. . End	</P>
. End	</SDOXX>
End	</PATDOC>



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.3

17. International Standard ISO 8879:1986 defines an **abstract syntax** and a **reference concrete syntax**. The reference concrete syntax for SGML tags is as follows:

	Start Tag		End Tag	
This is	<B>	text	</B>	that will appear emphasized as bold ...

Where

<	is the opening delimiter for Start Tags (1 character)
</	is the opening delimiter for End Tags (2 characters)
>	is the closing delimiter for both Start Tags and End Tags (1 character)
B	is the generic identifier of this particular tag, defined in the DTD

A generic identifier is a name that identifies a generic logical element. The text between the start tag and the end tag is a specific instance of the generic logical element. Depending upon the generic identifier, parameters may be required. In the description of the various tags in this Recommendation, parameters are referred to as "attributes" in conformance with ISO practice. For an explanation of the relationship between reference concrete syntax and abstract syntax, see International Standard ISO 8879:1986.

18. The following is a brief example of SGML markup:

```
<PATDOC>
<SDOBI LA=EN>
<B100> (Minimum bibliographic tags would need to be added here)
</SDOBI>
<SDODE LA=EN>
<H LVL=0>FABRIC SOFTENER COMPOSITION</H>
<H LVL=1>TECHNICAL FIELD</H>
...
<H LVL=1>SUMMARY OF THE INVENTION</H>
<P N=11>The present invention relates to an aqueous fabric softener composition comprising:
<SL>
<LI>(A) from 1% to 50% by weight of ... cyclic amines of the formula
<EMI FILE="92102108" ID="2.1" HE=30 WI=55 TI=CF>
wherein n is 2 or 3, R<SB>1</SB> and
...
<LI>(B) from 3% to 20% by weight of (A)
...
</SL>
</SDODE>
</PATDOC>
```

In the example above <EMI FILE="92102108" ID="2.1" HE=30 WI=55 TI=CF> refers to a chemical structure which has been scanned as an image and which will be imbedded in the text at this point at the time of presentation. <PATDOC> and </PATDOC> mark the beginning and end of a patent respectively. The other tags in the example are explained below and there are more extensive examples in Annex D.

### CHARACTER SETS

19. The data content of the majority of documents, including patents, consists of data characters. The data characters could be in any language consisting of many types of character ('character' is used in its broadest sense here to include graphical symbols). In this recommendation only one coded character set is referenced: ISO 646. This is probably the most common **system independent** character set in use today. Characters not in this code set should be represented by public entity references—preferably those contained in ISO 8879—these are referenced in the DTD in Annex B. Note that other character sets and character entity references are possible. It is not recommended to use the code pages contained in WIPO ST.31 since these can lead to problems in data interchange, are not easily maintained and are not as commonly used and accepted as the ISO 646 code page.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.4

### REFERENCES

20. The following documents are of fundamental importance to this Recommendation:

International Standard ISO 8879:1986, *Information processing – Text and office systems – Standard Generalized Markup Language (SGML)*;

Technical Report ISO/IEC/TR 9573:1988(E) *Information processing – SGML support facilities – Techniques for using SGML*;

International Standard ISO 639:1988, *Code for the Representation of Names of Languages*.

International Standard ISO 646:1991, *Information Processing – ISO 7-bit coded character set for information interchange*.

WIPO Standard ST.3, *Recommended Standard Two-Letter Code for the Representation of States, Other Entities and Intergovernmental Organizations*;

WIPO Standard ST.9, *Recommendation Concerning Bibliographic Data on and Relating to Patents and SPCs*;

WIPO Standard ST.16, *Recommended Standard Code for the Identification of Different Kinds of Patent Documents*.

21. For additional information concerning SGML the following publications may be of interest (please note there is now a considerable amount of literature, books and periodicals, on SGML, as well as many user groups, the list below is only a small selection):

American National Standards Institute. *Electronic manuscript preparation and markup*. (Z39.59). Transaction Publishers : New Brunswick (USA) and London, 1991. ISBN 0887389457.

Association of American Publishers. Electronic Manuscript Series : *Author's guide to electronic manuscript preparation and markup; Reference manual on electronic manuscript preparation and markup; Markup of mathematical formulas; Markup of tabular material*. Dublin, Ohio : Electronic Publishing Special Interest Group (EPSIG), 1989.

Bryan, Martin. *SGML : an author's guide to the Standard Generalized Markup Language (SGML)*. Wokingham : Addison-Wesley, 1988. ISBN 0201175355.

Goldfarb, Charles F. *The SGML handbook*. Oxford : Oxford University Press, 1990. ISBN 0 19 853737 9.

Van Herwijnen, Eric. *Practical SGML. 2nd.ed.* Dordrecht : Kluwer Academic Publishers, 1994. ISBN 0792394348

### REQUIREMENTS OF THE RECOMMENDATION

22. Documents which conform to this Recommendation shall be marked up in conformance with:

- International Standard ISO 8879:1986, Information Processing – Text and Office Systems – Standard Generalized Markup Language (SGML);
- the DTD contained in Annex B.

23. Documents which conform to this Recommendation shall use the *reference concrete syntax* defined in International Standard ISO 8879:1986. See also Annex A: *SGML Declaration for Patent Documents*.

24. The DTD contained in Annex B shall be provided separately from the individual documents in the collection of documents to which they apply.

25. Each document to which the DTD in Annex B applies will incorporate the DTD by reference.

26. Reference to the DTD contained in Annex B shall be made by use of its "public name" which has been [will be] registered with the appropriate international authority and is declared below in Annex B.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.5

27. No document in conformance with this Recommendation shall refer to or incorporate by reference a DTD 1) for which a public name has not been registered with the appropriate international authority; 2) which does not appear in this Recommendation.

28. It may happen that some particularly unusual document contains some text or image portion(s) which cannot be rendered for the end user with adequate fidelity, in the judgement of the issuing authority, without the introduction of one or more logical elements not contained in Annex B. In that event:

- 28.1. The issuing authority shall provide constructive notice to end users that some documents contain exceptional elements. Where possible, the exact identification of such documents shall be provided, either as a list of document numbers or contiguous ranges of document numbers.
- 28.2. The issuing authority shall make every attempt to have the required logical element(s) introduced into the appropriate DTD contained in the appropriate section of this Recommendation, so that other issuing authorities may take advantage of them, and so that presentation system vendors may take account of them in preparing presentation software and hardware.
- 28.3. The issuing authority may, at its discretion, include the required logical element(s) in a supplementary DTD which is incorporated by reference into the DTD(s) that apply to the document(s) in question until such time as the elements are incorporated into this Recommendation.
  - 28.3.1. A supplementary DTD shall not be incorporated directly into the document(s) to which it applies.
  - 28.3.2. A supplementary DTD shall not contain any duplicate logical elements included in the DTD contained in ST.32, Annex B.
  - 28.3.3. If a supplementary DTD is provided, constructive notice shall be given to the end user to that effect.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.6

### PART 1: SGML MARKUP FOR COMMON TEXT

The tags described in this part of ST.32 indicate text portions that are not specific to any one type of industrial property information and may therefore be used in any document conforming to ST.32.

#### GENERAL TEXT

TABLE OF SGML TAGS		
TAG	NAME	DESCRIPTION
<B>	Bold	Indicates the beginning of text to be highlighted at the time of presentation by using a bold typestyle. An end tag is required.
<BAI>	BAIkaku	Indicates Japanese text portion to be highlighted using an expanded font. An end tag is required.
<BCHG>	Beginning of a CHanGe	Indicates the beginning of a change in bibliographic data only. Attributes required. It is an empty element which should be followed by <ECHG>.
 	line BReak	Indicates the position in the text at which a line break occurs. No end tag is necessary.
<CHF>	CHaracter Fraction	Indicates a character construct consisting of two or more characters in a 'fraction type' construct. Use with the <CHFBR> tag. An end tag is required.
<CHFBR>	CHaracter Fraction BReak	Indicates the break point in a character 'fraction' construct consisting of two or more characters in a 'fraction type' construct. No end tag is necessary.
<CHG>	CHanGe	Indicates the beginning of a change (not in bibliographic data). Attributes required. An end tag is required
<DP>	Document Page	Indicates the beginning of a new page. The attribute N= is required. No end tag is necessary.
<ECHG>	End of a CHanGe	Indicates the end of a change in bibliographic data only. Attributes required. It is an empty element which should be preceded by <BCHG>.
<FLA>	FLoating Accents	This indicates a character enhanced with a particular attributing feature. An end tag is required.
<FLAC>	FLoating ACcents	This indicates the attributing feature in a floating accent construct. No end tag is necessary.
<FOO>	FOOtnote	Indicates a footnote. Attributes required. An end tag is required.
<FOR>	FOotnote Reference	Indicates a reference to a previous footnote. Attributes required. An end tag is required.
<H>	Heading level	Indicates a separate text portion that precedes text parts, for example, paragraphs. An end tag is required.
<HAN>	HANkaku	Indicates Japanese text portion to be highlighted using a compressed font. An end tag is required.
<I>	Italic	Indicates the beginning of text to be highlighted at the time of presentation by using an italic typestyle. An end tag is required.
<LTL>	LiTeraL	Indicates the beginning of text in which the space, indents, line endings, etc., should be preserved as keyed in the original document. An end tag is required.
<O>	'Over' embellishments	Indicates the beginning of text to be covered by an over, or mid, embellishment of a particular designated style (attribute) at the time of presentation. An end tag is required.
<P>	Paragraph	Indicates a text portion known as a paragraph and implies that the text will begin on a new line. No end tag is necessary.
<PATDOC>	PATent DOCument	Indicates the beginning of a patent document instance (file). An end tag is required.
<PC>	Paragraph Continuation	Indicates a continuation of an interrupted paragraph. No end tag is necessary.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.7

TABLE OF SGML TAGS		
TAG	NAME	DESCRIPTION
<PCL>	Page CoLumn	Indicates the beginning of a new column. The attribute N= is required. No end tag is necessary.
<PLN>	Page LiNe	Indicates the beginning of a new line. The attribute N= is required. No end tag is necessary.
<SB>	SuBscript	Indicates the beginning of text which is to be placed as a subscript to the preceding text outside mathematical formulae. An end tag is required.
<SDOxx>	Sub-DOcument	Indicates the beginning of a sub-document whose identity (xx) is included in the tag. An end tag is recommended.
<SP>	SuPerscript	Indicates the beginning of text which is to be placed as a superscript to the preceding text outside mathematical formulae. An end tag is required.
<TXF>	TeXt Frame	This indicates a rectangular area of text of a page. No end tag is necessary.
<U>	Under embellishment	Indicates the beginning of text to be highlighted with an under embellishment of a particular style (attribute) at the time of presentation. An end tag is required.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.8

TABLE OF ATTRIBUTES		
ATTRIBUTE	NAME	DESCRIPTION
ALIGN	ALIGN	Alignment of data.
CY	CountrY code	Indicates country code based on ST.3
DATE	DATE	Date: in the format YYYYMMDD
DNUM	Document NUMber	Identifier of document (publication or application number)
DTD	Document Type Definition	Version number of the DTD.
FILE	File name	The file name of a patent document or image file.
FN	Footnote Number	Unique identification for a footnote
FNREF	Foot Note REFerence	Unique identification for a footnote reference
FONT	FONT	Font used in text frames
FR	FRame	Frame number within a page
HE	HEight	Height of images in mm
ID	IDentifier	Has various parameters depending on tag
KIND	KIND	Kind of document based on ST.16
LA	LAnguage	Indicates sub-document language
LS	Line Spacing	Line spacing in text frames
LVL	LeVeL	Indicates the level of a heading
LX	X coordinate	X coordinate of image in 1/10mm
LY	Y coordinate	Y coordinate of image in 1/10mm
N	Number	Indicates numbers for paragraphs, pages, etc.
POS	POSition	Indicates various parameters depending on the tag
SIZE	SIZE	Font size in text frames
STATUS	STATUS	Indicates status of patent document and/or change
STYLE	STYLE	Indicates the style of various attributes, for example, over characters, etc.
TYPE	TYPE	Type of embellishment
WI	WIdth	Width of images in mm



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.9

### SGML TAGS: DESCRIPTION AND USAGE

#### DOCUMENT STRUCTURE

##### 1. <PATDOC> : PATent DOCument

This is the mandatory identifier with which every patent document must start. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

**FILE=***name* Where 'name' is the name of the patent document file, which contains the document instance.

**STATUS=** Status of the patent document, eg. contains changes, republished, deleted, withdrawn, etc.

**Note:** It is recommended that the following optional attributes should be used **only** when the mandatory tags, giving document identification, contained in the <SDOBI> sub-document, are not used. This may be the case, for example, when only partial information is exchanged between offices.

**CY=***xx* Where *xx* is the country or organisation, according to WIPO ST.3, publishing or issuing the patent document. <B190>

**DATE=***YYYYMMDD* Date of publication. <B140>

**DNUM=***n* Where *n* is the document number, usually the publication number but may also be the application number. <B110> or <B210>

**KIND=***xx* Where *xx* is the kind of patent document code taken from WIPO ST.16. <B130>

**DTD=***n* Where *n* is the version number of the DTD applied to a particular patent document. The default is ST.32 Version 3 (1995).

#### DTD Syntax:

```
<!ELEMENT patdoc - -      (sdo bi,(sdo ab*&sdo de?&sdo cl*&sdo dr?&sdo sr?))
                             +(%floats;)
>
<!--ATTLIST patdoc cy      CDATA      #IMPLIED      -- Country, organis. St.3      --
                             dnum      CDATA      #IMPLIED      -- Identification number      --
                             date      NUMBER    #IMPLIED      -- date of publication      --
                             file      CDATA      #IMPLIED      -- file identification      --
                             kind      CDATA      #IMPLIED      -- Kind of patent St.16      --
                             status     CDATA      #IMPLIED      -- Status of the patent doc.  --
                             dtd        NUTOKEN   #IMPLIED      -- Version NUMBER of DTD    -->
```

#### Examples:

```
<PATDOC><SDOBI>Here is a WIPO Patent Document (other tags would normally be included)</SDOBI></PATDOC>
<PATDOC FILE=92101123 CY=EP DATE=19921212 DNUM=0500111 KIND=A1>
<SDOBI>Here is a European Patent Office application with a search report (A1)(other tags would normally be
included)</SDOBI></PATDOC>
```

##### 2. <SDOxx> : Sub-DOCument tags

This is the mandatory identifier with which every sub-document must start. An end tag, although optional, is recommended.

Where *xx* = sub-document identifier



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.10

Possible sub-documents are:

<SDOAB>	ABstract
<SDOBI>	Bibliographic data
<SDOCL>	CLaims
<SDODE>	DEscription
<SDODR>	DRawings
<SDOSR>	Search Report

Required Attribute(s):

None.

Optional Attribute(s):

<i>CY</i> = <i>country code</i>	Indicates the country where the sub-document "CLAIMS" especially relate to, abbreviated in accordance with WIPO Standard ST.3 country code.
<i>LA</i> = <i>language code</i>	Indicates language of the sub-document in accordance with International Standard ISO 639:1988.
<i>STATUS</i> =	Status of the patent sub-document, eg. contains changes, republished, deleted, withdrawn, etc.

DTD Syntax:

```
<!ELEMENT sdobi - o (B000?,B100,B200?,B300?,B400?,B500?,B600?,B700?,B800?,
                      B900?) +(bchg|echg) -- Bibliographic data -->
<!ELEMENT sdoab - o ((h|p|pc|img;)+) -- Abstract -->
<!ELEMENT sdodr - o (emi+) -- Drawings -->
<!ELEMENT sdode - o (h|p|pc|img;)+ -- Description -->
<!ELEMENT sdocl - o (h|p|lst;)+ -- Claims -->
<!ELEMENT sdosr - o ((B510?,B520?,B560?,B580?)(emi+)) -- Search report -->
<!ATTLIST (sdobi|sdoab|sdode|sdocl|sdodr|sdosr)
          la NAME #IMPLIED -- language(ISO 639) --
          cy NAME #IMPLIED -- country code --
          status CDATA #IMPLIED -- Status of the sub-doc.-->
```

Examples:

```
<SDOBI>
<B500><B542>Here is bibliographic data – it should contain other tags also</B500>
</SDOBI>
<SDOCL LA=F>
<OL>
<LI>Dispositif de reséquencement (RU) pour un noeud d'un système de commutation de cellules, chaque cellule étant
constituée d'un nombre variable de sous-cellules ayant une longueur fixe, ce noeud comportant .....
<LI> ...
</OL>
</SDOCL>

<SDOAB LA=D>
<P>Die vorliegende Erfindung betrifft Impfstoffe auf Basis von Bovinen Herpesviren des Typs 1 (BHV-1) die Änderungen in
Bereichen ihres Genoms enthalten, die für nicht-essentielle Teile essentieller Proteine kodieren. Mit Hilfe dieser Impfstoffe
können geimpfte von nicht-geimpften Rindern unterschieden werden. Die Erfindung betrifft ferner Verfahren zur Isolierung
und Herstellung der geänderten BHV-1 Stämme, Isolierung und Herstellung der geänderten Proteine und Peptide.
</SDOAB>

<SDOCL LA=D CY=AT>
<OL>
<LI>Mikroorganismus DSM 7329 und DSM 7330.
<LI>Verfahren zur Herstellung von L-j-Aminosäuren durch enzymatische Umsetzung eines D-, L- und/oder D,L-5-
monosubstituierten Hydantoin und/oder einer D-, L- und/oder D,L-N-Carbamoyl-j-aminosäure,<BR>
...
</OL>
</SDOCL>
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.11

### 3. <CHG> : CHanGe

This indicates data which has been 'changed' (it could also indicate the original text). An end tag is required.

Required Attribute(s):

DATE=YYYYMMDD Indicates the date on which the text was changed.

STATUS= Indicates the status of the change, the value of this attribute has been left open but one letter codes are recommended, eg. A = amended text, D = deleted text, O = Original text.

Optional Attribute(s):  
None

DTD Syntax:

```
<!ELEMENT chg    - - (h|p|pc|(%ptext;))*    -- Change text          -->
<!ATTLIST chg   date    NUMBER          #REQUIRED    -- Date of change text    --
               status  CDATA          #REQUIRED    -- Status of the change   -->
```

Example:

```
<P><CHG DATE=19950321 STATUS=A>This data was amended on 21 March 1995</CHG>
```

### 4. <BCHG> : Beginning of a CHanGe

This indicates bibliographic data which has been 'changed' (it could also indicate the original text). It is an empty element – it should be followed by <ECHG>.

Required Attribute(s):

DATE=YYYYMMDD Indicates the date on which the text was changed.

STATUS= Indicates the status of the change, the value of this attribute has been left open but one letter codes are recommended, eg. A = amended text, D = deleted text, O = Original text.

Optional Attribute(s):  
None

DTD Syntax:

```
<!ATTLIST bchg  date    NUMBER          #REQUIRED    -- Date data changed      --
               status  CDATA          #REQUIRED    -- Status of the change   -->
```

Example:

```
<B235><BCHG DATE=19960321 STATUS=A><DATE>19960321</DATE><ECHG></B235>
```

### 5. <ECHG> : End of CHanGe

This indicates the end of data which has been 'changed' in bibliographic data (it could also indicate the original text). It is an empty element – it should be preceded by <BCHG>.

Required Attribute(s):  
None.

Optional Attribute(s):  
None.

DTD Syntax:

```
<!ELEMENT echg    - o EMPTY                -- End of changed bibliographic data -->
```

Example:

```
<B235><BCHG DATE=19960321 STATUS=A><DATE>19960321</DATE><ECHG></B235>
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.12

### 6. <H> : Headings

This indicates levels of headings which may be treated differently. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

LVL=*n* Indicates the level of the heading

ALIGN= Indicates the alignment of the header which may be centre, left, right – left is the default.

DTD Syntax:

```
<!ELEMENT h      - - (%ptext;)+          -- Header          -->
<!ATTLIST h      lvl NUMBER #IMPLIED      -- Header level    --
                  align (%align;) "left"   -- alignment       -->
```

*Examples:*

<H>This is a default heading</H>

<H LVL=0>This is the title heading</H>

<H LVL=1>This is a sub-section heading</H>

### 7. <P> : Paragraphs

This indicates a text portion commonly known as a paragraph. No end tag is necessary.

Required Attribute(s):  
None.

Optional Attribute(s):

N=*nnnnnn* Consisting of a 6-digit sequence number indicating every paragraph in a document or sub-document. Leading zeros may be dropped.

ALIGN= Indicates the alignment of the paragraph which may be centre, left, right – left is the default.

*Example:*

<P>First text paragraph . <P>Second text paragraph.

<P N=1>First text paragraph.<P N=2>Second text paragraph.

DTD Syntax:

```
<!ELEMENT p      - o (%ptext;)+          -- Paragraph elements -->
<!ATTLIST p      n  NUMBER #IMPLIED      -- Reference number   --
                  align (%align;) "left"  -- alignment          -->
```

### 8. <PC> : Paragraph Continuation

This indicates an interruption in a paragraph, for example, by a figure, table, etc. The existing paragraph should be continued. No end tag is necessary.

Required Attribute(s):  
None.

Optional Attribute(s):  
None.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.13

DTD Syntax:

```
<!ELEMENT pc      - o (%ptext;)+          -- Paragraph continuation      -->
```

*Example:*

```
<P N=12>Here starts a new text paragraph, it contains an EMI:  
<EMI ID='2.1' HE=10 WI=20 TI=CF>  
<PC>and continues without paragraph formatting ...
```

### 9. <BR> : BReak

This indicates a line break in general text. No end tag is necessary. Whether and how the break tag is interpreted at the time of presentation is not specified in this Recommendation. Note that this tag should not be used in mathematical formulae where <BREAK> is used.

Required Attribute(s):  
None.

Optional Attribute(s):  
None.

DTD Syntax:

```
<!ELEMENT br      - o EMPTY                -- Line break                -->
```

*Example:*

This line must break here and also break here but that's all for this paragraph.	<P>This line must break here and also break here but that's all for this paragraph.
--	--

*Note:* the above example assumes that the break tag is interpreted at the time of presentation as forcing a line break in the text. Other interpretations are possible.

### 10. <FOO> : FOOtnotes

This tag identifies a text portion which is the contents of a footnote. The footnote should be inserted in the text stream at the point where it is first referred to. The presentation software will cause the footnote to appear, usually, at the bottom of the page. An end tag is required.

Required Attribute(s):

FN=nnnn.nn	Consisting of a 4-digit sequence number indicating the page number of the original document on which the footnote occurred and a 2-digit sequence number indicating the sequence of footnotes on that particular page. Optionally, it may be replaced by a sequential numbering of footnotes within a document, in which case use FN=nnnnnnn. Either form is valid. It must be a unique reference in the document. Leading zeros may be dropped.
------------	--

Optional Attribute(s):  
None

DTD Syntax:

```
<!ELEMENT foo      - - (%ptext;)+          -- Footnotes                -->  
<!ATTLIST foo      fn NUTOKEN #REQUIRED    -- Footnote id.             -->
```

*Example:*

```
... text *<FOO FN='10.1'>* This is the text of the footnote – to be placed at the foot of a page – note that the asterisk "*" is  
also part of this footnote</FOO> ....
```

*Note:* The indicator, in this case "\*", is NOT inserted by application software, as is normal, because in patent documentation it is often not possible to change data submitted by a patent applicant.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.14

### 11. <FOR> : F<sup>o</sup>otnote Reference

This indicates from which point(s) in a document a footnote is referenced. An end tag is required.

Required Attribute(s):

FNREF=nnnn.nn

Consisting of a 4-digit sequence number indicating the original page number on which the footnote occurred and a 2-digit sequence number indicating the sequence of footnotes on that particular page. This attribute should contain exactly the same value as the attribute of the referenced footnote (FN=). Optionally, it may be replaced by a sequential numbering within a document, in which case use FNREF=nnnnnn. Either form is valid. Leading zeros may be dropped.

Optional Attribute(s):

None

DTD Syntax:

```
<!ELEMENT for      - - (%ptext;)+          -- Footnote reference      -->
<!ATTLIST for      fnref  NUTOKEN  #REQUIRED -- Footref id.          -->
```

Example:

text<FOR FNREF='10.1'>\*/FOR> ...

**Note:** At the time of presentation this should result in the SAME footnote as first appeared on page 10 of the original document being produced on the page where <FOR> is used. This may occur, for example, if there is a page break during processing between the two footnote references which were originally on the same page.

### TEXT 'HIGHLIGHTING' MARKUP

**Note:** The following codes: <B>, <BAI>, <HAN>, <I>, <O>, <U>, <SB> and <SP> may be regarded as tags which can be used to mark characters, words, phrases, etc. as 'highlighted', that is emphasised in some way. In other instances they may be replaced by a 'pure' SGML tag such as <HP<sub>n</sub>>, highlighted phrase, where n is the numeric value assigned to a particular form of highlighting which is determined at the time of presentation (bold, italic, etc.). However, for patent documents, for the purposes of readability, it is recommended that the codes below be used instead. (Highlighted phrase identifiers are not contained in the DTD).

### 12. <B> : B<sup>o</sup>ld

This indicates a text portion to be highlighted as bold. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT b      - - (%ptext;)+ -(b)          -- Bold typeface      -->
```

Example:

**This text is bold**

<B>This text is bold</B>

### 13. <BAI> : B<sup>a</sup>Ikaku

This indicates a Japanese text portion to be highlighted using an expanded font. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):  
None.

### DTD Syntax:

```
<!ELEMENT bai    - - (%ptext;)+ -(bai|han)      -- Expanded font      -->
```

14. <HAN> : HANkaku

This indicates a Japanese text portion to be highlighted using a compressed font. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):  
None.

### DTD Syntax:

```
<!ELEMENT han    - - (%ptext;)+ -(han|bai)      -- Compressed font      -->
```

15. **<I> : Italic**

This indicates a text portion to be highlighted as italic. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):  
None.

### DTD Syntax:

```
<!ELEMENT i      - - (%ptext;)+ - (i)          -- Italics          -->
```

*Example:*

[illegible]

16. <O> : 'Over' embellishments

The over-character tag is used to identify parts of text over which special accents or diacritical marks are to be placed.

*Note:* the 'mark' could also be placed mid character. In mathematical formulae use <OV>. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

POS= The position attribute defines the position of the mark and takes one of the values: above or mid. The default value is above.

**STYLE=** The style attribute defines the style of the mark. It takes one of the values: single, double, triple, dash, dots, or bold. The default value is single.

TYPE= The type attribute defines the type of the mark to be used. It takes one of the values: dot, dotdot, dot3, dot4, tie, tiebrace, hat, hacek, acute, grave, cedil, ring, macron, ogonek, dblac, breve, tilde, vec, rvec, dyad, circle, caret, prime, dprime, plus, none, bar. The default value is bar.

*Note:* Not all combinations of type and style attribute values would normally be used, eg `type=tilde, style=dots`.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.16

### DTD Syntax:

```
<!ELEMENT o      - - (%ptext;)+ -(o|ov)      -- 'Over' embellishment      -->
<!ATTLIST o      pos      (above|mid) "above"  -- position of 'over' embellishment  --
                  type      (%type;)  "bar"     -- types of embellishment(default bar) --
                  style      (%style;)  "single" -- Line style      (default single)  -->
```

### Examples:

This text has a single continuous bar over the whole sentence

<O>This text has a single continuous bar over the whole sentence</O>

-----  
The word example is covered by a dashed bar

The word <O STYLE=DASH>example</O> is covered by a dashed bar.

### 17. <U> : Under embellishments

The under-character tag is used to identify parts of text under which special accents or diacritical marks may be placed – typically an underscore. In mathematical formulae use <OV POS=BELOW>. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

STYLE= The style attribute defines the style of the mark. It takes one of the values: single, double, triple, dash, dots, or bold. The default value is single.

TYPE= The type attribute defines the type of the mark to be used. It takes one of the values: dot, dotdot, dot3, dot4, tie, tiebrace, hat, hacek, acute, grave, cedil, ring, macron, ogonek, dblac, breve, tilde, vec, rvec, dyad, circle, caret, prime, dprime, plus, bar. The default value is bar.

**Note:** Not all combinations of type and style attribute values would normally be used, eg type=tilde, style=dots.

### DTD Syntax:

```
<!ELEMENT u      - - (%ptext;)+ -(u|ov)      -- Underscore embellishment      -->
<!ATTLIST u      type      (%type;) "bar"     -- types of embellishment(default bar) --
                  style      (%style;) "single" -- Line style      (default single)  -->
```

### Examples:

This text has a single continuous underscore for the whole sentence.

<U>This text has a single continuous underscore (bar) for the whole sentence . </U>

The word example is underscored with a double bar.

The word <U STYLE=DOUBLE>example</U> is underscored with a double bar.

### 18. <SB> : SuBscript

This indicates a text portion to be placed as a subscript (inferior) to the immediately preceding character. An end tag is required. See also the <SUB> tag used in mathematical formulae.

Required Attribute(s):  
None.

Optional Attribute(s):

POS= The position attribute takes one of the values: pre, mid or post, post being the default.



### DTD Syntax:

```
<|ELEMENT sb      - ((%hil;)|(#PCDATA))* -(fla) -- Subscript      -->
<|ATTLIST (sp|sb) pos (PRE|MID|POST) "POST"    -- Position (default post) -->
```

*Example:*

$$\text{H}_2\text{O} \qquad \text{H}_{\text{SB}^2/\text{SB}}\text{O}$$

19. <SP>: **SuPerscript**

This indicates a text portion to be placed as a superscript (superior) to the immediately preceding character. An end tag is required. See also the <SUP> tag used in mathematical formulae.

Required Attribute(s):  
None.

Optional Attribute(s):

POS= The position attribute takes one of the values: pre, mid or post, post being the default.

### DTD Syntax:

```
<!ELEMENT sp - - ((%hil;)|(#PCDATA))* -(fla) -- Superscript -->
<!ATTLIST (sp|sb) pos (PRE|MID|POST) "POST" -- Position (default post) -->
```

*Example:*

$$X^{n-1} \qquad X_{<SP>n-1</SP>}$$

## MISCELLANEOUS

20. **<CHF>** : **C**haracter **F**raction constructs

This indicates 'fraction' constructs in general text. The alignment of 'numerator' and 'denominator' is centred by default. It should be used only in general text. An end tag is required.

See also the ‘true’ fraction tag, `<FRAC>`, used in mathematical formulae.

Required Attribute(s):  
None.

Optional Attribute(s):

**ALIGN=** Indicates the alignment of the numerator and/or denominator, which may be centre, left, right – centre is the default.

*Example:* (See below)

21. **<CHFBR> : CHaracter Fraction BReak**

This identifies the start of a character fraction 'denominator'. No end tag is necessary.

Required Attribute(s):  
None.

Optional Attribute(s):

**STYLE=** The style attribute defines the style of the mark preceding the character fraction denominator. It takes one of the values: `single`, `double`, `triple`, `dash`, `dots`, or `bold`. The default value is `single`.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.18

**TYPE=** The type attribute defines the type of the mark to be used preceding the character fraction denominator. It takes one of the values: dot, dotdot, dot3, dot4, tie, tiebrace, hat, hacek, acute, grave, cedil, ring, macron, ogonek, dblac, breve, tilde, vec, rvec, dyad, caret, circle, plus, prime, dprime, bar, none. The default value is bar.

**Note:** Not all combinations of type and style attribute values would normally be used, eg type=tilde, style=dots.

**DTD Syntax:**

```
<!ELEMENT chf - - (((#PCDATA)|(%hil;))+, chfbr) -- character fraction -->
<!ATTLIST chf align (%align;) "centre" -- alignment --
<!ELEMENT chfbr - o (((#PCDATA)|(%hil;))+ -- character fraction break -->
<!ATTLIST chfbr type (%type;) "bar" -- types of embellishment(default bar) --
style (%style;) "single" -- Line style (default single) -->
```

**Examples:**

$$\frac{2x}{3xy}$$

<CHF>2x<CHFBR>3xy</CHF>

20  
D

<CHF>20<CHFBR TYPE=NONE>D</CHF>

### 22. <FLA> : Floating Accents

This indicates a character, or characters, enhanced with a particular attributing feature(s). It enables "composite" characters not in a character set to be composed from characters and character entity references. It should be used in combination with the <FLAC> tag. An end tag is required.

**Required Attribute(s):**  
None.

**Optional Attribute(s):**  
None.

**DTD Syntax:**

```
<!ELEMENT fla - - (((#PCDATA)|(%hil;))+, flac) -- Floating accent construct -->
```

### 23. <FLAC> : Floating ACcent

This indicates the start of a floating accent to be placed above, mid, or below a base character, or characters, above is the default. It enables "composite" characters not in a character set to be composed from characters and character entity references. It should be used in combination with the <FLA> tag. No end tag is necessary.

**Required Attribute(s):**  
None.

**Optional Attribute(s):**

**POS=** The position attribute takes one of the values: above, mid or below, above being the default.

**DTD Syntax:**

```
<!ELEMENT flac - o (((#PCDATA)|(%hil;))+ -- Floating accent (upper part) -->
<!ATTLIST flac pos (ABOVE|MID|BELOW) "ABOVE" -- Position (default above) -->
```

**Examples:**

Å <FLA>A<FLAC>&circ;</FLA>

a <FLA>a<FLAC>&bull;</FLA>



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.19

### 24. <LTL> : LiTeraL text

Indicates the beginning of text in which the space, indents, line endings, etc., should be preserved as keyed in the original layout. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

WI=nnn Width: 3-digit expression in millimetres.

DTD Syntax:

```
<!ELEMENT ltl - - CDATA -- Literal text -->
<!ATTLIST ltl wi NUMBER #IMPLIED -- Width in mm -->
```

Example:

This text has a special layout which must be preserved exactly as entered.	<LTL> This text has a special layout which must be preserved exactly as entered. </LTL>
--	---

### PAGE STRUCTURE TAGS

The following tags are specific to patent document processing and are to be used to indicate page structure in order to allow exact citation of pages, page numbers, columns and lines. For post processing of the data these tags can, of course, be ignored if required.

### 25. <TXF> : TeXt Frame

This indicates an area of text within a page of a document. An end tag is not allowed – it is an EMPTY element.

Required Attribute(s):

FR=nnnn Consisting of a 4-digit sequence number within a page.

HE=nnn Height: 3-digit expression in millimetres.

WI=nnn Width: 3-digit expression in millimetres.

Optional Attribute(s):

LX=nnnn 4-digit X-coordinate expressed in 1/10 millimetres referencing to the top left corner of the page.

LY=nnnn 4-digit Y-coordinate expressed in 1/10 millimetres referencing to the top left corner of the page.

FONT=name The font used in the text frame, eg Courier, Helvetica, etc.

SIZE=nn A 2 digit number for the point size of the font.

LS=n Where n is the number (may be decimal) of the line spacing within the text frame.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.20

### DTD Syntax:

<!ELEMENT txf	- o EMPTY	-- Text frame	-->
<!ATTLIST txf	fr NUTOKEN #REQUIRED	-- Txf identity	-->
	he NUMBER #REQUIRED	-- Height in mm	-->
	wi NUMBER #REQUIRED	-- Width in mm	-->
	lx NUMBER #IMPLIED	-- X-coord 1/10 mm	-->
	ly NUMBER #IMPLIED	-- Y-coord 1/10 mm	-->
	font CDATA #IMPLIED	-- Font name	-->
	size NUMBER #IMPLIED	-- Font point size	-->
	ls NUTOKEN #IMPLIED	-- Line spacing	-->

### Example:

```
<PATDOC CY=JP>
<SDOAB>
<TXF FR=0001 HE=080 WI=080 LX=0200 LY=1800>
<P>Japanese Patent Office abstract...
</SDOAB></PATDOC>
```

## 26. <DP> : Document Page

This indicates the beginning of a page. No end tag is necessary.

*Note:* The use of this tag is optional since it is a formatting tag. It may be discarded at the time of presentation. However, it may be useful for patent documents where page citation is common and may need to be preserved in electronic document systems.

### Required Attribute(s):

N=nnnn 4-digit number being the page number per document.

### Optional Attribute(s):

None.

### DTD Syntax:

<!ELEMENT dp	- o EMPTY	-- Document page break	-->
<!ATTLIST dp	n NMTOKEN #REQUIRED	-- Document page number	-->

### Example:

```
<DP N=6>This is the start of page 6
```

## 27. <PCL> : Page CoLumn

This indicates the beginning of a column in a page. It should always be preceded by <TXF> tag. No end tag is necessary.

*Note:* The use of this tag is optional since it is a formatting tag. It may be discarded at the time of presentation. However, it may be useful for patent documents, where column citation is used, and may need to be preserved in electronic document systems.

### Required Attribute(s):

N=nnnn 4-digit number being the column number.

### Optional Attribute(s):

None.

### DTD Syntax:

<!ELEMENT pcl	- o EMPTY	-- Page column	-->
<!ATTLIST pcl	n NMTOKEN #REQUIRED	-- Page column number	-->

### Example:



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.21

<PCL N=2> This is the start of column 2

### 28. <PLN> : Page LiNe

This indicates the beginning of a line within a page. It should always be preceded by a <TXF> tag. No end tag is necessary.

*Note:* The use of this tag is optional since it is a formatting tag. It may be discarded at the time of presentation. However, it may be useful for patent documents, where line number citation is common, and may need to be preserved in electronic document systems.

Required Attribute(s):

N=nnnn 4-digit number being the line number.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT pln      - o EMPTY          -- page line      -->
<!ATTLIST pln      n  NMTOKEN  #REQUIRED -- page line number -->
```

*Example:*

<PLN N=15> This is the start of line 15



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.22

---

[Blank page]



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.23

### LISTS

TABLE OF SGML TAGS AND ATTRIBUTES		
TAG	NAME	DESCRIPTION
<DD>	Definition Description	Indicates a text portion which is the description of a tagged item in a definition list. No end tag is necessary.
<DL>	Definition List	Indicates a text portion to be displayed as a list, each item comprising a term followed by a description. An end tag is required.
<DT>	Definition Term	Indicates a text portion which is the term in a definition list. No end tag is necessary.
<LI>	List Item	Indicates the beginning of an item which forms part of a simple, ordered or unordered list. No end tag is necessary.
<OL>	Ordered List	Indicates a text portion to be displayed as a list, each item being identified by a sequential number or letter. An end tag is required.
<SL>	Simple List	Indicates a text portion to be displayed as a simple list. An end tag is required.
<UL>	Unordered List	Indicates a text portion to be displayed as a list, each item identified by a symbol which is defined in a required attribute (ST). An end tag is required.
ATTRIBUTE	NAME	DESCRIPTION
COMPACT	COMPACT	Indicates if lists should be processed as compact
LEVEL	LEVEL	Nesting level of a list
NUMSTYLE	NUMSTYLE	Numeric style of a list
PREFIX	PREFIX	Prefix for each list item
ST	STyle	Style (character or graphic) of an unordered list item
TSIZE	Term SIZE	Indicates the horizontal space allowed for definition terms plus gutter space

### SGML TAGS: DESCRIPTION AND USAGE

#### 29. <DL> : Definition List

This indicates a text portion known as a definition or glossary list. A definition list contains one or more items, each followed by its description. The items are identified by the <DT> identifier and the description by the <DD> identifier. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

**TSIZE=** This attribute is used to specify the indent to be used for the definition description. It is normally larger than the maximum width of the terms.

**COMPACT=** Used to indicate when no blank lines are to be left between definition items at the time of presentation.

DTD Syntax:

```
<!ELEMENT dl      - - (dt,dd)+          -- Definition list          -->
<!ATTLIST dl      tsize      NUMBER #IMPLIED -- Term size attribute      --
                  compact    (compact) #IMPLIED -- Spacing between items    -->
```

*Example: (see below)*



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.24

### 30. <DT> : Definition Term

This indicates a term in a definition list. No end tag is necessary.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT dt      - o (%ptext; )                -- Definition term                -->
```

*Example:* (see below)

### 31. <DD> : Definition Description

This indicates the description of an item (term) marked <DT> in a definition list. No end tag is necessary.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT dd      - o ((%ptext; )|p)+           -- Definition description           -->
```

*Example:*

In this example it is assumed that none of the terms exceed the length that may have been specified as default for such lists.

EPO	European Patent Office	<DL> <DT>EPO
JPO	Japanese Patent Office	<DD>European Patent Office <DT>JPO
USPTO	United States Patent and Trademark Office	<DD>Japanese Patent Office <DT>USPTO <DD>United States Patent and Trademark Office </DL>

### 32. <OL> : Ordered List

This indicates a portion of structured text known as a list. An ordered list will have a sequence of numbers or letters generated at the time the document is created, not at the time of presentation, to indicate the relative position in the list of each item. Lists may be nested. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

COMPACT=	Used to indicate when no blank lines are to be left between items at the time of presentation.
LEVEL=	Used to indicate the nesting level of a list.
NUMSTYLE=	Used to indicate the numeric style of a list.
PREFIX=	Used to indicate prefix for each list item.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.25

DTD Syntax:

```
<!ELEMENT ol      - - (li)+           -- Ordered list           -->
<!ATTLIST ol      compact (compact) #IMPLIED -- Spacing between items --
                  level   NUMBER   #IMPLIED -- Nesting level of list  --
                  numstyle CDATA    #IMPLIED -- Numbering style        --
                  prefix   CDATA    #IMPLIED -- Prefix for each list item -->
```

*Example:* (see below)

### 33. <SL> : Simple List

This indicates a portion of structured text known as a list. A simple list will not have anything preceding the list items to indicate them as such. Lists may be nested. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

COMPACT= Used to indicate when no blank lines are to be left between items at the time of presentation.

LEVEL= Used to indicate the nesting level of a list.

DTD Syntax:

```
<!ELEMENT sl      - - (li)+           -- Simple list           -->
<!ATTLIST sl      compact (compact) #IMPLIED -- Spacing between items --
                  level   NUMBER   #IMPLIED -- Nesting level of list  -->
```

*Example:* (see below)

### 34. <UL> : Unordered List

This indicates a portion of structured text known as a list. An unordered list will have symbols generated at the time of presentation to indicate each item. Lists may be nested. An end tag is required.

Required Attribute(s):

ST= This attribute is followed by an identifier for the character or the graphic symbol required to indicate each separate item in the list.

Optional Attribute(s):

COMPACT= Used to indicate when no blank lines are to be left between items at the time of presentation.

LEVEL= Used to indicate the nesting level of a list.

DTD Syntax:

```
<!ELEMENT ul      - - (li)+           -- Unordered list           -->
<!ATTLIST ul      st      NMTOKEN  #REQUIRED -- Ulist symbol            --
                  level   NUMBER   #IMPLIED -- Nesting level of list  --
                  compact (compact) #IMPLIED -- Spacing between items  -->
```

*Example:* (see below)

### 35. <LI> : List Item

This indicates an item of a list, <OL>, <SL> and <UL>. No end tag is necessary.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.26

Required Attribute(s):  
None.

Optional Attribute(s):  
None.

DTD Syntax:

```
<!ELEMENT li      - o ((%ptext;)|p)+          -- List item          -->
```

*Examples:*

Text

First item in a simple list.

Second item.

more text.

Text<SL><LI>First item in a simple list. <LI>Second item.</SL>more text.

Text

1. First item in a compact ordered list.  
2. Second item.  
more text.

Text<OL COMPACT=COMPACT><LI>First item in a compact ordered list.<LI>Second item.</OL>more text.

Text

- First item in an unordered list with 'bullets'.
- Second item.

more text.

Text

```
<UL ST="&bull;">  
<LI>First item in an unordered list with 'bullets'.  
<LI>Second item.  
</UL>  
more text
```

*Note:* here we have a character entity reference "&bull;" since a 'bullet' is not a character in the base code page ISO 646. It is contained in the public entity references cited in the DTD at Annex B.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.27

---

[Blank page]



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.28

### IMAGES

TABLE OF SGML TAGS AND ATTRIBUTES		
TAG	NAME	DESCRIPTION
<ELE>	Embedded image LEgend	Indicates a portion of text directly related to an embedded image. Attributes required. An end tag is required.
<EMI>	EMbedded Image	Indicates non character-coded data. Attributes required. No end tag is required since this is a reference to an external image file and the tag is empty.
<EMR>	EMbedded image Reference	Indicates a reference to a previous EMI. Attributes required. No end tag is necessary since it is self-contained and the tag is empty.
<RTI>	Replacement of Text by Image	Indicates text that is also captured as an image. The image data may be used in place of the text in order to guarantee that presentation is identical to the original document. Attributes required. An end tag is necessary.
<GAI>	GAlji	Indicates a reference to a Gaiji (Japanese) dot font file which is composed of five dot font files. Attributes required. An end tag is required.
ATTRIBUTE	NAME	DESCRIPTION
FILE	FILE	External file name of the image
HE	HEight	Height of images in mm
ID	InDentifier	Has various parameters depending on tag
IMF	IMage Format	Indicates the image format of a stored image.
LX	X coordinate	X coordinate of image in 1/10mm
LY	Y coordinate	Y coordinate of image in 1/10mm
TI	Type of Image	Type of image stored
WI	WIdth	Width of images in mm

### SGML TAGS: DESCRIPTION AND USAGE

#### 36. <EMI> : EMbedded Image

This indicates any information which is not character coded, for example, drawings, chemical structures, graphs, etc. It is non-SGML data. No end tag is necessary since no text is allowed, it is empty. The information will normally be stored in a standard graphics file format. WIPO Standard ST.33 (compression according to CCITT Group 4) is the recommended default.

For external references, that is, to the image itself, we have a unique identifier to the external name of the image via the use of a file name which, for patent documents, is usually the publication number, or application number, of the patent document (acting as the unique filename) in combination with the internal identification specified below.

Required Attribute(s):

**ID=nnnn.nnnn** Internal identifier consisting of a 4-digit sequence number indicating the original page number on which the image occurred and a 4-digit sequence number indicating the sequence of images on that particular page. (This follows the frame and sequence number indexing methodology used in WIPO Standard ST.33). Optionally, it may be replaced by a sequential numbering of images within a document, in which case use ID=nnnnnnnn. Either form is valid.

**HE=nnn** Height: 3-digit expression in millimetres.

**WI=nnn** Width: 3-digit expression in millimetres.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.29

### Optional Attribute(s):

<b>FILE=</b> <i>name</i>	Where 'name' is the name (with pointer if required) of the image file, which contains the embedded image.
<b>LX=</b> <i>nnnn</i>	4-digit X-coordinate expressed in 1/10 millimetres of embedded image location referencing to the top left corner of the page.
<b>LY=</b> <i>nnnn</i>	4-digit Y-coordinate expressed in 1/10 millimetres of embedded image location referencing to the top left corner of the page.

**Note:** The above two attributes should be used only when physical pages are represented. In all cases leading zeros may be dropped.

**IMF=** Indicates, generally, the type of IImage Format, or File, of the stored image. Possible formats and files include:

ST33	WIPO ST.33 (default)
CGM	Computer Graphics Metafile
EPS	Encapsulated Postscript
G3	CCITT Group 3 compression
G4	CCITT Group 4 compression
TIFF	Tag Image File Format
IGES	Initial Graphics Exchange Format
JPEG	Joint Photographic Experts Group Format
MPEG	Motion Picture Experts Group Format
GEM	Digital Research GEM
AI	Adobe Illustrator
GIF	Compuserve Graphics Image Format
PCT	Apple Picture File Format
BMP	Microsoft Bitmap File Format
PCX	Paintbrush File Format
WMF	Windows Metafile Format
PGL	Hewlett-Packard Graphics Language
WPG	WordPerfect Graphics File format
etc.	

The default format used is office-dependent and must be stated in the DTD. Also note that they are not mutually exclusive, for example, ST.33 and TIFF files may comprise CCITT Group 4 compression.

<b>TI=</b>	Type of embedded Image. Possible type names include:
AD	Abstract Drawing
CF	Chemical Formulae
CI	Clipped Image
CP	Computer Programs
DN	DNA sequences
DR	DRawings
FF	undefined characters
FG	FiGures
GR	GRaphs
MF	Mathematical Formulae
PA	Full PAge facsimile image
PH	PHotographs
SR	Search Report forms
TB	TaBular data
TX	TeXt character(s)
UI	Undefined Images



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.30

### DTD Syntax:

```
<!ELEMENT emi      - o EMPTY                      -- Embedded image          -->
<!ATTLIST emi      id      NUTOKEN    #REQUIRED      -- Image identity          --
                  he      NUMBER     #REQUIRED      -- Height in mm            --
                  wi      NUMBER     #REQUIRED      -- Width in mm             --
                  file    CDATA      #IMPLIED        -- image file name        --
                  lx      NUMBER     #IMPLIED        -- X-coord 1/10 mm        --
                  ly      NUMBER     #IMPLIED        -- Y-coord 1/10 mm        --
                  imf      (%imgfmt;) #IMPLIED        -- Format stored emi       --
                  ti      (AD|CF|CI|CP|DN|DR|FF|FG|GR|MF|PA|PH|SR|TB|TX|UI) #IMPLIED -- Image type              -->
```

### Examples:

```
<EMI ID='2.1' HE=10 WI=20 TI=CF>
```

Identifies the first embedded image on page 2 of the current document which is a chemical representation with actual sizes of 10mm vertical and 20mm horizontal.

```
<EMI FILE="d:\image\fig22.wpg" ID="12.6" HE=30 WI=100 IMF=WPG TI=MF>
```

**Note:** The identity attribute has been standardised for embedded images, footnotes and their associated references. The use of page and frame number generates a unique code within a document that will:

- identify the related entities;
- form a means of reference to the original document when inspecting the digitised data; and
- bind the entities together at the time of presentation, without regard to the fact that the final page location may differ from that of the original document.

### 37. <ELE> : Embedded image LEgend

This indicates a portion of text directly related to an embedded image. An end tag is required.

#### Required Attribute(s):

**ID=nnnn.nnnn** Consisting of a 4-digit sequence number indicating the page number on which the image occurred and a 4-digit sequence number indicating the sequence of images on that particular page. This attribute contains exactly the same values as the congruent attribute of the related embedded image. Optionally, it may be replaced by a sequential numbering of images within a document, in which case use ID=nnnnnnnn. Either form is valid. Leading zeros may be dropped.

#### Optional Attribute(s):

None.

### DTD Syntax:

```
<!ELEMENT ele      - - (%ptext;)+                  -- Figure caption          -->
<!ATTLIST ele      id      NUTOKEN    #REQUIRED      -->
```

### Examples:

```
<ELE ID="2.1">This is the legend of the first embedded image on page 2</ELE>...
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.31

### 38. <EMR> : EMbedded image Reference

This indicates a reference to an embedded image. The tag is self-contained. This tag should be used for referring to images which occur more than once in a document, since the full <EMI> tag need not be repeated and the image need not be scanned more than once.

Required Attribute(s):

**ID=nnnn.nnnn** Consisting of a 4-digit sequence number indicating the original page number on which the image occurred and a 4-digit sequence number indicating the sequence of images on that particular page. This attribute contains exactly the same values as the congruent attribute of the referenced embedded image. Optionally, it may be replaced by a sequential numbering of images within a document, in which case use ID=nnnnnnnn. Either form is valid. Leading zeros may be dropped.

Optional Attribute(s):  
None.

DTD Syntax:

```
<!ELEMENT emr      - o EMPTY                -- Reference to emi      -->
<!ATTLIST emr      id      NUTOKEN    #REQUIRED                >
```

Examples:

<EMR ID="2.1">This is a reference to the first embedded image on page 2...

Note: For further explanation see <EMI> above.

### 39. <RTI> : Replacement of Text by Image

Indicates text that is also captured as an image. The image data may be used in place of the text in order to guarantee that presentation is identical to the original document. An end tag is required. The image should be stored in a standard format, for example WIPO Standard ST.33.

Required Attribute(s):

**ID=nnnn.nnnn** Consisting of a 4-digit sequence number indicating the page number on which the image occurred and a 4-digit sequence number indicating the sequence of images on that particular page. Optionally, it may be replaced by a sequential numbering of images within a document, in which case use ID=nnnnnnnn. Either form is valid. In both cases leading zeros may be deleted.

**HE=nnn** Height: 3-digit expression in millimetres.

**WI=nnn** Width: 3-digit expression in millimetres.

Optional Attribute(s):

**FILE=name** Where 'name' is the name (with pointer if required) of the image file, which contains the RTI image.

**IMF=** Indicates, generally, the type of Image Format, or File, of the stored image. See <EMI> for full list.  
ST33 WIPO ST.33 (default)

The default format used is office-dependent and must be stated in the DTD. Also note that they are not mutually exclusive, for example, a TIFF file may comprise CCITT Group 4 compression.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.32

**LX=nnnn** 4-digit X-coordinate expressed in 1/10 millimetres of embedded image location referencing to the top left corner of the page.

**LY=nnnn** 4-digit Y-coordinate expressed in 1/10 millimetres of embedded image location referencing to the top left corner of the page.

*Note:* The above two attributes are used only when physical pages are represented.

DTD Syntax:

```
<!ELEMENT rti - - CDATA -- Replace text with image -->
<!-- rti identity --
  he NUMBER #REQUIRED -- Height in mm --
  wi NUMBER #REQUIRED -- Width in mm --
  file CDATA #IMPLIED -- image file name --
  lx NUMBER #IMPLIED -- X-coord 1/10 mm --
  ly NUMBER #IMPLIED -- Y-coord 1/10 mm --
  imf (%imgfmt;) #IMPLIED -- image format -->
```

*Example:*

```
<SDOBI><B100>Minimum B100 tags required here<B100>
<RTI ID=00000001 HE=150 WI=170 LX=0200 LY=0300>
Japanese Patent Office title page (bibliographic information)...
</RTI>
</SDOBI>
```

### 40. <GAI> : Gaiji

This indicates a reference to a Gaiji dot font file which is composed of five dot font files each of different sizes. It may be of particular use within the Japanese Patent Office. An end tag is required.

Required Attribute(s):

**ID=nnnn** Consisting of a 4-digit number indicating the sequence number of the dot font character in the Gaiji file.

Optional Attribute(s):  
None.

DTD Syntax:

```
<!ELEMENT gai - - CDATA -- Gaiji character -->
<!-- rti identity --
  id NUTOKEN #REQUIRED
>
```

*Example:*



<GAI ID=0001> Japanese Gaiji dot font character </GAI>



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.33

### TABLES

TABLE OF SGML TAGS AND ATTRIBUTES		
TAG	NAME	DESCRIPTION
<CEL>	table CELI	Indicates start of a new cell. No end tag is necessary.
<ROW>	table ROW	Indicates start of a new row. No end tag is necessary.
<TAB>	TABLE	Indicates the beginning of the tabular data. Attribute required. An end tag is required.
<TCH>	Table Column Header	For one particular column or multiple columns. No end tag is necessary.
<TSB>	Table StuB lines	For single or multiple rows. No end tag is necessary.
<TSH>	Table SubHeading	For one or more columns, same as for header. No end tag is necessary.
<TTI>	Table Title	May appear above or below the actual table. No end tag is necessary.
ATTRIBUTE	NAME	DESCRIPTION
AL	ALign	Used to justify the tabular data
CB	Column Begin	Indicates start and end columns
CE	Column End	For straddle headers or cells
CO	COlumn	Number of columns in the table
CS	Column Separator	Column separation attributes
ID	IDentifier	Any identifier applied to the original table
OR	ORientation	Used to signal table orientation
RB	Row Begin	Indicates start and end rows
RE	Row End	For straddle stub lines or cells
ROTATION	ROTATION	Rotation of data within a cell
RS	Row Separator	Row separation attributes

### SGML TAGS: DESCRIPTION AND USAGE

#### 41. <TAB> : TABular material

This indicates the beginning of tabular data. An end tag is required.

Required Attribute(s):

CO=*nn*                                      2-digit number giving the total number of columns in a table.

Optional Attribute(s):

ID=                                      Any identifier applied to the original table, for example, 'TABLE 1.'

OR=                                      Orientation.  
L                      Landscape  
P                      Portrait (default)

RS=                                      Row Separator(s)



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.34

CS= Column Separator(s)

RS and CS consist of a row or column identifier and separator style.

Row and Column identifiers are:

P Preceding first column or row  
F Following last column or row  
A All columns or rows not explicitly identified  
n Explicit number of row or column to follow

Separator style.

Possible styles are:

BL blank space between (default)  
S single  
D double  
T triple  
B bold  
DA dashed  
DT dotted

DTD Syntax:

```
<!ELEMENT tab - - (row,(%rowcnt;))p)+ -- Main structure -->
<!ATTLIST tab co NUMBER #REQUIRED -- Number of columns --
              or (L|P) "P" -- Orientation --
              id CDATA #IMPLIED -- Identifier --
              cs CDATA #IMPLIED -- Col separators --
              rs CDATA #IMPLIED -- Row separators --
```

Examples:

```
<TAB CO=5 ID='Table 1'>
<ROW><CEL>DATA 1<CEL>DATA 2<CEL>DATA 3<CEL>DATA 4<CEL>DATA 5
</TAB>
```

tabular material consisting of five columns of information identified as Table 1:

Table 1

DATA 1	DATA 2	DATA 3	DATA 4	DATA 5
--------	--------	--------	--------	--------

```
<TAB CO=6 RS='P B F B A S' CS='P B F B A S'>
<ROW><CEL>DATA 1<CEL>DATA 2<CEL>DATA 3<CEL>DATA 4<CEL>DATA 5<CEL>DATA 6
</TAB>
```

Tabular material consisting of six columns of information surrounded by a bold box and the rows and columns separated by single lines:

DATA 1	DATA 2	DATA 3	DATA 4	DATA 5	DATA 6
--------	--------	--------	--------	--------	--------

See also below.

### 42. <TTI> : Table Title

This indicates the title of the tabular data. A title would usually appear above the table but it may also appear below where it would be termed a caption, but the same tag will suffice. No end tag is necessary.

Required Attribute(s):

None.

Optional Attribute(s):

AL= L Left  
R Right  
C Centered (default)



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.35

DTD Syntax:

```
<!ELEMENT tti    - o (%ptext;)*           -- Table title           -->
<!ATTLIST tti    al  (L|R|C) "C"           -- Text alignment         -->
```

*Example:*

<TTI>Title of the Table.

### 43. <TCH> : Table Column Header

This indicates the header of one column or multiple columns in the table. No end tag is necessary.

Required Attribute(s):

None.

Optional Attribute(s):

AL=

L	Left
R	Right
C	Centered (default)

CB=*nn*                      2-digit number giving start column in the case of a straddled header.

CE=*nn*                      2-digit number giving end column in the case of a straddled header.

DTD Syntax:

```
<!ELEMENT tch    - o (%ptext;)*           -- Column header         -->
<!ATTLIST tch    cb  NUMBER #IMPLIED       -- Start column          --
                  ce  NUMBER #IMPLIED       -- End column            --
                  al  (L | R | C) "C"       -- Text alignment        -->
```

*Examples:*

<TCH>Header for single column

<TCH CB=1 CE=2>Header which straddles both columns one and two.

### 44. <TSH> : Table Sub-Header

This indicates the subheader of one column or multiple columns in the table. No end tag is necessary.

Required Attribute(s):

None.

Optional Attribute(s):

AL=

L	Left
R	Right
C	Centered (default)

CB=*nn*                      2-digit number giving start column in the case of a straddled header.

CE=*nn*                      2-digit number giving end column in the case of a straddled header.

DTD Syntax:

```
<!ELEMENT tsh    - o (%ptext;)*           -- Column subhead        -->
<!ATTLIST tsh    cb  NUMBER #IMPLIED       -- Start column          --
                  ce  NUMBER #IMPLIED       -- End column            --
                  al  (L | R | C) "C"       -- Text alignment        -->
```

*Examples:*



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.36

<TSH>Subheader for single column

<TSH CB=1 CE=2>Subheader which straddles both columns one and two.

### 45. <TSB> : Table Stub line

This indicates the stub line (text descriptor) for one or more rows in the table. No end tag is necessary.

Required Attribute(s):  
None.

Optional Attribute(s):

AL=	L	Left (default)
	R	Right
	C	Centered
	D	Decimal
	E	Exponent

RB=*nn* 2-digit number giving start row in the case of a straddled stub line.

RE=*nn* 2-digit number giving end row in the case of a straddled stub line.

*Note:* Stub lines may straddle rows. If the leftmost column contains row-straddling stub lines, then all stub lines must specify the RB= (row begin) attribute. Straddling stub lines must also specify the RE= (row end) attribute.

DTD Syntax:

<!ELEMENT tsb	- o (%ptext;)*	-- Stub field	-->
<!ATTLIST tsb	rb NUMBER #IMPLIED	-- Start row	--
	re NUMBER #IMPLIED	-- End row	--
	al (L   R   C   D   E) "L"	-- Text alignment	-->

*Examples:*

<TSB RB=1>Stub line for a single row where a subsequent stub line straddles more than one row.

<TSB RB=7 RE=8>Stub line which straddles rows seven and eight.

### 46. <ROW> : ROW

This indicates the start of a new row in the table. No end tag is necessary.

Required Attribute(s):  
None.

Optional Attribute(s):  
None.

*Note:* Simple rows contain only cells. Each cell may contain more than one line of type. Other rows may contain stub lines as the left-most cell. Stub lines may straddle more than one row.

DTD Syntax:

<!ELEMENT row	- o EMPTY	-- Table row	-->
---------------	-----------	--------------	-----

*Examples:*

<ROW>row five of table

<ROW>row six of table.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.37

### 47. <CEL> : CELI

This indicates the start of a new data cell in the table. No end tag is necessary.

Required Attribute(s):

None.

Optional Attribute(s):

AL= R Right (default)  
L Left  
C Centered  
D Decimal  
E Exponent

RB=nn 2-digit number giving start row in the case of straddled cells.

RE=nn 2-digit number giving end row in the case of straddled cells.

CB=nn 2-digit number giving start column in the case of straddled cells.

CE=nn 2-digit number giving end column in the case of straddled cells.

ROTATION= Specifies the rotation of the contents of a cell.

**Note:** Cells may straddle columns and/or rows. If a row contains column straddling cells, then all cells must specify the column begin attribute. Likewise, if a row contains row straddling cells, all cells must specify the row begin attribute. Straddling cells must also specify the row end and/or column end attributes. Some rows may contain stub lines as the leftmost cell. Stub lines may also straddle rows but never columns.

DTD Syntax:

```
<!ELEMENT cel - o ((%ptext;))* -- Table cell -->
<!ATTLIST cel rb NUMBER #IMPLIED -- Start row --
re NUMBER #IMPLIED -- End row --
cb NUMBER #IMPLIED -- Start column --
ce NUMBER #IMPLIED -- End column --
al (L | R | C | D | E) "R" -- Text alignment --
rotation NUMBER #IMPLIED -- Rotation of cell contents -->
```

*Examples:*

Simple Table Rows

<ROW><CEL>Data<CEL>Data<CEL>Data

Complex Table Rows

<ROW><CEL CB=1>Data<CEL CB=2 CE=3>Data<CEL CB=4>Data

Table I – Original

COOLING SYSTEM COMPONENTS			
DESCRIPTION	RETAIL PRICE		QUANTITY
	ex VAT	inc VAT	in stock
Radiators	295.50	330.00	3,012
Hose Clips	5.25	6.25	27,435
Lower Pipes	23.66	26.50	12,445
Upper Pipes	21.35	23.00	13,752
Caps	15.50	17.00	4,049
Pumps	341.00	375.00	3,553



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.38

Table I – Structure

! <TAB CO=4> !			
! +-----+ !			
! ! <TTI> ! !			
! +-----+ !			
! !			
! +-----+ +-----+ +-----+ +-----+ !			
! ! <TCH> ! ! <TCH> ! ! <TCH> ! !			
! +-----+ +-----+ +-----+ +-----+ !			
! +-----+ +-----+ +-----+ +-----+ !			
! ! <TSH> ! ! <TSH> ! ! <TSH> ! !			
! +-----+ +-----+ +-----+ +-----+ !			
! !			
! +-----+ +-----+ +-----+ +-----+ !			
! ! <TSB> ! ! <CEL> ! ! <CEL> ! !			
! +-----+ +-----+ +-----+ +-----+ !			
! +-----+ +-----+ +-----+ +-----+ !			
! ! <TSB> ! ! <CEL> ! ! <CEL> ! !			
! +-----+ +-----+ +-----+ +-----+ !			
! +-----+ +-----+ +-----+ +-----+ !			
! ! <TSB> ! ! <CEL> ! ! <CEL> ! !			
! +-----+ +-----+ +-----+ +-----+ !			
! +-----+ +-----+ +-----+ +-----+ !			
! ! <TSB> ! ! <CEL> ! ! <CEL> ! !			
! +-----+ +-----+ +-----+ +-----+ !			
! +-----+ +-----+ +-----+ +-----+ !			
! ! <TSB> ! ! <CEL> ! ! <CEL> ! !			
! +-----+ +-----+ +-----+ +-----+ !			
! </TAB> !			
! +-----+ !			

Table I – Markup

```
<TAB CO=4 RS=0'PS FS AS' CS='PS FS AS'>
<ROW><TTI>COOLING SYSTEM COMPONENTS
<ROW><TCH AL=L>DESCRIPTION
<TCH CB=2 CE=3>RETAIL PRICE
<TCH AL=R>QUANTITY
<ROW><TSH>
<TSH AL=R>ex Vat
<TSH AL=R>inc Vat
<TSH AL=R>in stock
<ROW><TSB>Radiators<CEL AL=D>295.50<CEL AL=D>330.00<CEL>3,012
<ROW><TSB>Hose Clips<CEL AL=D>5.25<CEL AL=D>6.25<CEL>27,435
<ROW><TSB>Lower Pipes<CEL AL=D>23.66<CEL AL=D>26.50<CEL>12,445
<ROW><TSB>Upper Pipes<CEL AL=D>21.35<CEL AL=D>23.00<CEL>13,752
<ROW><TSB>Caps<CEL AL=D>15.50<CEL AL=D>17.00<CEL>4,049
<ROW><TSB>Pumps<CEL AL=D>341.00<CEL AL=D>375.00<CEL>3,553
</TAB>
```



# **HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION**

Ref.: Standards – ST.32

page: 3.32.39

Table II – Original

<p><b>TABLE 1</b> <b>THE CURING OF COATING COMPOSITIONS UNDER ULTRAVIOLET LIGHT</b></p>						
<i>COMPOSITION</i>	<i>TIME (MIN.)</i>	<i>D-IMPACT* THICKNESS (MIL)</i>	<i>R-IMPACT** ADMISSION</i>	<i>HARDNESS</i>	<i>(IN-LB)***</i>	<i>(IN-LB2)***</i>
1	75	O.1-0.2	90 percent	8H	25	10
	180	O.3-0.5	100 percent	2H	50	10
	180	0.5	100 percent	HB	100	0
2	130	O.1-0.2	100 percent	8H	25	0
	150	O.1-0.2	100 percent	8H	25	0
3	60	0.2	100 percent	8H	50	0
	120	0.2	100 percent	8H	50	0
4	60	0.2	100 percent	8H	30	10
	90	1.0	60 percent	8H	40	10
5	120	O.4-0.5	95 percent	8H	30	10
6	120	0.2	100 percent	8H	25	0
7	60	0.4	100 percent	8H	160	50
	120	0.4	100 percent	8H	160	50
8	60	O.4-0.5	100 percent	8H	75	10
9	60	O.2-0.4	100 percent	8H	40	0
10	60	O.2-0.4	100 percent	8H	40	0
11	30	0.5	100 percent	8H	100	100
12	30	O.05-0.07	100 percent	6H	40	10
<p>* Direct impact  ** Reverse impact  *** Inch-Pounds</p>						

## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.40

Table II – Structure

1	2	3	4	5	6	7	Column	Row
<TAB CO=7 ID='TABLE 1'>							!	!
<TTI>							!	!
							!	!
<TCH>	<TCH>	<TCH>	<TCH>	<TCH>	<TCH>	<TCH>	<TCH>	2
<TSB>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	3
<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	4
<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	5
<TSB>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	6
<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	7
<TSB>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	8
<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	9
<TSB>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	10
<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	11
<TSB>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	12
<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	13
<TSB>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	14
<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	15
<TSB>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	16
<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	17
<TSB>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	18
<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	19
<TSB>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	<CEL>	20
</TAB>							!	!



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.41

Table II – Mark-up

```
<TAB CO=7 ID='TABLE 1' RS='PS FS AS' CS='PS FS AS'>
<ROW><TTI>THE CURING OF COATING COMPOSITIONS UNDER ULTRAVIOLET LIGHT
<ROW><TCH><U>COMPOSITION</U>
<TCH><U>TIME(MIN.)</U>
<TCH>D-IMPACT<FOR FNREF="18.1">*</FOR><U>THICKNESS (MIL)</U>
<TCH>R-IMPACT<FOR FNREF="18.2">*</FOR><U>ADHESION</U>
<TCH><U>HARDNESS</U>
<TCH><U>(IN-LB)<FOR FNREF="18.3">***</FOR></U>
<TCH><U>(IN-LB2)<FOR FNREF="18.3">***</FOR></U>
<ROW><TSB RB=3 RE=5>1<CEL>75<CEL AL=C>0.1-0.2<CEL>90 percent<CEL>8H<CEL>25<CEL>10
<ROW><CEL>180<CEL AL=C>0.3-0.5<CEL>100 percent<CEL>2H<CEL>50<CEL>10
<ROW><CEL>180<CEL>0.5<CEL>100 percent<CEL>HB<CEL>100<CEL>0
<ROW><TSB RB=6 RE=7>2<CEL>130<CEL AL=C>0.1-0.2<CEL>100 percent<CEL>8H<CEL>25<CEL>0
<ROW><CEL>150<CEL AL=C>0.1-0.2<CEL>100 percent<CEL>8H<CEL>25<CEL>0
<ROW><TSB RB=8 RE=9>3<CEL>60<CEL AL=C>0.2<CEL>100 percent<CEL>8H<CEL>50<CEL>0
<ROW><CEL>120<CEL AL=C>0.2<CEL>100 percent<CEL>8H<CEL>50<CEL>0
<ROW><TSB RB=10 RE=11>4<CEL>60<CEL AL=C>0.2<CEL>100 percent<CEL>8H<CEL>30<CEL>10
<ROW><CEL>90<CEL AL=C>1.0<CEL>60 percent<CEL>8H<CEL>40<CEL>10
<ROW><TSB RB=12>5<CEL>120<CEL AL=C>0.4-0.5<CEL>95 percent<CEL>8H<CEL>30<CEL>10
<ROW><TSB RB=13>6<CEL>120<CEL AL=C>0.2<CEL>100 percent<CEL>8H<CEL>25<CEL>0
<ROW><TSB RB=14 RE=15>7<CEL>60<CEL>0.4<CEL>100 percent<CEL>8H<CEL>160<CEL>50
<ROW><CEL>120<CEL AL=C>0.4<CEL>100 percent<CEL>8H<CEL>160<CEL>50
<ROW><TSB RB=16>8<CEL>60<CEL AL=C>0.4-0.5<CEL>100 percent<CEL>8H<CEL>75<CEL>10
<ROW><TSB RB=17>9<CEL>60<CEL AL=C>0.2-0.4<CEL>100 percent<CEL>8H<CEL>40<CEL>0
<ROW><TSB RB=18>10<CEL>60<CEL AL=C>0.2-0.4<CEL>100 percent<CEL>8H<CEL>40<CEL>0
<ROW><TSB RB=19>11<CEL>30<CEL AL=C>0.5<CEL>100 percent<CEL>8H<CEL>100<CEL>100
<ROW><TSB RB=20>12<CEL>30<CEL AL=C>0.05-0.07<CEL>100 percent<CEL>6H<CEL>40<CEL>10
<FOO FN="18.1">*</FOO> Direct Impact</FOO>
<FOO FN="18.2">*</FOO> Reverse Impact</FOO>
<FOO FN="18.3">***</FOO> Inch-Pounds</FOO>
</TAB>
```

*Note:* The footnote text has been captured within the table tag. This will indicate to a formatter that this footnote is associated with the table and should be presented immediately following the table rather than at the foot of the page.



## **HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION**

Ref.: Standards – ST.32

page: 3.32.42

---

[Blank page]



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.43

### CHEMICAL FORMULAE

TABLE OF TAGS AND ATTRIBUTES		
TAG	NAME	DESCRIPTION
<CHE>	CHEmical formula	Indicates the beginning of a quasilinear formula. An end tag is required.
<CHR>	CHEmical Reaction	Indicates the beginning of a chemical reaction formula. An end tag is required.
<CRF>	Chemical ReFeRenCe	Indicates the beginning of a reference to a chemical formula. Attribute required. No end tag is necessary, it is self-contained.
ATTRIBUTE	NAME	DESCRIPTION
ID	IDentifier attribute	A unique name.
NUM	NUMber	Used to specify an explicit formula number.
REFID	REFeRenCe number IDentification	An id reference value giving a unique name.

### SGML TAGS: DESCRIPTION AND USAGE

*Note:* Tagging is confined to relatively simple formulae. No attempt has been made to develop coding for so-called “ring-structures” or Markush structures.

#### 48. <CHE> : CHEmical formula

This indicates the beginning of a quasi-linear chemical formula. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

ID= A unique name, which must start with a letter, eg. id=xyz

NUM= Used to specify an explicit formula number.

DTD Syntax:

```
<!ELEMENT che - - (%ptext;)*           -- Chemical formula      -->
<!ATTLIST che id ID #IMPLIED           -- chem reaction id      --
              num CDATA #IMPLIED        -- specific number       -->
```

*Example:*

2FeCl<sub>2</sub>.FeCl<sub>3</sub>.xH<sub>2</sub>O                      <CHE>2FeCl<SB>2</SB>.FeCl<SB>3</SB>.xH<SB>2</SB>O </CHE>

#### 49. <CHR> : CHEmical Reaction

This indicates the beginning of a chemical reaction formula. An end tag is required. When descriptive text must appear above and/or below an arrow the <CHF> construct is used.

Required Attribute(s):  
None.

Optional Attribute(s):

ID= A unique name, which must start with a letter, eg. id=xyz

NUM= Used to specify an explicit formula number.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION


Ref.: Standards – ST.32

page: 3.32.44

### DTD Syntax:

```
<!ELEMENT chr - - (%ptext;)*           -- Chemical reaction    -->
<!ATTLIST chr id ID #IMPLIED           -- chem reaction id      --
              num CDATA #IMPLIED       -- specific number       -->
```

### Examples:



### 50. <CRF> : Chemical ReFERENCE

This indicates from which point(s) a chemical representation is referenced. The tag is self-contained and therefore there is no end tag. Although a reference might be a text string requiring no markup, markup is recommended for purposes of searching.

#### Required Attribute(s):

REFID= A unique name, which must start with a letter, eg. refid=xyz

#### Optional Attribute(s):

None.

### DTD Syntax:

```
<!ELEMENT crf - o EMPTY                -- Reference to che. formula -->
<!ATTLIST crf refid IDREF #REQUIRED    -- Unique reference        -->
```

### MATHEMATICAL FORMULAE

TABLE OF SGML TAGS AND ATTRIBUTES		
TAG	NAME	DESCRIPTION
<ABOVE>	ABOVE	Indicates a formula value to be displayed above another formula value. No end tag is necessary.
<BOX>	BOXes	Indicates parts of a formula to be placed in a box. An end tag is required.
<BREAK>	BREAK	This indicates a line break in the formula. The tag is self contained, ie. it has no content.
<COL>	COLumn(s)	This indicates a column in a matrix. An end tag is required.
<DF>	Display Formula	This indicates the beginning of displayed mathematical formula(e). An end tag is required.
<DFG>	Display Formula Group	This indicates a group of display mathematical formula(e) that are to be processed together. An end tag is required.
<DFREF>	Display Formula REference	Indicates a reference to a formula. Attribute required. No end tag is necessary.
<F>	inline Formula	Indicates an inline formula. An end tag is required.
<FENCE>	FENCEs	Indicates a fence or bracket. An end tag is required.
<FRAC>	FRActions	This indicates fractions. An end tag is required.
<FROM>	FROM	Identifies the lower limit for the <INTEGRAL>, <PLEX>, <PRODUCT> and <SUM> tags. No end tag is required.
<INTEGRAL>	INTEGRAL	This indicates information to be displayed as an integral, using the general limits form of presentation. An end tag is required.
<ITALIC>	ITALIC	This indicates parts of a formula to be set in italic. An end tag is required.
<MARK>	MARK	This indicates a mark for vertical alignment within a formula. Attribute required. It is self-contained and therefore no end tag is necessary.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.45

TABLE OF SGML TAGS AND ATTRIBUTES		
TAG	NAME	DESCRIPTION
<MARKREF>	MARK REFERENCE	This indicates a reference to a defined mark and causing the system to vertically align the formula on that mark. Attribute required. No end tag is necessary.
<MATRIX>	MATRIX	This indicates a matrix formula. An end tag is required.
<MIDDLE>	MIDDLE (post)	This indicates a single separator mark called a post in a formula. An end tag is necessary.
<OF>	OF	Identifies the operand for the <INTEGRAL>, <PLEX>, <PRODUCT> and <SUM> tags. No end tag is required.
<OPERATOR>	OPERATOR	Identifies an operator in a <PLEX> construction. Its use is optional.
<OV>	Over	This indicates parts of a formula over which special characters or diacriticals are to be placed. An end tag is required.
<OVER>	OVER	This indicates a fraction denominator. No end tag is necessary.
<PILE>	PILE	This indicates segments of a formula that are to be placed one above the other. An end tag is required.
<PLEX>	PLEX	Identifies a general limits operator. Must be followed immediately by the operator. An end tag is required.
<POWER>	POWER	This indicates an exponential formula. An end tag is required.
<PRODUCT>	PRODUCT	This indicates a formula that presents the product of formula values using the general limits form of presentation. An end tag is required.
<ROMAN>	ROMAN	This indicates parts of a formula to be set in roman. An end tag is required.
<ROOT>	ROOT	This indicates data to be displayed as a root. An end tag is required.
<SQRT>	SQuare RooT	This indicates a square root. An end tag is required.
<SQUARE>	SQUARE	This indicates data to be displayed as a square. An end tag is required.
<SUB>	SUBscript	This indicates a mathematical inferior placed as a subscript. An end tag is required.
<SUM>	SUMmation	This indicates a formula to be displayed as a summation, using the general limits form of presentation. An end tag is required.
<SUP>	SUPerscript	This indicates a mathematical superior placed as a superscript. An end tag is required.
<TENSOR>	TENSORs	This indicates a tensor. Attribute required. An end tag is required.
<TO>	TO	Identifies the upper limit for the <INTEGRAL>, <PLEX>, <PRODUCT> and <SUM> tags. No end tag is required.
<VEC>	VECtor	This indicates a vector. An end tag is required.
ATTRIBUTE	NAME	DESCRIPTION
ALIGN	ALIGNment	Used to specify alignment of data.
CLOSE	CLOSE	Use to specify a character in fence constructs.
ID	IDentifier attribute.	Used to specify various formula identity attributes.
NUM	NUMber	Used to specify an explicit formula number.
OPEN	OPEN	Used to specify a character in fence constructs.
PAGE	PAGE	Used to specify page number may be system generated for references.
POS	POSition	Position of inferiors and superiors.
POSF	POSition of the First suffix	Used to specify the position of the first suffix attribute of tensors.
REFID	REFerence IDentification	Used to identify various formula references.
SPC	SPaCing	Spacing of elements
STYLE	STYLE	Used to define the style of a character, for example, double fence.
SUFFIX	SUFFIX	Used to identify suffixes of tensors.
TYPE	TYPE	Used to define the type of character used, for example, brace fence.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.46

### SGML TAGS: DESCRIPTION AND USAGE

These tags are taken from: ISO *Technical Report ISO/IEC/TR 9573:1988(E) – Information processing – SGML support facilities – Techniques for using SGML*. In particular, section 8 – Mathematics. The layout and some examples are different. Due acknowledgement is given to the ISO document.

### FORMULA AND FORMULA REFERENCE

#### 51. **<F> : inline Formula**

This indicates an inline mathematical formula. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT f - - (%formel;)+ -(br|matrix|pile|frac|mark|markref) -- In-line formula -->
```

*Example:*

... the basic assumption is that  $2 \times 2 = 4$  and therefore ...      ... the basic assumption is that  $\langle F \rangle 2 \times 2 = 4 \langle /F \rangle$  and therefore ...

*Note:* In simple cases such as this the use of SGML tags is not mandatory since the formula can be keyed, printed, etc., as part of the text stream. Nevertheless, markup is recommended for purposes of searching.

In addition it is recommended that  $\langle F \rangle$  be used sparingly since if multi-level formulae are tagged as such later processing (display, printing) may be difficult or create awkward line spacing in the application. For these reasons the DTD has been modified to allow only certain constructs within the  $\langle F \rangle$  tag.

#### 52. **<DF> : Display Formula**

This indicates the beginning of displayed (set off from the text) mathematical formula(e). An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

**ALIGN=**      The alignment attribute takes one of the values left, right, centre. Left is the default value.

**ID=**      A unique name, which must start with a letter, eg. id=xyz.

**NUM=**      Used to specify an explicit formula number. If omitted, sequential numbering of the formulae would normally be performed by the text formatter.

DTD Syntax:

```
<!ELEMENT df - - (%formel;)+ -(br) -- Display formula -->
<!ATTLIST df align (%align;) "centre" -- Alignment -->
            id ID #IMPLIED -- Display formula id -->
            num CDATA #IMPLIED -- Display formula number -->
```

*Example:*

$n^2 = G.d/D^2 = G_2.t/(D.p^2)$       (1)       $\langle DF \text{ NUM}=(1) \rangle n \langle SUP \rangle 2 \langle /SUP \rangle = G.d/D \langle SUP \rangle 2 \langle /SUP \rangle = G \langle SUB \rangle 2 \langle /SUB \rangle .t/(D.p \langle SUP \rangle 2 \langle /SUP \rangle) \langle /DF \rangle$



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.47

### 53. <DFG> : Display Formula Group

This indicates a group of displayed (set off from the text) mathematical formula(e) that are to be processed together. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

ALIGN= The alignment attribute takes one of the values left, right, centre. Left is the default value.

ID= A unique name, which must start with a letter, eg. id=xyz.

NUM= Used to specify an explicit formula number for the group.

DTD Syntax:

```
<!ELEMENT dfg - - (df+)
```

<!ATTLIST dfg align	(%align;)	"centre"	-- Alignment	-->
id	ID	#IMPLIED	-- Display formula group id	-->
num	CDATA	#IMPLIED	-- Display formula group num	-->

Examples:

NUM= Used to specify an explicit formula number for the group.

DTD Syntax:

```
<!ELEMENT dfg - - (df+)
```

<!ATTLIST dfg align	(%align;)	"centre"	-- Alignment	-->
id	ID	#IMPLIED	-- Display formula group id	-->
num	CDATA	#IMPLIED	-- Display formula group num	-->

Examples:

$$n^2 = G \cdot d / D^2 = G_2 \cdot t / (D \cdot p^2)$$

$$x^2 = H \cdot d / D^2 = G_2 \cdot t / (E \cdot p^2)$$

$$y^2 = J \cdot d / D^2 = G_2 \cdot t / (F \cdot p^2)$$

```
<DFG NUM=(1)><DF>n<SUP>2</SUP> = G.d/D<SUP>2</SUP> =
G<SUB>2</SUB>.t/(D.p<SUP>2</SUP>)</DF> <DF>x<SUP>2</SUP> =
H.d/D<SUP>2</SUP> = G
<SUB>2</SUB>.t/(E.p<SUP>2</SUP>)</DF><DF>y <SUP>2</SUP> =
J.d/D<SUP>2</SUP> = G<SUB>2</SUB>
</SUB>.t/(F.p<SUP>2</SUP>)</DF></DFG>
```

$$n^2 = G \cdot d / D^2 = G_2 \cdot t / (D \cdot p^2) \quad (1a)$$

$$x^2 = H \cdot d / D^2 = G_2 \cdot t / (E \cdot p^2) \quad (1b)$$

$$y^2 = J \cdot d / D^2 = G_2 \cdot t / (F \cdot p^2) \quad (1c)$$

```
<DFG><DF NUM=(1a)>n<SUP>2</SUP> = G.d/D <SUP>2</SUP> =
G<SUB>2</SUB>.t/(D.p<SUP>2</SUP>)</DF><DF
NUM=(1b)>x<SUP>2</SUP> = H.d/D<SUP>2</SUP> =
G<SUB>2</SUB>.t/(E.p<SUP>2</SUP>)</DF><DF
NUM=(1c)>y<SUP>2</SUP> = J.d/D<SUP>2</SUP> =
G<SUB>2</SUB>.t/(F.p<SUP>2</SUP>)</DF></DFG>
```

### 54. <DFREF> : mathematical Formula REFERENCE

This indicates a formula reference, or formula group reference, within text phrases. It refers to an identified formula (see <DF> and <DFG> above). The tag is self-contained and therefore there is no end tag.

Required Attribute(s):

REFID= A unique name, which must start with a letter, eg. id=xyz.

Optional Attribute(s):

PAGE= The page number attribute can take the values yes and no, in the first case, which is the default, the appropriate page number, supplied by the system, is added to the reference.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.48

DTD Syntax:

<!ELEMENT dfref	- o EMPTY	-- Formula reference	-->
<!ATTLIST dfref	refid IDREF #REQUIRED	-- Formula id	-->
	page (yes no) "yes"	-- Page number	-->

Example:

$$n^2 = G \cdot d / D^2 = G_1 \cdot t / (D \cdot p^2) \quad [12]$$

.....  
An example is shown on page 15 ....

```
<DF ID="Math12" NUM=[12]>n<SUP>2</SUP> =
G.d/
D<SUP>2</SUP> = G<SUB>2</SUB>.t/ (D.p
<SUP>2</SUP></DF>
```

An example is shown on <DFREF REFID="Math12">

...

Note: on processing the page number of the reference may be generated.

### FORMULA CONTENT

#### 55. <MARK> : MARK

This indicates a position for vertical alignment within a formula. In many cases, for example when aligning multiple formulae on equal signs, marking and referring to a horizontal position is required. The mark tag is used to define a mark. It is self-contained and therefore no end tag is necessary.

Required Attribute(s):

ID= The required identifier attribute is used when referring to a mark and must be unique.

Optional Attribute(s):

None.

DTD Syntax:

<!ELEMENT mark	- o EMPTY	-- Mark for alignment	-->
<!ATTLIST mark	id ID #REQUIRED	-- Reference id for the mark	-->

Examples:

See <MARKREF> below

#### 56. <MARKREF> : MARK REFERENCE

This indicates a reference to a defined mark and causes the system to vertically align the formula horizontally on that mark. The appropriate value for the reference identifier attribute (refid=) must be provided. The tag is self-contained, ie. it has no content, therefore, no end tag is necessary.

Required Attribute(s):

REFID= The identifier for the mark to which reference is made.

Optional Attribute(s):

None.

DTD Syntax:

<!ELEMENT markref	- o EMPTY	-- Reference to a mark	-->
<!ATTLIST markref	refid IDREF #REQUIRED	-- Id of the mark referred to	-->

Example:

$$\begin{aligned} z &= x + 6y - 3 + 12x - 3y \\ &= x + 3y - 3 + 12x \\ &= 13x + 3y - 3 \end{aligned}$$

```
<DF> z <MARK ID=x> = x + 6y - 3 + 12x - 3y</DF>
<DF> <MARKREF REFID=x> 8y - 12</DF>
<DF> <MARKREF REFID=x> y - 3</DF>
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.49

### 57. <BREAK> : BREAK

This indicates that a line break occurred at this point in a formula. The type attribute (*type=*) with values optional or required indicates if the break point is to be considered an optional breakpoint, and thus similar to hyphenating words, or a mandatory break. The latter is the default. Since the tag has no content an end tag is not required.

Required Attribute(s):  
None.

Optional Attribute(s):

TYPE= The type of break – required or optional. Required is the default.

DTD Syntax:

```
<!ELEMENT break - o EMPTY -- break point in formula -->
<!ATTRIBUTE break type (required|optional) "required" -- type of break -->
```

### 58. <BOX> : BOXes

This indicates parts of a formula to be placed in a box. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

STYLE= Style attribute – see <OV> below, default is a single line.

DTD Syntax:

```
<!ELEMENT box - - (%formel;)+ -- Box around a formula -->
<!ATTLIST box style (%style;) "single" -- Box line styles -->
```

Example:

a + b
-------

<BOX>a + b</BOX>

### 59. <OV> : 'Over' embellishments

This identifies parts of a formula where special accents or diacritical marks may be placed: over, mid or below data. In general text use <O> or <U>. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

POS= The position attribute defines the position of the mark and takes one of the values: above, below or mid. The default value is above.

STYLE= The style attribute defines the style of the mark. It takes one of the values: single, double, triple, dash, dots, or bold. The default value is single.

TYPE= The type attribute defines the type of the mark to be used. It takes one of the values: dot, dotdot, dot3, dot4, tie, tiebrace, hat, hacek, acute, grave, cedil, ring, macron, ogonek, dblac, breve, tilde, vec, rvec, dyad, circle, caret, prime, dprime, plus, bar, none. The default value is bar.

*Note:* Not all combinations of type and style attribute values would normally be used, eg *type=tilde, style=dots*.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.50

DTD Syntax:

```
<!ELEMENT ov - - (%formel;)+ -- 'over' embellishments -->
<!ATTLIST ov pos (above|below|mid) "above" -- position --
              type (%type;) "bar" -- type of embellishment --
              style(%style;) "single" -- style -->
```

Example:

$x + y$  `<OV>x + y</OV>`

60. **<TENSOR> : TENSORS**

This indicates a tensor in a formula. An end tag is required.

Required Attribute(s):

**SUFFIX=** The suffix attribute takes the suffixes of the tensor; a space indicating a switch from superscript to subscript or subscript to superscript.

Optional Attribute(s):

**POSF=** The value of the position of the first suffix attribute takes the value sup or sub, sup being the default.

DTD Syntax:

```
<!ELEMENT tensor - - (%formel;)+ -- tensors -->
<!ATTLIST tensor posf (sub|sup) "sup" -- position of the suffix --
                  suffix CDATA #REQUIRED -- value of the first suffix -->
```

Example:

$A^i_j{}^k = g^{ip} g^{kq} A_{pj}{}^q$  
`<TENSOR SUFFIX="i j k">A</TENSOR> = <TENSOR SUFFIX="ip">g`  
`</TENSOR><TENSOR SUFFIX="kq">g</TENSOR><TENSOR POSF=SUB`  
`SUFFIX="pj q">A</TENSOR>`

61. **<ITALIC> : ITALIC**  
**<ROMAN> : ROMAN**

These indicate parts of a formula to be set in italic or roman, contrary to common practice and not being a function name. End tags are required.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT italic - - (%formel;)+ -(italic) -- Italic -->
<!ELEMENT roman - - (%formel;)+ -(roman) -- Roman -->
```

Example:

$x + y = a^2$  `<F>x + y = <ITALIC>a<SUP>2</SUP></ITALIC></F>`

62. **<FRAC> : FRACTIONS**

This indicates fractions. The alignment of numerator and denominator is centered by default.

*Note:* that the ISO numerator tag `<num>` can be omitted since the element is required. An end tag is required.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.51

Required Attribute(s):

None.

Optional Attribute(s):

ALIGN= Indicates the alignment of the numerator and/or denominator, which may be centre, left, right – centre is the default.

DTD Syntax:

```
<!ELEMENT frac - - ((%formel;)+, over) -- Fraction numerator -->
<!ATTLIST frac align (%align;) "centre" -- Fraction alignment -->
```

Example: (See below)

### 63. <OVER> : OVER (fraction denominator)

This identifies a fraction denominator. No end tag is necessary.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT over - o ((%formel;)+) -- Fraction denominator -->
```

Examples:

$$\frac{2x}{3xy}$$

```
<DF><FRAC>2x<OVER>3xy</FRAC></DF>
```

$$\frac{2x + 3y^2}{12x - 12y}$$

```
<DF><FRAC>2x + 3y<SUP>2</SUP><OVER>12x - 12y</FRAC></DF>
```

$$\frac{1}{1 + \frac{1}{y^2}}$$

```
<DF><FRAC>1<OVER>1+<FRAC>1<OVER>y<SUP>2</SUP></FRAC></FRAC></DF>
```

$$\frac{1}{1 + \frac{1}{y^2}}$$

```
<DF><FRAC ALIGN=L>1<OVER>1+<FRAC>1<OVER>y<SUP>2</SUP></FRAC></FRAC></DF>
```

### 64. <SUP> : SUPerscript

This indicates a mathematical superior placed as a superscript. Several levels are allowed. An end tag is required.

*Note:* In cases where the optional attribute, POS=, is NOT used, the position of superscript, whether following or preceding the base character, can be determined by where the <SUP> is placed in the text (see examples below).

Required Attribute(s):

None.

Optional Attribute(s):

POS= The position attribute takes one of the values pre, mid, or post. The default is post.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.52

DTD Syntax:

```
<!ELEMENT sup      - - (%formel;)+      -- Superscript      -->
<!ATTLIST (sup|sub) pos (PRE|MID|POST) "POST" -- Position (default post) -->
```

Examples:

$e^x$                       `e<SUP>x</SUP>`

$x-y_N$                       `<SUP>x-y</SUP>N` or `N<SUP POS=PRE>x-y</SUP>`

See further examples below.

### 65. <SUB> : SUBscript

This indicates a mathematical inferior placed as a subscript. Several levels are allowed. An end tag is required. See notes at <SUP> above.

Required Attribute(s):  
None.

Optional Attribute(s):

POS=                      The position attribute takes one of the values *pre*, *mid*, or *post*. The default is *post*.

DTD Syntax:

```
<!ELEMENT sub      - - (%formel;)+      -- Subscript      -->
<!ATTLIST (sup|sub) pos (PRE|MID|POST) "POST" -- Position (default post) -->
```

Examples:

$T_2^1$                       `T<SUP>1</SUP><SUB>2</SUB>`

$E^{x^2}$                       `E<SUP>x<SUP>2</SUP></SUP></SUP>`

$2^{n_1}$                       `2<SUP>n<SUB>1</SUB></SUP></SUP>`

$E^{a_2^1}$                       `E<SUP>a<SUP>1</SUP><SUB>2</SUB></SUP></SUP>`

Using the hairspace character entity reference it is possible to indicate a staggered arrangement:

$T_1^2 \quad T_3$                       `<DF>T<SUB>1</SUB>&hairsp;<SUP>2</SUP>&hairsp;<SUB>3</SUB></DF>`

### 66. <PILE> : PILEs

This indicates segments of a formula that are to be placed one above the other. The <PILE> tag is immediately followed by an implied "above1" element, specification of which is not required, (ISO: "where both the start and end tags can and should be omitted). This is followed by one or more above elements, where the start tag is required. Alignment is to centre by default. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):

ALIGN=                      Indicates the alignment of values which are centered by default.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.53

SPC= Indicates the spacing between elements, close or normal. Normal is the default.

### 67. <ABOVE> : ABOVE

This indicates a formula value to be displayed above another formula value. An <ABOVE> tag can be used as many times as necessary to achieve the required stacking of formula values. An above can occur within columns, in a matrix (see below), and piles. No end tag is necessary.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

<!ELEMENT pile	- -	((%formel;)+,above+)	-- Top element, above+	-->
<!ATTLIST pile	spc	(NORM   CLOSE) "NORM"	-- Spacing	-->
	align	(%align;) "centre"	-- Alignment	-->
<!ELEMENT above	- o	((%formel;)+)	-- Lower layers	-->

Example:

**a**  
**b**  
**c**

`<PILE>a<ABOVE>b<ABOVE>c</PILE>`

### 68. <FENCE> : FENCES

This indicates fences (brackets), which may be of variable size. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

TYPE= Type of fence, for opening and closing constructs, which may be one of the following:

(	paren (Default)
[	bracket
{	brace
	bar
<	angbrack
/	solidus
	none

STYLE= Style of the fence. It takes one of the values: single, double, triple, dash, dots or bold. The default value is single.

CLOSE=*character* Specifies a character that is to be displayed as a closing fence on the right end of the data. Any value for the type attribute is ignored.

OPEN=*character* Specifies a character that is to be displayed as an opening fence on the left end of the data. Any value for the type attribute is ignored.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.54

DTD Syntax:

```
<!ELEMENT fence      - - (%formel;)+           -- Brackets, parentheses etc. -->
<!ATTLIST fence      type (%fency; ) "paren"    -- Fence kind code           --
                  style (%style; ) "single"      -- Line styles               --
                  open  CDATA #IMPLIED          -- Special open char         --
                  close CDATA #IMPLIED          -- Special close char        -->
```

Examples:

$\left\{ \frac{2x + 3y^2}{[12x - 12y] \times 14.5} \right\}$	<code>&lt;FENCE TYPE=BRACE&gt;&lt;FRAC&gt;2x + 3y&lt;SUP&gt;2&lt;/SUP&gt;&lt;OVER&gt;&lt;FENCE TYPE=BRACKET&gt;12x - 12y&lt;/FENCE&gt; x 14.5&lt;/FRAC&gt;&lt;/FENCE&gt;</code>
$\left  \frac{A + 1}{B} \right $	<code>&lt;FENCE TYPE=BAR STYLE=DOUBLE&gt;&lt;FRAC&gt;A + 1&lt;OVER&gt;B&lt;/FRAC&gt;&lt;/FENCE&gt;</code>
$\left( \frac{a}{b}, 1 \right)$	<code>&lt;FENCE OPEN=" ( "CLOSE=" ] "&gt;&lt;FRAC&gt;a&lt;OVER&gt;b&lt;/FRAC&gt;,1&lt;/FENCE&gt;</code>

69.    **<MIDDLE> : MIDDLE (post)**

This indicates a single separator mark called a "post" in a formula. The `<MIDDLE>` tag is used with the fence tag to separate values within a fence. An end tag is necessary.

Required Attribute(s):  
None.

Optional Attribute(s):

STYLE=                                      Style of the post. See above for style attributes. The default is a single post.

DTD Syntax:

```
<!ELEMENT middle     - - (#PCDATA)             -- Middle of a space         -->
<!ATTLIST middle     style (%style; ) "single"  -- Line styles               -->
```

Example:

$\left( \frac{d}{dx} u \right)_{x=0}$	<code>&lt;FENCE&gt;&lt;FRAC&gt;df&lt;OVER&gt;dx&lt;/FRAC&gt;(y)&lt;MIDDLE&gt; &lt;/MIDDLE&gt; &lt;SUB&gt;x=0&lt;/SUB&gt;&lt;/FENCE&gt;</code>
---------------------------------------	---

PLEXES

70.    **<PLEX> : PLEX and <OPERATOR>: OPERATOR**

This indicates a formula to be presented in the style of a general limit operator. A plex must contain an operator as the first element. Specification of the operator tag `<OPERATOR>` is optional. The operator can be followed by from-operators (`<FROM>` tags) and to-operators (`<TO>` tags), as well as an of-operand (`<OF>` tag). See examples below. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):  
None.

DTD Syntax:

```
<!ELEMENT plex       - - (operator,(from?&to?)?,of?) -- Generalized operator     -->
<!ELEMENT operator   o o (#PCDATA)                 -- Operator symbol          -->
```

See below for examples.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.55

*Note:* The sum, integral, and product elements are special cases of the general plex, the operator being implied by these tags, for which see below.

### 71. **<SUM> : SUMmation**

This indicates a formula to be displayed as a summation, using the limit form of presentation. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT sum - - ((from?&to?)?,of?) -- Summation -->
```

### 72. **<INTEGRAL> : INTEGRAL**

This indicates information to be displayed as an integral, using the limit form of presentation. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT integral - - ((from?&to?)?,of?) -- Integral -->
```

### 73. **<PRODUCT> : PRODUCT**

This indicates a formula that presents the product of formula values using the limit form of presentation. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT product - - ((from?&to?)?,of?) -- Product -->
```

### 74. **<FROM> : Operator for “limits”**

This identifies the lower limit for the <INTEGRAL>, <PLEX>, <PRODUCT> and <SUM> tags. No end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT from - o (%formel;)+ -- Start index for operator -->
```

### 75. **<OF> : Operator for “limits”**

This identifies the operand for the <INTEGRAL>, <PLEX>, <PRODUCT> and <SUM> tags. No end tag is required.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.56

Required Attribute(s):  
None.

Optional Attribute(s):  
None.

DTD Syntax:

<!ELEMENT of - o (%formel;)+ -- Formula operated upon -->

### 76. <TO> : Operator for “limits”

Identifies the upper limit for the <INTEGRAL>, <PLEX>, <PRODUCT> and <SUM> tags. No end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):  
None.

DTD Syntax:

<!ELEMENT to - o (%formel;)+ -- End index for operator -->

Examples:

$$\bigcup_{i=1}^{10} a_i$$

<PLEX>U<FROM>i=1<TO>10<OF>a<SUB>i</SUB></PLEX>

$$\sum_{i=1}^{10} a_i$$

<SUM><FROM>i=1<TO>10<OF>a<SUB>i</SUB></SUM>

### 77. <SQRT> : Square Root

This indicates a square root. An end tag is required.

Required Attribute(s):  
None.

Optional Attribute(s):  
None.

DTD Syntax:

<!ELEMENT sqrt - - (%formel;)+ -- Square root -->

Example:

$$\sqrt{a+b}$$

<SQRT>a+b</SQRT>

### 78. <SQUARE> : SQUARE

This indicates data to be displayed as a square. An end tag is required.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.57

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT square - - (%formel;)+ -- Square -->
```

*Example:*

$(a + b)^2$  `<SQUARE>a+b</SQUARE>`

### 79. <ROOT> : ROOT

This indicates data to be displayed as a root. A root must contain a degree and an of-operand (<OF> tag, see above). The degree of the root may be tagged <DEGREE> but it is recommended NOT to do so in patent documents. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT root - - ((%formel;)+,of) -- Root: degree/of -->
```

*Example:*

$\sqrt[4]{a+b}$	$\sqrt[n+b]{x+y}$	<code>&lt;ROOT&gt;4&lt;OF&gt;a+b&lt;/ROOT&gt;</code>	<code>&lt;ROOT&gt;a+b&lt;OF&gt;x+y&lt;/ROOT&gt;</code>
-----------------	-------------------	--	--

### 80. <POWER> : POWER

This indicates an exponential formula. A power must contain a degree and an of-operand (<OF> tag, see above). The degree element must occur before the of-operand. The degree of the power may be tagged <DEGREE> but it is recommended NOT to do so in patent documents. An end tag is required.

Required Attribute(s):

None.

Optional Attribute(s):

None.

DTD Syntax:

```
<!ELEMENT power - - ((%formel;)+,of) -- Power: degree/of -->
```

*Example:*

$(a + b)^4$	$(x + y)^{n+b}$	<code>&lt;DF&gt;</code>
		<code>&lt;POWER&gt;4&lt;OF&gt;a+b&lt;/POWER&gt;&lt;POWER&gt;a+b&lt;OF&gt;x+y&lt;/POWER&gt;</code>
		<code>&lt;/DF&gt;</code>





## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.59

they are combined with bibliographic tags to give citations to data searched. Examples are given for each type of data in Annex D.

85. The tags below are based on two sources:

- 1) European Workgroup on SGML. *MAJOUR: modular application for Journals*. European Workgroup on SGML (EWS), 1991.
- 2) Association of American Publishers. *Electronic Manuscript Series : Author's guide to electronic manuscript preparation and markup*; Reference manual on electronic manuscript preparation and markup. Dublin, Ohio : Electronic Publishing Special Interest Group (EPSIG), 1989.

Due acknowledgement is given to these sources.

TABLE OF SGML TAGS				
Parameter entities and tags			Content	Description
CIT			#PCDATA %PCIT; %NCIT; REL	Citation start tag
%PCIT;				Patent Document Citations
	%EXTDOC;		see below	Cited Document
	%NAM;		see below	Citation Applicant or Patentee
	PIC		#PCDATA	IPC of Citation
	PNC		#PCDATA	National Classification of Citation
%NCIT;				Non-Patent Document Citations
ARTCIT				Article information, citation
	%AUTHGRP;		see below	Author Group
	ATL		#PCDATA	Article Title
	SBT		#PCDATA	Article Subtitle
	JNL			Journal Reference
		JTL	#PCDATA	Journal Title
		SBT	#PCDATA	Subtitle
		JABT	#PCDATA	Journal Abbreviated Title
		PNM	%PARTY;	Publisher's Name and Address
		DATE	see below	Publication Date
		VID	#PCDATA	Volume Identification
		INO	#PCDATA	Journal Issue Number
		ANO	#PCDATA	Abstract Number
	PP			Page Numbers
		PPF	#PCDATA	First Page Number
		PPL	#PCDATA	Last Page Number
	ISSN		#PCDATA	International Standard Serial Number
	CDN		#PCDATA	International Coden
	CNG			Conference Proceedings
		CNN	#PCDATA	Conference Number
		CNM	#PCDATA	Conference Name
		DATE	see below	Conference Date
		CNP	#PCDATA	Conference Place
		CNS	#PCDATA	Conference Sponsor
	BOOKID		see below	Article in Book – Book Identification Group
BOOKCIT				Book Information, citation



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.60

TABLE OF SGML TAGS				
Parameter entities and tags			Content	Description
	%AUTHGRP;		see below	Author Group
	BOOKID		see below	Book Identification Group
	PART		#PCDATA	Part
	SECT		#PCDATA	Section, chapter
	PP			Page Numbers
		PPF	#PCDATA	First Page Number
		PPL		Last Page Number
DBASECIT				Database Information Group, citation
	DBN		#PCDATA	Name of Database
	PNM		%PARTY;	Database Publisher or Service Name and Address
	DBS		#PCDATA	Section of Database
	SRT		#PCDATA	Search Terms
	DATE		see below	Publication Date
OTHCIT			#PCDATA	Other reference (paragraph form)
REL			#PCDATA	Relevant passage
%AUTHGRP;				Author Group
	AUTHOR		%PARTY;	Author's Name
	COAUTH		%PARTY;	Co-author's Name
	COLLAB		%PARTY;	Collaborator
BOOKID				Book Identification
	TI		#PCDATA	Title
	SBT		#PCDATA	Subtitle
	EDN		%PARTY;	Editor's Name
	MSN		#PCDATA	Monographic Series Number
	MST		#PCDATA	Monographic Series Title
	ISBN		#PCDATA	International Standard Book Number
	CDN		#PCDATA	International Coden
	ANO		#PCDATA	Abstract Number
	PNM		%PARTY;	Publisher's Name/Address
	VID		#PCDATA	Volume Identification
	NO		#PCDATA	Book Number
	ED		#PCDATA	Edition Statement
	DATE		see below	Publication Date
%DOC; %EXTDOC;				Document Identification
	DNUM		#PCDATA	Document Number
		ANUM	#PCDATA	Application Number
		PNUM	#PCDATA	Publication Number
	DATE		see below	Document Date
	CTRY		see below	Publishing Country or Organization (ST.3)
	KIND		#PCDATA	Document Kind (ST.16)
	BNUM		#PCDATA	Bulletin Number
	DTXT		#PCDATA	Descriptive Text
PARENT				Describes parent document
	DNUM		see above	Document number
	CDOC		%DOC;	Child Document
	PDOC		%DOC;	Parent Document



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.61

TABLE OF SGML TAGS				
Parameter entities and tags			Content	Description
	PSTA		#PCDATA	Parent Application Status
	PPUB		%DOC;	Patent Associated with Parent Document
	%PARTY;			Individual or Organization Data
	%NAM;		see below	Individual or organization name
	ADR		see below	Individual or organization address
	DTXT		#PCDATA	Descriptive Text
	RCTRY		CTRY	Country of Residence (ST.3)
	NCTRY		CTRY	Country of Nationality (ST.3)
	%NAM;			General Name
	TTL		#PCDATA	Title (e.g., Mr. ,Mrs. ,Ms. ,Dr. , CPT, etc.)
	FNM		#PCDATA	Given and Middle Name(s) and/or Initials
	SNM		#PCDATA	Family name , last, surname or, if unable to distinguish: whole personal or organisation name
	SFX		#PCDATA	Suffix (e.g., II, Jr., Sr., Esq., et al.)
	IID		#PCDATA	Individual ID Number ( e.g., US Social Security)
	IRF		#PCDATA	Individual Reference Number (filing, etc.)
	SYN		#PCDATA	Synonym, cross reference
	ONM		#PCDATA	Organization name
	OID		#PCDATA	Identifying Number of Organization
	ODV		#PCDATA	Division of Organization
	DID		#PCDATA	Identifying Number of Division
	ADR			Address
	%NAM;		%NAM;	Name, Organization, if part of address
	OMC		#PCDATA	Organization Mail Code
	PBOX		#PCDATA	Post Office Box Number
	STR		#PCDATA	Street, house number or name, district (of city), apt. number, etc.
	CITY		#PCDATA	City or Town
	CNTY		#PCDATA	County, Parish, Department, etc.
	STATE		#PCDATA	Region of Country (State, Province, etc.)
	CTRY		#PCDATA	Country
	PCODE		#PCDATA	Postal Code
	EAD		#PCDATA	Electronic Address (e.g., e-mail)
	TEL		#PCDATA	Telephone number, including area or regional code
	FAX		#PCDATA	Facsimile Telephone Number
	DATE			Date
	DATE		#PCDATA	YYYYMMDD
	TIME		#PCDATA	HHMMSS (UCT)
NOTE: Entities begin with “%” and end with “;”. Entities do not appear as tags in marked up documents. Refer to DTD syntax below and Annex B – DTD.				

For the DTD syntax see Annex B.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.62

### PART 2: SGML MARKUP FOR PATENT BIBLIOGRAPHIC DATA

86. This part of the Recommendation provides SGML tags for all bibliographic fields identified in WIPO Standards ST.9 and ST.30. In doing so some inconsistencies and omissions in WIPO Standards ST.9 and ST.30 had to be resolved.

87. INID codes will be used, where available, as the basis of the generic identifiers for the SGML markup start tags. To conform to SGML rules, which do not allow pure numerics as generic identifiers, numeric tags will be preceded by a "B".

88. An attempt has been made to identify all common data elements which may be present in bibliographic data relating to patent documents – typically all data appearing on the title page of patents and/or data required for electronic data exchange. It is realised that this is a difficult task. In order to meet any particular requirement of a patent office not contained in the tags below two courses of action are proposed:

88.1. In the tags beginning <B000> to <B099> these tags are reserved for Office specific tags which do not fit logically into any other numerical area. In addition, if used, these tags should end with the two letter ST.3 code of the country or organisation using the tag, eg. <B050EP>. The DTD should be changed to add any new tags, any receiving office notified that these tags have been added to and, ideally, WIPO should be notified in order that future revisions may include the proposed tag(s). The DTD indicates that this data is optional.

88.2. In the tags beginning <B100> to <B999>, defined below, it is possible to indicate Office specific tags which fit logically into an existing numerical range. However, if used, these additional tags should end with the two letter ST.3 code of the country or organisation using the tag, eg. <B578US>. The DTD should be changed to add any new tags, any receiving office notified that these tags have been added and, ideally, WIPO should be notified in order that future revisions may include the proposed tag(s). The list of tags below contains examples of EPO, JPO and USPTO tags which fall into this category. These are included as examples only and need not form part of the DTD.

89. An example of the markup of bibliographic data can be found in Annex D.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.63

### PATENT BIBLIOGRAPHIC DATA

TABLE OF SGML TAGS FOR BIBLIOGRAPHIC DATA						
INID	Bibliographic tag			Content		Description
	B000					Office Specific System/File Information
		EPTAGS				EPO-specific tags
			B001EP	#PCDATA		Selective mask for states involved
			B002EP	#PCDATA		Reserved
			B003EP	#PCDATA		Indicator 'no A-doc pub. by EPO'
			B004EP	#PCDATA		Re-establishments of rights indicator
			B005EP	#PCDATA		Printer identification
			B006EP	#PCDATA		Indicator for international applications
			B010EP	#PCDATA		Other rights and legal means of execution
			B011EP	(date, dnum, ctry)		Serial number, date and states
			B020EP	CDATA		Data concerning bibliographic record creation
			B021EP	CDATA		Data concerning bibliographic record correction(s)
			B030EP	CDATA		Legal status data
			B050EP			Free text data
				B051EP	#PCDATA	Language
				B052EP	#PCDATA	Text
			B053EP	#PCDATA		Remarks
			B060EP	CDATA		Receipt of documents data, check data for electronic filing
			B061EP	CDATA		Data relating to fees, financial information
			B070EP	#PCDATA		B Publication technical field
			B078EP	#PCDATA		No opposition filed
		USTAGS				Placeholder for USPTO-specific tags
		JPTAGS				Placeholder for JPO-specific tags
		xxTAGS				Placeholder for other patent offices
10	B100					Document Identification
11		B110		#PCDATA		Number of the patent document, usually the publication number.
12		B120				Plain language designation
			B121	#PCDATA		Plain language designation of the kind of document, eg. European Patent Application
			B121EP	#PCDATA		Descriptive text for B121 (EPO)
13		B130		#PCDATA		Kind of document according to WIPO ST.16
		B131EP		#PCDATA		Extended kind of document code (EPO)
		B140		DATE		Document date, usually date of publication
19		B190		#PCDATA		Publishing country or organization (ST.3)
		B195		#PCDATA		Source furnishing record
20	B200					Domestic Filing Data
21		B210		#PCDATA		Number assigned to the application
		B210EP		#PCDATA		Application number in unstandardised form (EPO)
22		B220		DATE		Application filing date
		B225		DNUM, DATE?, %PARTY;		Receiving Office data eg. date of receipt of application, office address



# **HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION**

Ref.: Standards – ST.32

page: 3.32.64

TABLE OF SGML TAGS FOR BIBLIOGRAPHIC DATA					
INID	Bibliographic tag			Content	Description
23		B230			Other dates
			B231	DATE	Exhibition filing date
			B232	DATE	Complete specification filing date
			B233	DATE	Receipt date at national office
			B234	DATE	Receipt date at international office
			B235	DATE	Date of refusal of application
			B236	DATE	Date of withdrawal
			B237	DATE	Date application deemed withdrawn
			B238EP	DATE	Date of receipt of request for re-establishment of rights
			B238	DATE	Date of application rights re-established
			B239	DATE	Date of revocation
24		B240			Date from which industrial property rights may have effect
			B241	DATE	Date of request for examination
			B242	DATE	Date of despatch of 1st examination report
			B243	DATE	Date of patent maintained as amended
			B244	(date, cntry+)	Request for conversion to national application
			B245	DATE	Date of suspension/interruption of proceedings
			B245EP	#PCDATA	Suspension/interruption indicator (EPO)
			B246	DATE	Date of resumption of proceedings
			B248	DATE	Date of notification rights after appeal
25		B250		#PCDATA	Language of original filing (ISO 639)
		B250EP		#PCDATA	Admissible non-EPO language (EPO)
		B251EP		#PCDATA	Procedural language (EPO)
26		B260		#PCDATA	Language of application publication (ISO 639)
30	B300				Priority Data
31		B310		#PCDATA	Priority application number
		B310EP		#PCDATA	Priority application number in unstandardised form (EPO)
32		B320		DATE	Date of filing of priority application
33		B330		CTRY	Allotting country or organization (ST.3)
34		B340		CTRY	Country party to the Paris Convention (ST.3)
		B345		%DOC;	Patent family Information
		B345EP		%DOC;	INPADOC patent family information (EPO)
40	B400				Public Availability Dates
		B405		%DOC;	Patent bulletin / gazette information
41		B410		%DOC;	Unexamined, not printed document without grant
42		B420		%DOC;	Examined, not printed document without grant
43		B430		%DOC;	Unexamined printed document without grant
44		B440		%DOC;	Examined printed document without grant
45		B450		%DOC;	Printed document with grant (e.g. US Pat)
		B451EP		DATE	Date of announcement (EPO)
46		B460		%DOC;	Document claim(s) only available



# **HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION**

Ref.: Standards – ST.32

page: 3.32.65

TABLE OF SGML TAGS FOR BIBLIOGRAPHIC DATA					
INID	Bibliographic tag			Content	Description
47		B470		%DOC;	Not printed document with grant
		B472			Term of grant
			B473	DATE	Disclaimer date
			B474	#PCDATA	Term of grant
			B475	%DOC;	Lapse of patent
		B476		%DOC;	Invalidation of patent
		B477		%DOC;	Document printed as amended, (eg. EPO B2)
50	B500				Technical Information
51		B510			International Patent Classification (IPC) data
			B511	#PCDATA	Main classification
			B512	#PCDATA	Further classification
			B513	#PCDATA	Additional information
			B514	#PCDATA	Linked indexing code
			B515	#PCDATA	Unlinked indexing code
			B516	#PCDATA	Edition of IPC
			B517EP	#PCDATA	Non-obligatory supplementary class. (EPO)
52		B520			Domestic or national classification
			B521	#PCDATA	Main classification
			B522	#PCDATA	Further classification
			B523	#PCDATA	Additional information
			B524	#PCDATA	Linked indexing code
			B525	#PCDATA	Unlinked indexing code
			B526	#PCDATA	Edition of classification
			B527	#PCDATA	Country code (ST.3)
			B528US	#PCDATA	Digest reference (USPTO)
53		B530		#PCDATA	Universal Decimal Classification
54		B540			Title of the invention
			B541	#PCDATA	Language of title (ISO 639)
			B542	#PCDATA	Title of invention
55		B550			Keywords or descriptors
			B551	#PCDATA	Language (ISO 639)
			B552	#PCDATA	Keywords or descriptors
56		B560			List of prior art documents, if separate from descriptive text, eg. on the title page. Where the search report is a sub-document use <SDOSR> plus the tags below)
			B561	#PCDATA,%PCIT; REL	Patent citation (with B563 and B564)
			B561EP	#PCDATA	Number of copies of citations (EPO)
			B562	#PCDATA,%NCIT;	Non-Patent citation (with B563 and B564)
			B563	#PCDATA	Category of cited document (office dependent)
			B564	#PCDATA	Claims to which cited document is relevant
			B565	DATE	Date of completion of search report
			B565EP	DATE	Date of drawing up and despatch of supplementary search report (EPO)
			B566	DATE	Date of mailing of search report
			B566EP	DATE	Date of despatch of correction to search report (EPO)



# **HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION**

Ref.: Standards – ST.32

page: 3.32.66

TABLE OF SGML TAGS FOR BIBLIOGRAPHIC DATA					
INID	Bibliographic tag			Content	Description
			B567	%PARTY;	Place of search – international search authority
			B568	%DOC;	Publication of search report
			B569	%NAM;	Search report examiner
57		B570			Abstract or claim, use <SDOAB> and <SDOCL> where possible
			B571	#PCDATA	Language of abstract
			B572	%DOC;	Abstract doc. information, eg. abstract number if different to doc. number
			B575	#PCDATA	Language of claims
			B576	%DOC;	Claims doc. info.
			B577	#PCDATA	Number of claims, eg. claims number if different to doc. number
			B578US	#PCDATA	Exemplary claim number (USPTO)
58		B580			Field of search
			B581	#PCDATA	IPC
			B582	#PCDATA	National classification
			B583US	#PCDATA	Field of mechanized search (USPTO)
			B584US	#PCDATA	Other field of search (USPTO)
		B590			Information about specification and drawing, for main data use <SDODE> and <SDODR> respectively
			B591	#PCDATA	Language of specification (ISO 639)
			B592	#PCDATA	Number of text pages
			B595	#PCDATA	Number of drawing sheets
			B596	#PCDATA	Number of figures
			B597	#PCDATA	Number of attached image files
			B598	#PCDATA	Figure number on first (title) page, abstract drawing
			B599EP	#PCDATA	Subsequently filed technical data (EPO)
60	B600				References to other legally or procedurally related domestic patent documents
61		B610		PARENT	Earlier document to which this is an addition
62		B620		PARENT	Earlier application from which the present document has been divided out
		B620EP		PARENT	Other types of relationship (EPO)
			B621EP	%DOC;	Relation for application numbers (EPO)
			B622EP	%DOC;	Relation for publication numbers (EPO)
63		B630			Continuations
			B631	PARENT	Earlier application of which the present document is a continuation
			B632	PARENT	Document of which this is a continuation-in-part
			B633	PARENT	Document of which this is a continuing reissue
64		B640		PARENT	Document being reissued
		B645		PARENT	Document of which this is a reexamination
65		B650		PARENT	Previously published document concerning same application
		B655		PARENT	Document previously published by another country/organisation



# **HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION**

Ref.: Standards – ST.32

page: 3.32.67

TABLE OF SGML TAGS FOR BIBLIOGRAPHIC DATA					
INID	Bibliographic tag			Content	Description
66		B660		PARENT	Document for which this is a substitute
		B665			Patent correction information
			B666	%DOC;	Document being corrected
			B667	#PCDATA	Type of correction
			B668	#PCDATA	Descriptive text relating to correction
67		B670		PARENT	Document on which utility model is based
70	B700				Parties Concerned with the Document
71		B710			Applicant information
			B711	%PARTY;	Name and address
				B711EP    %PARTY;	Name and address for correspondence (EPO)
				B713EP    #PCDATA	Applicant authorisation number (Art.133 (3), EPC) (EPO)
				B716EP    CTRY	Designated contracting states for applicant (EPO)
				B717EP    CTRY	Designated extension states for applicant (EPO)
				B718EP    DATE	Effective date for transfer of rights (EPO)
			B712US	empty	Rule 47 Indicator (USPTO)
	72	B720			Inventor information
			B721	%PARTY;	Name and address
				B724EP    #PCDATA	Waiver by inventor of information pursuant to Rule 17(3), EPC (EPO)
				B725EP    #PCDATA	The inventor has agreed to waive his entitlement to designation, Rule 18(3), EPC. (EPO)
73				B726EP    #PCDATA	Origin of applicant's rights if not inventor: as employee (EPO)
				B727EP    #PCDATA	Origin of applicant's rights if not inventor: under agreement (EPO)
				B728EP    #PCDATA	Origin of applicant's rights if not inventor: as co-inventor (EPO)
				B729EP    #PCDATA	Origin of applicant's rights if not inventor: as successor in title (EPO)
		B730			Grantee (assignee) information
			B731	%PARTY;	Name and address
				B736EP    CTRY	Designated states for grantee (EPO)
				B737EP    CTRY	Designated extension states for grantee (EPO)
				B738EP    DATE	Effective date for transfer of rights (EPO)
			B732US	#PCDATA	Assignee type code (USPTO)
74		B740			Attorney, agent, representative information
			B741	%PARTY;	Attorney or Agent name and address
				B742EP    #PCDATA	General authorisation number (EPO)
		B745			Persons acting upon the document
			B746	%NAM;	Primary examiner
			B747	%NAM;	Assistant examiner
			B748US	#PCDATA	Art Group/Unit (USPTO)
<i>Note:</i> INID Codes 75 and 76 have not been implemented					
		B780			Opposition data
			B781	(dnum,date,kind?) %PARTY;	Opponent data, name and address
			B784	%PARTY;	Attorney or agent information



# **HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION**

Ref.: Standards – ST.32

page: 3.32.68

TABLE OF SGML TAGS FOR BIBLIOGRAPHIC DATA						
INID	Bibliographic tag			Content		Description
				B785	DATE	Opposition deemed not to have been filed
				B786	DATE	Opposition inadmissible
				B787	DATE	Date of rejection of opposition
				B788	DATE	Date of termination of opposition
				B789	#PCDATA	No opposition filed
		B790				Licensee Data
			B791	(dnum,date,kind) %PARTY;		Licensee data, name and address
				B794	%PARTY;	Attorney or agent information
				B796	CTRY	Designated countries for license
80 90	B800					International Convention Data other than the Paris Convention
81		B810		CTRY		Designated States – PCT
		B820		CTRY		PCT Elected States
83		B830				Microorganism deposits information
			B831	#PCDATA		Deposit file number
			B832	#PCDATA		Authority where deposit made
			B833	DATE		Date of deposit
84		B840		CTRY		Designated contracting states
		B844EP				States to which the application/patent is extended (EPO)
			B845EP	%DOC;		Extended state data (EPO)
				B846EP	DATE	End data (withdrawal) (EPO)
85		B850		DATE		Date of PCT Articles 22/39 fulfillment
86		B860				PCT or regional filing information
			B861	%DOC;		Document Identification
			B862	#PCDATA		Filing Language (ISO 639)
			B863	DATE		PCT ° 371 Date
			B864	DATE		PCT ° 102(e) Date
87		B870				PCT or regional publication information
			B871	%DOC;		Document identification
			B872	#PCDATA		Publication language (ISO 639)
88		B880		%DOC;		Deferred publication of search report
89		B890				CMEA Agreement data
			B891	%DOC;		Havana agreement document identification
			B892	DATE		Havana agreement date of property rights
	B900					Miscellaneous data
91		B910		DATE		Date PCT application no longer has effect

For the DTD syntax see Annex B.



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.69

---

[Blank page]



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.70

### INDEX OF ELEMENTS AND ATTRIBUTES

(For Part 1 only)

#### ELEMENTS

<ABOVE> : .....	52	<RTI> : .....	30
<B> : .....	13	<SB> : .....	16
<BAI> : .....	13	<SDOxx> : .....	8
<BCHG> : .....	10	<SL> : .....	24
<BOX> : .....	49	<SQRT> : .....	56
  : .....	12	<SQUARE> : .....	56
<BREAK> : .....	49	<SUB> : .....	52
<CEL> : .....	36	<SUM> : .....	54
<CHE> : .....	43	<SUP> : .....	51
<CHF> : .....	16	<TAB> : .....	32
<CHFBR> : .....	16	<TCH> : .....	34
<CHG> : .....	10	<TO> : .....	55
<CHR> : .....	43	<TSB> : .....	35
<COL> : .....	58	<TSH> : .....	34
<CRF> : .....	44	<TTI> : .....	33
<DD> : .....	23	<TXF> : .....	15
<DF> : .....	19	<U> : .....	15
<DFG> : .....	23	<UL> : .....	24
<DFREF> : .....	10	<VEC> : .....	57
<DL> : .....	23		
<DP> : .....	19	al= .....	33-35
<DT> : .....	23	ALIGN .....	11
<ECHG> : .....	10	align= . .....	11, 12, 16, 46, 47, 50, 52, 58
<ELE> : .....	29	CB .....	34, 36
<EMI> : .....	27	CE .....	34, 36
<EMR> : .....	30	CLOSE .....	53
<F> : .....	46	CO .....	32
<FENCE> : .....	53	compact= .....	22, 23
<FLA> : .....	17	cs= .....	50, 51, 56, 59
<FLAC> : .....	17	CY .....	8, 9
<FOO> : .....	12	DATE .....	8, 10
<FOR> : .....	13	DNUM .....	8
<FRAC> : .....	50	DTD .....	8
<FROM> : .....	55	FILE .....	8, 28, 30
<GAI> : .....	31	file= .....	5, 45
<H> : .....	11	FN .....	12
<HAN> : .....	14	fn= .....	12, 41
<I> : .....	14	FNREF .....	13
<INTEGRAL> : .....	55	fnref= .....	13, 41
<ITALIC> : .....	50	FONT .....	18
<LI> : .....	24	FR .....	18
<LTL> : .....	18	HE .....	18, 27, 30
<MARK> : .....	48	ID .....	27, 29, 30, 31, 43, 46, 47
<MARKREF> : .....	48	id= .....	27, 29, 30, 31, 43, 46-48
<MATRIX> : .....	58	imf= .....	28, 31
<MIDDLE> : .....	54	KIND .....	8
<O> : .....	14	LA .....	9
<OF> : .....	55	level= .....	23, 24
<OL> : .....	23	LS .....	18
<OV> : .....	49	LVL .....	11
<OVER> : .....	51	LX .....	18, 28, 30
<P> : .....	11	LY .....	18, 28, 30
<PATDOC> : .....	8	N .....	11, 19, 20
<PC> : .....	11	num= .....	43, 47, 48
<PCL> : .....	19	numstyle= .....	37
<PILE> : .....	52	OPEN .....	53
<PLEX> : .....	54	POS .....	14
<POWER> : .....	57	pos= .....	14, 15, 49, 51
<PRODUCT> : .....	55	posf= .....	50
<ROMAN> : .....	50	prefix= .....	22
<ROOT> : .....	57	RB .....	35, 36
<ROW> : .....	36	rb= .....	35, 36
		RE .....	35, 36
		re= .....	35, 36
		REFID .....	44, 47



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.71

refid= .....	44, 47
rotation= .....	54?
rs= .....	32, 37
SIZE .....	18
spc= .....	52
STATUS .....	8-10
status= .....	8-10
STYLE .....	14
style= .....	15, 16, 49, 50, 53
SUFFIX .....	50
ti= .....	29
tsize= .....	22
TYPE .....	14
type= .....	14, 15, 53, 54
WI .....	18, 27, 30



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.72

### ANNEX A

#### SGML DECLARATION FOR PATENT DOCUMENTS

The ST.32 SGML Declaration below contains the reference concrete syntax to be applied when exchanging patent data in roman languages. It is not necessary, usually, to include this declaration and/or the DTD with the patent document data being exchanged. The declaration and the DTD, below, shall be deemed as the defaults for this purpose. It is stressed that the declaration may be modified, as required, for a particular language's character set, eg. for Russian or Japanese; or for particular parsers, etc.

If, for any reason, patent data is exchanged using a different character set then the receiving agent should be informed and the declaration modified accordingly. It is strongly advised that, for roman languages, this declaration should be the default since ISO 646 is processable by most systems; although extension, to ASCII 437, for example, may be an acceptable second level alternative.

```
<!SGML "ISO 8879:1986"  
-- Default SGML declaration using the Reference concrete syntax --
```

```
CHARSET  
BASESET "ISO 646-1983//CHARSET  
        International Reference Version (IRV)//ESC 2/5 4/0"  
DESCSET 0    9    UNUSED  
        9    2    9  
        11   2    UNUSED  
        13   1    13  
        14   6    UNUSED  
        20   3    UNUSED  
        23   3    UNUSED  
        26   1    UNUSED  
        27   5    UNUSED  
        32  95    32  
        127  1    UNUSED  
        128 127  128  
CAPACITY SGMLREF  
TOTALCAP 60000  
ENTCAP   35000  
ENTCHCAP 35000  
ELEMCAP  35000  
GRPCAP   35000  
EXGRPCAP 35000  
EXNMCAP  35000  
ATTCAP   35000  
ATTCHCAP 35000  
AVGRPCAP 35000  
NOTCAP   35000  
NOTCHCAP 35000  
IDCAP    35000  
IDREFCAP 35000  
MAPCAP   35000  
LKSETCAP 35000  
LKNMCAP  35000  
SCOPE    DOCUMENT  
SYNTAX  
SHUNCHAR CONTROLS 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17  
        18 19 22 23 24 25 27 28 29 30 31 127  
BASESET "ISO 646-1983//CHARSET  
        International Reference Version (IRV)//ESC 2/5 4/0"  
DESCSET 0    128    0  
FUNCTION RE    13  
        RS    10  
        SPACE 32  
        TAB   SEPCHAR 9  
NAMING   LCNMSTRT ""
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.73

```
UCNMSTRT " "
LCNMCHAR "- ."
UCNMCHAR "- ."
NAMECASE GENERAL YES
          ENTITY NO
DELIM    GENERAL SGMLREF
          SHORTREF SGMLREF
NAMES    SGMLREF
QUANTITY SGMLREF LITLEN 500 ATTCNT 50
FEATURES
MINIMIZE DATATAG NO      OMITTAG YES    RANK      NO      SHORTTAG YES
LINK      SIMPLE NO      IMPLICIT NO    EXPLICIT NO
OTHER     CONCUR NO     SUBDOC   YES 1  FORMAL   YES
APPINFO   NONE>
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.74

### ANNEX B

#### DOCUMENT TYPE DEFINITION FOR PATENT DOCUMENTS

```
<!--
<!-- DOCUMENT TYPE DEFINITION FOR PATENT DOCUMENTS FOR WIPO ST.32
<!-- EPO/USPTO revised standard WIPO ST.32

      DTD (EPO Version: 3.4   Nov 1995)

<!--
<!-- *****
<!--
<!DOCTYPE patdoc [
<!--
<!-- ***** ISO CHARACTER ENTITIES *****
<!-- (C) International Organization for Standardization 1986
      Permission to copy in any form is granted for use with
      conforming SGML systems and applications as defined in
      ISO 8879, provided this notice is included in all copies.
<!--
<!ENTITY % ISOnum PUBLIC
      "ISO 8879-1986//ENTITIES Numeric and Special Graphic//EN">
%ISOnum;
<!ENTITY % ISolat1 PUBLIC
      "ISO 8879-1986//ENTITIES Added Latin 1//EN">
%ISolat1;
<!ENTITY % ISolat2 PUBLIC
      "ISO 8879-1986//ENTITIES Added Latin 2//EN">
%ISolat2;
<!ENTITY % ISOpub PUBLIC
      "ISO 8879-1986//ENTITIES Publishing//EN">
%ISOpub;
<!ENTITY % ISOtech PUBLIC
      "ISO 8879-1986//ENTITIES General Technical//EN">
%ISOtech;
<!ENTITY % ISOgrk1 PUBLIC
      "ISO 8879-1986//ENTITIES Greek Letters//EN">
%ISOgrk1;
<!ENTITY % ISOgrk2 PUBLIC
      "ISO 8879-1986//ENTITIES Monotoniko Greek//EN">
%ISOgrk2;
<!ENTITY % ISOgrk3 PUBLIC
      "ISO 8879-1986//ENTITIES Greek Symbols//EN">
%ISOgrk3;
<!ENTITY % ISOgrk4 PUBLIC
      "ISO 8879-1986//ENTITIES Alternative Greek Symbols//EN">
%ISOgrk4;
<!ENTITY % ISOcyr1 PUBLIC
      "ISO 8879-1986//ENTITIES Russian Cyrillic//EN">
%ISOcyr1;
<!ENTITY % ISOcyr2 PUBLIC
      "ISO 8879-1986//ENTITIES Non-Russian Cyrillic//EN">
%ISOcyr2;
<!ENTITY % ISOamso PUBLIC
      "ISO 8879-1986//ENTITIES Added Math Symbols: Ordinary//EN">
%ISOamso;
<!ENTITY % ISOamsb PUBLIC
      "ISO 8879-1986//ENTITIES Added Math Symbols: Binary Operators//EN">
%ISOamsb;
<!ENTITY % ISOamsr PUBLIC
      "ISO 8879-1986//ENTITIES Added Math Symbols: Relations//EN">
%ISOamsr;
<!ENTITY % ISOamsn PUBLIC
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.75

```
"ISO 8879-1986//ENTITIES Added Math Symbols: Negated Relations//EN">
%ISOamsn;
<!ENTITY % ISOamsa PUBLIC
  "ISO 8879-1986//ENTITIES Added Math Symbols: Arrow Relations//EN">
%ISOamsa;
<!ENTITY % ISOamsc PUBLIC
  "ISO 8879-1986//ENTITIES Added Math Symbols: Delimiters//EN">
%ISOamsc;
<!ENTITY % ISObox PUBLIC
  "ISO 8879-1986//ENTITIES Box and Line Drawing//EN">
%ISObox;
<!ENTITY % ISodia PUBLIC
  "ISO 8879-1986//ENTITIES Diacritical Marks//EN">
%ISodia;
<!--
<!-- (C) International Organization for Standardization 1991
      Permission to copy in any form is granted for use with
      conforming SGML systems and applications as defined in
      ISO 8879, provided this notice is included in all copies.
-->
-->
-->
<!ENTITY % ISOAMSA PUBLIC
  "ISO 9573-13:1991//ENTITIES Added Math Symbols: Arrow Relations//EN">
%ISOAMSA;
<!ENTITY % ISOAMSB PUBLIC
  "ISO 9573-13:1991//ENTITIES Added Math Symbols: Binary Operators//EN">
%ISOAMSB;
<!ENTITY % ISOAMSC PUBLIC
  "ISO 9573-13:1991//ENTITIES Added Math Symbols: Delimiters//EN">
%ISOAMSC;
<!ENTITY % ISOAMSN PUBLIC
  "ISO 9573-13:1991//ENTITIES Added Math Symbols: Negated Relations//EN">
%ISOAMSN;
<!ENTITY % ISOAMSO PUBLIC
  "ISO 9573-13:1991//ENTITIES Added Math Symbols: Ordinary//EN">
%ISOAMSO;
<!ENTITY % ISOAMSR PUBLIC
  "ISO 9573-13:1991//ENTITIES Added Math Symbols: Relations//EN">
%ISOAMSR;
<!ENTITY % ISOICHEM PUBLIC
  "ISO 9573-13:1991//ENTITIES Chemistry//EN">
%ISOICHEM;
<!ENTITY % ISOGRK3 PUBLIC
  "ISO 9573-13:1991//ENTITIES Greek Symbols//EN">
%ISOGRK3;
<!ENTITY % ISOGRK4 PUBLIC
  "ISO 9573-13:1991//ENTITIES Alternative Greek Symbols//EN">
%ISOGRK4;
<!ENTITY % ISOMFRK PUBLIC
  "ISO 9573-13:1991//ENTITIES Math Alphabets: Fraktur//EN">
%ISOMFRK;
<!ENTITY % ISOMOPF PUBLIC
  "ISO 9573-13:1991//ENTITIES Math Alphabets: Open Face//EN">
%ISOMOPF;
<!ENTITY % ISOMSCR PUBLIC
  "ISO 9573-13:1991//ENTITIES Math Alphabets: Script//EN">
%ISOMSCR;
<!ENTITY % ISOPUB PUBLIC
  "ISO 9573-13:1991//ENTITIES Publishing//EN">
%ISOPUB;
<!ENTITY % ISOTECH PUBLIC
  "ISO 9573-13:1991//ENTITIES General Technical//EN">
%ISOTECH;
<!-- (C) International Organization for Standardization 1992
      Permission to copy in any form is granted for use with
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.76

```
conforming SGML systems and applications as defined in
ISO 8879, provided this notice is included in all copies.
<!--ENTITY % ISOCH PUBLIC
"ISO 9573-11:1992//ENTITIES Chemistry//EN">
%ISOCH;-->
<!--
<!-- ENTITY % patspec SYSTEM "patspent.ent"
<!-- Special characters used in patent documents but not defined
in public sets. See Annex C of ST.32.
When including this file reference in the DTD the reference may
have to be modified depending on the system and parser in use.
Note that this entity is commented out of this DTD.
<!-- %patspec;
<!--
<!--
<!-- ***** GROUPED ENTITIES *****
<!--
<!-- Types of embedded images and captions
<!-- ENTITY % img "emi | emr | ele | rti | txf | gai "
>
<!-- Types of highlighting, superscripts, subscripts, and floating accents
<!-- fgfr - figure reference and clrf - claims reference
as forseen for later use
<!-- ENTITY % hil "b | i | o | u | bai | han | chf | fla | ltl | sb | sp "
>
<!-- Types of lists
<!-- ENTITY % lst "dl | ol | sl | ul"
>
<!-- Displayed and in-line math formulae
<!-- altmath is forseen for later use
<!-- ENTITY % math "f | df | dfg | dfref | altmath"
>
<!-- Chemical formulae, chemical reactions, and chemical structure diagrams
<!-- ENTITY % chem "che | chr | crf"
>
<!-- Types of tables
<!-- calstab is forseen for later use
<!-- ENTITY % table "tab | calstab"
>
<!-- Five types of complex material inside or outside of paragraphs
<!-- bioseq is forseen for later use
<!-- ENTITY % compl "(%lst;)|(%table;)|(%math;)|(%chem;)|bioseq"
>
<!-- Name of an individual or organization
<!-- ENTITY % nam "ttl?,(fnm?&snm?),sfx?,iid?,irf?,onm?,syn*,oid?,(odv,did)*"
>
<!-- Components of party
<!-- ENTITY % party "(%nam;),adr?,dtx*,rctry?,nctry?"
>
<!-- Components of the author group
<!-- ENTITY % authgrp "(author|coauth|collab)+"
>
<!-- Components of document identification
<!-- ENTITY % doc "(dnum?&date?),ctry?,kind?,bnum?,dtx*"
>
<!-- ENTITY % extdoc "(dnum&date?),ctry?,kind?,bnum?,dtx*"
>
<!-- Components of a patent document citation
<!-- ENTITY % pcit "(%extdoc;),(%nam;)*,pic*,pnc*"
>
<!-- Components of a non-patent document citation
<!-- ENTITY % ncit "(artcit|bookcit|dbasecit|othcit)"
>
<!-- Contents of a paragraph
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.77

```
<!-- -->
<!ENTITY % ptext "#PCDATA|(%hil;)|(%img;)|(%compl;)|(cit) "
>
<!ENTITY % floats "dp|txf|chg|foo|for|br|pcl|pln|rti|emi"
>
<!-- -->
<!-- ***** GROUPED ATTRIBUTES ***** -->
<!-- -->
<!ENTITY % imgfmt "ST33 | TIFF | CGM | G3 | G4 | EPS |
IGES | JPEG | MPEG | GEM | AI | GIF | PCT | BMP |
PCX | WMF | PGL | WPG"
-- ST33 + de facto standards-->
<!ENTITY % align "center | centre | left | right"
-- alignment -->
<!ENTITY % style "single | double | triple | dash | dots | bold"
-- style of a line or mark -->
<!ENTITY % type "dot | dotdot | dot3 | dot4 | tie | tiebrace | circle |
hat | hacek | acute | grave | cedil | ring | macron |
ogonek | dblac | breve | tilde | vec | rvec |
dyad | caret | prime | dprime | plus | bar | none"
-- type of a line or mark -->

<!-- -->
<!-- ***** PATENT DOCUMENT ***** -->
<!-- -->
<!ELEMENT patdoc - - (sdobi,(sdoab*&sdode?&sdocl*&sdodr?&sdosr?))
+ (%floats;)
>
<!ATTLIST patdoc cy CDATA #IMPLIED -- Country, organis. St.3 --
dnum CDATA #IMPLIED -- Identification number --
date NUMBER #IMPLIED -- date of publication --
file CDATA #IMPLIED -- file identification --
kind CDATA #IMPLIED -- Kind of patent St.16 --
status CDATA #IMPLIED -- Status of the patent doc. --
dtd NUTOKEN #IMPLIED -- Version NUMBER of DTD -->
<!-- -->
<!-- ***** PATENT SUB-DOCUMENTS ***** -->
<!-- -->
<!-- sdobi Bibliography, defined later -->
<!ELEMENT sdoab - o ((h|p|pc| %img;)+) -- Abstract -->
<!ELEMENT sdodr - o (emi+) -- Drawings -->
<!ELEMENT sdode - o (h|p|pc| %img;)+ -- Description -->
<!ELEMENT sdocl - o (h|p| %lst;)+ -- Claims -->
<!ATTLIST (sdobi|sdoab|sdode|sdocl|sdodr|sdosr)
la NAME #IMPLIED -- language (ISO 639) --
cy NAME #IMPLIED -- country code --
status CDATA #IMPLIED
-- Status of the sub-doc. -->
<!-- sdosr Search report defined later -->
<!-- -->
<!-- ***** MAJOR CONTENTS OF SUBDOCUMENTS ***** -->
<!-- -->
<!ELEMENT h - - (%ptext;)+ -- Headers -->
<!ATTLIST h lvl NUMBER #IMPLIED -- Header level --
align (%align;) "left" -- Alignment -->
<!-- -->
<!ELEMENT p - o (%ptext;)+ -- Paragraph elements -->
<!ATTLIST p n NUMBER #IMPLIED -- Reference number --
align (%align;) "left" -- Alignment -->
<!ELEMENT pc - o (%ptext;)+ -- Paragraph continuation -->
<!-- -->
<!-- ***** HIGHLIGHTED ELEMENTS ***** -->
<!-- -->
<!ELEMENT b - - (%ptext;)+ -(b) -- Bold -->
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.78

```
<!ELEMENT bai      - -      (%ptext;)+ -(bai|han)  -- Expanded font      -->
<!ELEMENT han      - -      (%ptext;)+ -(han|bai)  -- Compressed font    -->
<!ELEMENT i        - -      (%ptext;)+ -(i)        -- Italic              -->
<!ELEMENT o        - -      (%ptext;)+ -(o|ov)      -- 'Over' embellishment -->
<!ATTLIST o        pos      (above|mid) "above"    -- pos. of 'over' embell. --
                                     type      (%type;)"bar"        -- type of a line or mark --
                                     style     (%style;)"single"     -- style of a line or mark -->
<!ELEMENT u        - -      (%ptext;)+ -(u|ov)      -- Underscore embellishment -->
<!ATTLIST u        type      (%type;)"bar"        -- type of a line or mark --
                                     style     (%style;)"single"     -- style of a line or mark -->
<!ELEMENT sp       - -      ((%hil;)|(#PCDATA))* -(fla)
                                     -- Superscript in gen. text-->
<!ELEMENT sb       - -      ((%hil;)|(#PCDATA))* -(fla)
                                     -- Subscript in gen. text -->
<!ATTLIST (sp|sb) pos      (PRE|MID|POST) "POST"    -- Position (default post) -->
<!--
<!-- The following elements are for review / forseen for later use
  ELEMENT fgrf - - (#PCDATA)          Reference to a figure
  ELEMENT clrf - - (#PCDATA)          Reference to a claim
<!--
<!-- ***** CONSTRUCTS *****
<!--
<!ELEMENT chf      - -      (((#PCDATA)|(%hil;))+, chfbr)
                                     -- Character fraction      -->
<!ATTLIST chf      align      (%align;)"centre"    -- alignment            -->
<!ELEMENT chfbr    - o      (((#PCDATA)|(%hil;))+ -- Char fraction break  -->
<!ATTLIST chfbr    type      (%type;)"bar"
                                     style     (%style;)"single"
>
<!--
<!ELEMENT fla      - -      (((#PCDATA)|(%hil;))+, flac)
                                     -- Floating accent base  -->
<!ELEMENT flac     - o      ((#PCDATA)|(%hil;))+ -- Floating accent
                                     (upperpart)
                                     -->
<!ATTLIST flac     pos      (ABOVE|MID|BELOW) "ABOVE"
                                     -- Position (default ABOVE) -->
<!--
<!-- ***** ALL KINDS OF LISTS *****
<!--
<!ELEMENT dl       - -      (dt,dd)+              -- Definition list      -->
<!ATTLIST dl       tsize     NUMBER #IMPLIED      -- Term size attribute  --
                                     compact    (%compact)#IMPLIED    -- Spacing between items -->
<!ELEMENT dt       - o      (%ptext;)+            -- Definition term      -->
<!ELEMENT dd       - o      ((%ptext;)|p)+        -- Definition description -->
<!ELEMENT ol       - -      (li)+                -- Ordered list         -->
<!ATTLIST ol       compact    (%compact)#IMPLIED    -- Spacing between items --
                                     level     NUMBER #IMPLIED      -- Nesting level of list --
                                     prefix     CDATA #IMPLIED        -- Prefix for each list item--
                                     numstyle   CDATA #IMPLIED        -- Numbering style      -->
<!ELEMENT sl       - -      (li)+                -- Simple list          -->
<!ATTLIST sl       compact    (%compact)#IMPLIED    -- Spacing between items --
                                     level     NUMBER #IMPLIED      -- Nesting level of list -->
<!ELEMENT ul       - -      (li)+                -- Unordered list       -->
<!ATTLIST ul       st        CDATA #REQUIRED       -- Ulist symbol         --
                                     level     NUMBER #IMPLIED      -- Nesting level of list --
                                     compact    (%compact)#IMPLIED    -- Spacing between items -->
<!ELEMENT li       - o      ((%ptext;)|p)+        -- List item            -->
<!--
<!-- ***** IMAGE RELATED ELEMENTS *****
<!--
<!ELEMENT emi      - o      EMPTY                -- Embedded image       -->
<!ATTLIST emi      id        NUTOKEN #REQUIRED     -- Image identity       --
                                     he         NUMBER #REQUIRED     -- Height in mm         --
                                     wi         NUMBER #REQUIRED     -- Width in mm          --
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.79

```

        file      CDATA      #IMPLIED      -- File name of image      --
        lx        NUMBER     #IMPLIED      -- X-coord 1/10 mm        --
        ly        NUMBER     #IMPLIED      -- Y-coord 1/10 mm        --
        imf        (%imgfmt;) #IMPLIED      -- Format stored emi      --
        ti        (AD|CF|CI|CP|DN|DR|FG|FF|GR|MF|PA|PH|SR|TB|TX|UI)
                #IMPLIED      -- Image type                -->
<!ELEMENT emr    - o      EMPTY            -- Reference to emi      -->
<!ATTLIST emr    id        NUTOKEN #REQUIRED
>
<!ELEMENT ele    - -      (%ptext;)+        -- Figure caption      -->
<!ATTLIST ele    id        NUTOKEN #REQUIRED
>
<!ELEMENT gai    - -      CDATA              -- Gaiji character      -->
<!ATTLIST gai    id        NUTOKEN #REQUIRED
>
<!ELEMENT rti    - -      CDATA              -- Replace text with image -->
<!ATTLIST rti    id        NUTOKEN #REQUIRED  -- rti identity         --
                he        NUMBER #REQUIRED    -- Height in mm         --
                wi        NUMBER #REQUIRED    -- Width in mm          --
                file      CDATA #IMPLIED      -- File name of image   --
                lx        NUMBER #IMPLIED      -- X-coord 1/10 mm      --
                ly        NUMBER #IMPLIED      -- Y-coord 1/10 mm      --
                imf        (%imgfmt;) #IMPLIED -- image format         -->
<!--
<!-- ***** Miscellaneous *****
<!--
<!ELEMENT br     - o      EMPTY            -- Line brea           -->
<!--
<!ELEMENT foo    - -      (%ptext;)+        -- Footnotes           -->
<!ATTLIST foo    fn        NUTOKEN #REQUIRED  -- Footnote id.        -->
<!ELEMENT for     - -      (%ptext;)+        -- Footnote reference   -->
<!ATTLIST for    fnref     NUTOKEN #REQUIRED  -- Footref id.         -->
<!--
<!ELEMENT ltl    - -      CDATA              -- Literal text         -->
<!ATTLIST ltl    wi        NUMBER #IMPLIED    -- Width in mm          -->
<!--
<!ELEMENT chg    - -      (%ptext;)+        -- Change of document parts -->
<!ATTLIST chg    date      NUMBER #REQUIRED    -- Date of change text  --
                status     CDATA #REQUIRED    -- Status of change     -->
<!--
<!-- ***** PATENT STRUCTURE TAGS *****
<!--
<!ELEMENT txf    - o      EMPTY            -- Text frame           -->
<!ATTLIST txf    fr        NUTOKEN #REQUIRED  -- Txf identity         --
                he        NUMBER #REQUIRED    -- Height in mm         --
                wi        NUMBER #REQUIRED    -- Width in mm          --
                lx        NUMBER #IMPLIED      -- X-coord 1/10 mm      --
                ly        NUMBER #IMPLIED      -- Y-coord 1/10 mm      --
                font      CDATA #IMPLIED      -- Font name            --
                size      NUMBER #IMPLIED      -- Font point size      --
                ls        NUTOKEN #IMPLIED     -- Line spacing         -->
<!ELEMENT dp     - o      EMPTY            -- Doc. page break      -->
<!ATTLIST dp     n         NMTOKEN #REQUIRED  -- Doc. page number     -->
<!ELEMENT pcl    - o      EMPTY            -- Page column          -->
<!ATTLIST pcl    n         NMTOKEN #REQUIRED  -- Page column number   -->
<!ELEMENT pln    - o      EMPTY            -- Page line            -->
<!ATTLIST pln    n         NMTOKEN #REQUIRED  -- Page line number     -->
<!--
<!-- ***** Pseudo IN-LINE CHEMISTRY *****
<!--
<!ELEMENT che    - -      (%ptext;)*        -- Chemical formula     -->
<!ATTLIST che    id        ID #IMPLIED      -- chem reaction id     --
                num      CDATA #IMPLIED      -- specific number      -->
<!ELEMENT chr    - -      (%ptext;)*        -- Chemical reaction     -->
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.80

```
<!ATTLIST chr      id      ID      #IMPLIED      -- chem reaction id      --
                  num      CDATA    #IMPLIED      -- specific number      -->
<!ELEMENT crf      - o      EMPTY      -- Reference to che. formula-->
<!ATTLIST crf      refid    IDREF    #REQUIRED      -- reference id.      -->
<!--
<!-- ***** TABLE TAGS - ELEMENTS AND ATTRIBUTES *****
<!--
<!ENTITY % rowcnt "(t|t|?)(tch*,tsh*)(tsb?,cel*)" -- Head + start of body
<!--
<!-- calstab forseen for later use
<!ELEMENT calstab - o      EMPTY      -- CALS table
<!--
<!ELEMENT tab      - -      ((row,(%rowcnt;))|p)+ -- Main structure
<!ATTLIST tab      co      NUMBER  #REQUIRED      -- Number of columns
                  or      (L|P)    "P"      -- Orientation
                  id      CDATA    #IMPLIED      -- Identifier
                  cs      CDATA    #IMPLIED      -- Col separators
                  rs      CDATA    #IMPLIED      -- Row separators
<!ELEMENT tti      - o      (%ptext;)*      -- Table title
<!ATTLIST tti      al      (L|R|C) "C"      -- Text alignment
<!ELEMENT tch      - o      (%ptext;)*      -- Column header
<!ATTLIST tch      cb      NUMBER  #IMPLIED      -- Start column
                  ce      NUMBER  #IMPLIED      -- End column
                  al      (L | R | C) "C"      -- Text alignment
<!ELEMENT tsh      - o      (%ptext;)*      -- Column subhead
<!ATTLIST tsh      cb      NUMBER  #IMPLIED      -- Start column
                  ce      NUMBER  #IMPLIED      -- End column
                  al      (L | R | C) "C"      -- Text alignment
<!ELEMENT tsb      - o      (%ptext;)*      -- Stub field
<!ATTLIST tsb      rb      NUMBER  #IMPLIED      -- Start row
                  re      NUMBER  #IMPLIED      -- End row
                  al      (L | R | C | D | E) "L"
                  -- Text alignment
<!--
<!-- Table row
<!-- Table cell
<!ATTLIST cel      rb      NUMBER  #IMPLIED      -- Start row
                  re      NUMBER  #IMPLIED      -- End row
                  cb      NUMBER  #IMPLIED      -- Start column
                  ce      NUMBER  #IMPLIED      -- End column
                  al      (L | R | C | D | E) "R" -- Text alignment
                  rotation NUMBER  #IMPLIED      -- Rotation of cell contents-->
<!--
<!-- ***** BIOLOGICAL SEQUENCES *****
<!-- This section forseen for later use (PATENTIN)
<!--
<!ELEMENT bioseq - o      EMPTY
                  -- (Stub for later expans.) -->
<!--
<!-- Reference number
<!--
<!-- ***** MATHEMATICAL ENTITIES *****
<!--
<!ENTITY % elem "plex|sum|integral|product|sqrt|root|square|power|fence|
                vec|matrix|pile|tensor|frac|sup|sub"
                  -- Constructs
<!--
<!ENTITY % layout "mark|markref|break|box|middle|ov|roman|italic"
                  -- Layout see %hil;
<!--
<!ENTITY % formel " (%elem; ) | ( %layout; ) | #PCDATA "
                  -- Formula elements
<!--
<!--
<!-- Kinds of fence
<!--
<!-- ***** MATHEMATICAL MAIN ELEMENTS *****
<!--
<!-- The following element allows for alternate math markup schemes.
<!-- NOTATION AAP SYSTEM " "
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.81

```
<!NOTATION EQN SYSTEM " " >
<!NOTATION GML SYSTEM " " >
<!NOTATION TeX SYSTEM " " >
<!NOTATION WP SYSTEM " " >
<!NOTATION Word SYSTEM " " >
<!ELEMENT altmath - - CDATA -- Alternate math markup -->
<!-- ATTLLIST altmath system NOTATION (AAP|EQN|GML|TeX|WP|Word)
Alternate markup systems -->
<!--
<!-- The following elements, etc. are ISO/TR 9573 based and recommended -->
<!--
<!ELEMENT f - - (%formel;)+ -(br|matrix|pile|frac|mark|markref)
-- In-line formula -->
<!ELEMENT df - - (%formel;)+ -(br) -- Display formula -->
<!ATTLLIST df align (%align;) "centre" -- Alignment --
num CDATA #IMPLIED -- Display formula number --
id ID #IMPLIED -- Display formula id -->
<!ELEMENT dfg - - (df+)-->
<!ATTLLIST dfg align (%align;) "centre" -- Alignment --
num CDATA #IMPLIED -- Display formula group num--
id ID #IMPLIED -- Display formula group id -->
<!ELEMENT dfref - o EMPTY -- Formula reference -->
<!ATTLLIST dfref refid IDREF #REQUIRED -- Formula id --
page (yes|no) "yes" -- page reference -->
<!ELEMENT sup - - (%formel;)+ -- Superscript -->
<!ELEMENT sub - - (%formel;)+ -- Subscript -->
<!ATTLLIST (sup|sub) pos (PRE|MID|POST) "POST" -- Position (default post) -->
<!ELEMENT frac - - ((%formel;)+, over) -- Fraction numerator -->
<!ATTLLIST frac align (%align;) "centre" -- Fraction alignment -->
<!ELEMENT over - o ((%formel;)+) -- Fraction denominator -->
<!--
<!-- ***** CONSTRUCTS WITH 'FROM' 'TO' 'OF' ***** -->
<!--
<!ELEMENT plex - - (operator,(from?&to?)?,of?)
-- Generalized operator -->
<!ELEMENT operator o o (#PCDATA) -- Operator symbol -->
<!ELEMENT from - o (%formel;)+ -- Start index for operator -->
<!ELEMENT to - o (%formel;)+ -- End index for operator -->
<!ELEMENT of - o (%formel;)+ -- Formula operated upon -->
<!ELEMENT sum - - ((from?&to?)?,of?) -- Summation -->
<!ELEMENT integral - - ((from?&to?)?,of?) -- Integral -->
<!ELEMENT product - - ((from?&to?)?,of?) -- Product -->
<!--
<!-- ***** ROOTS AND POWERS ***** -->
<!--
<!ELEMENT sqrt - - (%formel;)+ -- Square root -->
<!ELEMENT root - - ((%formel;)+,of) -- Root: degree/of -->
<!ELEMENT square - - (%formel;)+ -- Square -->
<!ELEMENT power - - ((%formel;)+,of) -- Power: degree/of -->
<!--
<!-- ***** FENCES AND HIGHLIGHTS ***** -->
<!--
<!ELEMENT fence - - (%formel;)+ -- Brackets,parentheses etc.-->
<!ATTLLIST fence type (%fency;) "paren" -- Fence kind code --
style (%style;) "single" -- Style of fence --
open CDATA #IMPLIED -- Special open char --
close CDATA #IMPLIED -- Special close char -->
<!--
<!-- ***** VECTORS, MATRICES, PILES ***** -->
<!--
<!ELEMENT vec - - (%formel;)+ -- Designates vector name -->
<!ELEMENT matrix - - (col+) -- Matrix is a set of cols. -->
<!ELEMENT col - - ((%formel;)+,above+) -- Top element, above+ -->
<!ATTLLIST col align (%align;) "centre"
```



# HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.82

```

-- Column alignment -->
<!ELEMENT pile - - ((%formel;)+,above+) -- Top element, above+ -->
<!ATTLIST pile spc (NORM | CLOSE) "NORM" -- Spacing --
               align (%align;) "centre" -- Alignment -->
<!ELEMENT above - o ((%formel;)+) -- Lower layers -->
<!--
<!-- ***** LAYOUT ORIENTED CODING ***** -->
<!--
<!ELEMENT mark - o EMPTY -- Mark for alignment -->
<!ATTLIST mark id ID #REQUIRED -- Reference id for the mark-->
<!ELEMENT markref - o EMPTY -- Reference to a mark -->
<!ATTLIST markref refid IDREF #REQUIRED -- Id of the mark referred -->
<!ELEMENT break - o EMPTY -- Break point in formula -->
<!ATTLIST break type (required|optional) "required"
-- type of break -->
<!ELEMENT box - - (%formel;)+ -- Box around a formula -->
<!ELEMENT roman - - (%formel;)+ -(roman) -- Roman -->
<!ELEMENT italic - - (%formel;)+ -(italic) -- Italic -->
<!ELEMENT middle - - (#PCDATA) -- Middle of a space -->
<!ATTLIST (box|middle) style (%style;) "single" -- Line styles -->
<!ELEMENT ov - - (%formel;)+ -- 'Over' embellishment -->
<!ATTLIST ov pos (above|below|mid) "above"
-- position of 'over' emb. --
               type (%type;) "bar" -- type of a line or mark --
               style (%style;) "single" -- style of a line or mark -->
<!ELEMENT tensor - - (%formel;)+ -- tensors -->
<!ATTLIST tensor posf (sub|sup) "sup" -- position of the suffix --
               suffix CDATA #REQUIRED -- value of the first suffix-->
<!--
<!-- ***** BIBLIOGRAPHY SUB-DOCUMENT ***** -->
<!--
<!ELEMENT sdobi - o (B000?,B100,B200?,B300?,B400?,B500?,B600?,
                    B700?,B800?,B900?) +(bchg|echg)
>
<!ELEMENT bchg - o EMPTY -- Begin change -->
<!ATTLIST bchg date NUMBER #REQUIRED -- Date of change --
               status CDATA #REQUIRED -- Status of change -->
<!ELEMENT echg - o EMPTY -- End change -->
<!--
<!-- ***** SYSTEM/FILE INFORMATION ***** -->
<!--
<!ELEMENT B000 - o (eptags?,ustags?,jptags?,xxtags?)
>
<!-- The following tags are for the specific use of the EPO - -->
<!-- they are inserted as an example and may be changed at the -->
<!-- discretion of the EPO. -->
<!ELEMENT eptags - o
                    (B001EP?,B002EP?,B003EP?,B004EP?,B005EP?,
                     B006EP?,B010EP?,B020EP?,B021EP?,B030EP?,
                     B050EP?,B053EP*,B060EP?,B061EP?,B070EP?,B078EP?)
>
<!ELEMENT B001EP - o (#PCDATA) -- Select. mask for states
-- involved -->
<!ELEMENT B002EP - o (#PCDATA) -- Reserved -->
<!ELEMENT B003EP - o (#PCDATA) -- Indicator 'no A-doc pub.
-- by EPO' -->
<!ELEMENT B004EP - o (#PCDATA) -- Re-establishments of
-- rights indicator -->
<!ELEMENT B005EP - o (#PCDATA) -- Printer id. -->
<!ELEMENT B006EP - o (#PCDATA) -- Ind. for inter. applic. -->
<!ELEMENT B010EP - o (B011EP)+ -- Other rights and legal
-- means of execution -->
<!ELEMENT B011EP - o (date,dnum,ctry*) -- Serial number date and
-- states -->

```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.83

```
<!ELEMENT B020EP - -      CDATA          -- Biblio rec. creation    -->
<!ELEMENT B021EP - -      CDATA          -- Biblio. rec. correction  -->
<!ELEMENT B030EP - -      CDATA          -- Legal status data      -->
<!ELEMENT B050EP - o      (B051EP,B052EP)+ -- Free text data        -->
<!ELEMENT B051EP - o      (#PCDATA)      -- Language               -->
<!ELEMENT B052EP - o      (#PCDATA)      -- Free text              -->
<!ELEMENT B053EP - o      (#PCDATA)      -- Remarks                -->
<!ELEMENT B060EP - -      CDATA          -- Check data             -->
<!ELEMENT B061EP - -      CDATA          -- Data relating to fees   -->
<!ELEMENT B070EP - o      (#PCDATA)      -- B pub. technical field  -->
<!ELEMENT B078EP - o      (DATE)         -- Date of 'no oppo. filed' -->
<!--
<!ELEMENT ustags - o      EMPTY
>
<!ELEMENT jptags - o      EMPTY
>
<!--
<!ELEMENT xxtags - o      EMPTY
>
<!--
<!-- ***** DOCUMENT IDENTIFICATION *****
<!-- ***** B100 IS REQUIRED WITHIN SDOBI *****
<!--
<!ELEMENT B100 - o      (B110,B120?,B130,B131EP?,B140,B190,B195?)
>
<!ELEMENT B110 - o      (#PCDATA)          -- Doc. number REQUIRED    -->
<!--
<!ELEMENT B120 - o      (B121,B121EP?)     -- Plain lang. designation -->
<!ELEMENT B121 - o      (#PCDATA)          -- Plain lang. designation -->
<!ELEMENT B121EP - o    (#PCDATA)          -- Descrip. text for      -->
                                   B121 (EPO)
<!--
<!ELEMENT B130 - o      (#PCDATA)          -- Doc. kind (ST.16)
                                   REQUIRED
<!ELEMENT B131EP - o    (#PCDATA)          -- Ext. kind of
                                   doc. code (EPO)
<!ELEMENT B140 - o      (date)             -- Doc. date (publication
                                   or issue) REQUIRED
<!ELEMENT B190 - o      (#PCDATA)          -- Publishing country or org.
                                   (ST.3) REQUIRED
<!ELEMENT B195 - o      (#PCDATA)          -- Source furnishing record -->
<!--
<!-- ***** DOMESTIC FILING DATA *****
<!--
<!ELEMENT B200 - o      (B210,B210EP?,B220,B225?,B230?,B240?,
                                   B250?,B250EP?,B251EP?,B260?)
>
<!ELEMENT B210 - o      (#PCDATA)          -- Application number      -->
<!ELEMENT B210EP - o    (#PCDATA)          -- Application number in
                                   unstandardised form (EPO)
<!ELEMENT B220 - o      (date)             -- Application filing date -->
<!ELEMENT B225 - o      (dnum, date?, %party;) -- Receiving office data  -->
<!--
<!ELEMENT B230 - o      (B231?,B232?,B233?,B234?,B235?,
                                   B236?,B237?,B238EP?,B238?,B239?)
>
<!--
<!-- Other dates
<!ELEMENT B231 - o      (date)             -- Exhibition filie        -->
<!ELEMENT B232 - o      (date)             -- Complete spec. fil. date -->
<!ELEMENT B233 - o      (date)             -- Receipt date nat. office -->
<!ELEMENT B234 - o      (date)             -- Receipt date nat. office -->
<!ELEMENT B235 - o      (date)             -- Date of refusalplication -->
<!ELEMENT B236 - o      (date)             -- Date of withdra appl.   -->
<!ELEMENT B237 - o      (date)             -- Date appl. withdrawn    -->
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.84

```
<!ELEMENT B238EP - o      (date)          -- Date of receiptquest for
                                re-establishment of rights-->
<!ELEMENT B238 - o      (date)          -- Date appl. reest.      -->
<!ELEMENT B239 - o      (date)          -- Date of revocation      -->
<!--
<!ELEMENT B240 - o      (B241?,B242?,B243?,B244?,B245?,B245EP?,B246?,B248?)
>
<!--
Effective dates for property rights      -->
<!ELEMENT B241 - o      (date)          -- Date of request for exam.-->
<!ELEMENT B242 - o      (date)          -- Date of despatch of 1st.
                                exam. report -->
<!ELEMENT B243 - o      (date)          -- Date pat. maint. as
                                amended -->
<!ELEMENT B244 - o      (date,ctry+)    -- Request for conversion
                                to natl. appl. -->
<!ELEMENT B245 - o      (date)          -- Suspension/interruption
                                of proceedings -->
<!ELEMENT B245EP - o      (#PCDATA)     -- Suspension/interruption
                                indicator -->
<!ELEMENT B246 - o      (date)          -- Date of resumption of
                                proceedings -->
<!ELEMENT B248 - o      (date)          -- Date of notification
                                rights after appeal-->
<!--
<!ELEMENT B250 - o      (#PCDATA)     -- Language of original
                                filing (ISO 639) -->
<!ELEMENT B250EP - o      (#PCDATA)     -- Admissable non-EPO
                                language (EPO) -->
<!ELEMENT B251EP - o      (#PCDATA)     -- Procedure language (EPO) -->
<!ELEMENT B260 - o      (#PCDATA)     -- Language of application
                                publ. ISO 639 -->
<!--
<!-- ***** FOREIGN PRIORITY DATA *****
<!--
<!ELEMENT B300 - o      ((B310,B310EP?,B320,B330,B340?)*,(B345?,B345EP?)*
>
<!ELEMENT B310 - o      (#PCDATA)     -- Priority appli. number -->
<!ELEMENT B310EP - o      (#PCDATA)     -- Priority appli. number in
                                unstandardised form (EPO)-->
<!ELEMENT B320 - o      (date)          -- Fil. date of prio. app. -->
<!ELEMENT B330 - o      (ctry)          -- Publ. ctry or org. (ST.3)-->
<!ELEMENT B340 - o      (ctry)          -- Paris Union ctry (ST.3) -->
<!ELEMENT B345 - o      (%doc;)         -- Patent family info. -->
<!ELEMENT B345EP - o      (%doc;)         -- INPADOC pat.family
                                info. (EPO)-->
<!--
<!-- ***** PUBLIC AVAILABILITY DATES AND TERM OF PROTECTION *
<!--
<!ELEMENT B400 - o      (B405?,(B410?,B420?,B430?,B440?,
                                B450?,B460?,B470?),B451EP?,B472?,B476?,B477?)
>
<!ELEMENT B405 - o      (%doc;)         -- Pat. bull./gaz. info. -->
<!ELEMENT B410 - o      (%doc;)         -- Unexam. not printed doc.
                                without grant -->
<!ELEMENT B420 - o      (%doc;)         -- Examined not printed
                                document without grant -->
<!ELEMENT B430 - o      (%doc;)         -- Unexamined printed document
                                without grant -->
<!ELEMENT B440 - o      (%doc;)         -- Examined printed document
                                without grant -->
<!ELEMENT B450 - o      (%doc;)         -- Printed document with
                                grant (USPat) -->
<!ELEMENT B451EP - o      (date)          -- Date of announc. (EPO) -->
<!ELEMENT B460 - o      (%doc;)         -- Doc. claims only avail. -->
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.85

```
<!ELEMENT B470    - o      (%doc;)          -- Not printed document
                                   with grant      -->
<!ELEMENT B472    - o      (B473?,B474?,B475?) -- Term of grant      -->
<!ELEMENT B473    - o      (date)             -- Disclaimer date    -->
<!ELEMENT B474    - o      (#PCDATA)          -- Term of grant      -->
<!ELEMENT B475    - o      (%doc;)+           -- Lapse of patent    -->
<!ELEMENT B476    - o      (%doc;)            -- Invalidation of patent -->
<!ELEMENT B477    - o      (%doc;)            -- Document printed as amended,
                                   -->
<!--
<!-- ***** TECHNICAL INFORMATION *****
<!--
<!ELEMENT B500    - o      (B510?,B520*,B530?,B540?,B550?,
                                   B560?,B570?,B580?,B590?)
>
<!--
<!-- ***** IPC DATA *****
<!--
<!ELEMENT B510    - o      (B516?,B511,(B512|B513|B514|B515)*,B517EP?)
>
<!--
International Patent Classification      -->
<!ELEMENT B516    - o      (#PCDATA)          -- Edition, version of IPC -->
<!ELEMENT B511    - o      (#PCDATA)          -- Main classification     -->
<!ELEMENT B512    - o      (#PCDATA)          -- Further classification  -->
<!ELEMENT B513    - o      (#PCDATA)          -- Additional information  -->
<!ELEMENT B514    - o      (#PCDATA)          -- Linked indexing code    -->
<!ELEMENT B515    - o      (#PCDATA)          -- Unlinked indexing code  -->
<!ELEMENT B517EP  - o      (#PCDATA)          -- Non-obligatory suppl.
                                   class. (EPO) -->
<!--
<!-- ***** NATIONAL CLASSIFICATION DATA *****
<!--
<!ELEMENT B520    - o      (B527,B526?,B521,(B522|B523|B524|B525|B528US)*)
>
<!--
Domestic or National classification      -->
<!ELEMENT B521    - o      (#PCDATA)          -- Main classification     -->
<!ELEMENT B522    - o      (#PCDATA)          -- Further classification  -->
<!ELEMENT B523    - o      (#PCDATA)          -- Additional information  -->
<!ELEMENT B524    - o      (#PCDATA)          -- Linked indexing code    -->
<!ELEMENT B525    - o      (#PCDATA)          -- Unlinked indexing code  -->
<!ELEMENT B526    - o      (#PCDATA)          -- Edition, version       -->
<!ELEMENT B527    - o      (#PCDATA)          -- Country code (ST.3)    -->
<!ELEMENT B528US  - o      (#PCDATA)          -- Digest reference       -->
<!--
<!-- *****
<!--
<!ELEMENT B530    - o      (#PCDATA)          -- Universal Dec. Class.  -->
<!--
<!ELEMENT B540    - o      (B541?,B542)+       -- Title                  -->
<!ELEMENT B541    - o      (#PCDATA)          -- Lang. of title (ISO 639) -->
<!ELEMENT B542    - o      (#PCDATA)          -- Title of invention     -->
<!--
<!ELEMENT B550    - o      (B551?,B552*)*      -- Keywords and descriptors -->
<!ELEMENT B551    - o      (#PCDATA)          -- Lang. of keywords
                                   and descriptors -->
<!ELEMENT B552    - o      (#PCDATA)          -- Keywords and descriptors -->
<!--
<!-- ***** CITATION, SEARCH REPORT DATA *****
<!--
<!ELEMENT B560    - o      ((B561,B563?,B564*)*,(B562,B563?,B564*)*,
                                   B561EP?,B565?,B565EP?,
                                   B566?,B566EP?,B567?,B568?,B569?)
                                   -- Citations and mini-search report -->
<!--
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.86

```
<!-- ***** If the SEARCH REPORT is a separate sub-document use the -->
<!--          tags below within the SDOSR tag - see below  ***** -->
<!-- -->
<!ELEMENT B561    - o      (#PCDATA|((%pcit;),rel*))
                                -- Patent doc. citation -->
<!ELEMENT B561EP  - o      (#PCDATA)
                                -- Number of copies of
                                citations (EPO) -->
<!ELEMENT B562    - o      (#PCDATA|(%ncit;))
                                -- Non-patent doc. citation -->
<!ELEMENT B563    - o      (#PCDATA)
                                -- Category of cited doc
                                office dependent -->
<!ELEMENT B564    - o      (#PCDATA)
                                -- Claim to which cited
                                doc is relevant -->
<!ELEMENT B565    - o      (date)
                                -- Date of completion of
                                search report -->
<!ELEMENT B565EP  - o      (date)
                                -- Date of drawing up
                                suppl.search report (EPO)-->
<!ELEMENT B566    - o      (date)
                                -- Date of mailing of
                                search report -->
<!ELEMENT B566EP  - o      (date)
                                -- Date of despatch of
                                correction to search
                                report (EPO) -->
<!ELEMENT B567    - o      (%party;)
                                -- Place of search,
                                intl. search authority -->
<!ELEMENT B568    - o      (%doc;)
                                -- Publ. of ser. report -->
<!ELEMENT B569    - o      (%nam;)
                                -- Search report examiner -->
<!-- -->
<!-- ***** ABSTRACT & CLAIMS DATA ***** -->
<!-- -->
<!ELEMENT B570    - o      (B571?,B572?,B575*,B576?,B577,B578US*)
                                -- Abstract or claim -->
<!ELEMENT B571    - o      (#PCDATA)
                                -- Lang. of abstr.(ISO 639) -->
<!ELEMENT B572    - o      (%doc;)
                                -- Abstract doc. info. -->
<!ELEMENT B575    - o      (#PCDATA)
                                -- Lang. of claims (ISO 639)-->
<!ELEMENT B576    - o      (%doc;)
                                -- Claims doc. info. -->
<!ELEMENT B577    - o      (#PCDATA)
                                -- Number of claims -->
<!ELEMENT B578US  - o      (#PCDATA)
                                -- Exemplary claim number -->
<!-- -->
<!-- ***** -->
<!-- -->
<!ELEMENT B580    - o      ((B581|B582|B583US|B584US)*)
                                -- Field of search -->
<!ELEMENT B581    - o      (#PCDATA)
                                -- IPC -->
<!ELEMENT B582    - o      (#PCDATA)
                                -- National classification -->
<!ELEMENT B583US  - o      (#PCDATA)
                                -- Field of mechan. search -->
<!ELEMENT B584US  - o      (#PCDATA)
                                -- Other field of search -->
<!-- -->
<!ELEMENT B590    - o      (B591?,B592?,B595?,B596?,B597?,B598*)
                                -- Spec. & drawings -->
<!ELEMENT B591    - o      (#PCDATA)
                                -- Lang. of spec. ISO 639 -->
<!ELEMENT B592    - o      (#PCDATA)
                                -- Number of text pages -->
<!ELEMENT B595    - o      (#PCDATA)
                                -- Number of drawing sheets -->
<!ELEMENT B596    - o      (#PCDATA)
                                -- Number of figures -->
<!ELEMENT B597    - o      (#PCDATA)
                                -- No. of attached
                                image files -->
<!ELEMENT B598    - o      (#PCDATA)
                                -- Figure number on
                                first (title) page -->
<!-- -->
<!-- ***** RELATED PATENTS OR APPLICATIONS ***** -->
<!-- -->
<!ELEMENT B600    - o      ((B610|B620|B620EP|B630|B640|
                                B645|B650|B655|B660|B665|B670)*)
>
<!--          Information about a document which is a parent through: -->
<!ELEMENT B610    - o      (parent)
                                -- Earlier doc. to which
```



# HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.87

```

                                this is an addition -->
<!ELEMENT B620    - o      (parent)      -- Earlier application from
                                which the present doc.
                                has been divided out -->
<!--
<!ELEMENT B620EP - o      (parent|B621EP|B622EP)
                                -- Other types of relationship (EPO) -->
<!ELEMENT B621EP - o      (%doc;)      -- Relation for app.no.(EPO)-->
<!ELEMENT B622EP - o      (%doc;)      -- Relation for pub.no.(EPO)-->
<!ELEMENT B630    - o      (B631|B632|B633) -- Continuations -->
<!ELEMENT B631    - o      (parent)      -- Continuation -->
<!ELEMENT B632    - o      (parent)      -- Continuation-in-part -->
<!ELEMENT B633    - o      (parent)      -- Continuing reissue -->
<!--
<!ELEMENT B640    - o      (parent)      -- Reissue -->
<!ELEMENT B645    - o      (parent)      -- Reexamination -->
<!ELEMENT B650    - o      (parent)      -- Same application -->
<!ELEMENT B655    - o      (parent)      -- Document previously
                                published by another
                                country/organisation -->
<!ELEMENT B660    - o      (parent)      -- Substitution -->
<!ELEMENT B665    - o      (B666,B667,B668?) -- Pat. correction info. -->
<!ELEMENT B666    - o      (%doc;)      -- Document being corrected -->
<!ELEMENT B667    - o      (#PCDATA)     -- Type of correction -->
<!ELEMENT B668    - o      (#PCDATA)     -- Descriptive text
                                relating to correction -->
<!ELEMENT B670    - o      (parent)      -- Basis of utility model -->
<!--
<!ELEMENT parent o o      (dnum?,cdoc*,pdoc?,psta?,ppub?)
>
<!--      dnum      document number -->
<!ELEMENT cdoc    - o      (%doc;)+      -- child doc. id. -->
<!ELEMENT pdoc    - o      (%doc;)+      -- parent doc. id. -->
<!ELEMENT psta    - o      (#PCDATA)     -- parent status code -->
<!ELEMENT ppub    - o      (%doc;)      -- id of patent
                                associated with parent -->
<!--
<!-- ***** PARTIES CONCERNED WITH THE DOCUMENT ***** -->
<!--
<!ELEMENT B700    - o      (B710?,B720?,B730?,B740?,B745?,B780?,B790?)
>
<!--
<!-- ***** APPLICANTS ***** -->
<!--
<!ELEMENT B710    - o      (B711,B712US?)+ -- Applicant information -->
<!ELEMENT B711    - o      (%party;,B711EP?,B713EP?,(B716EP?,B717EP?,B718EP?)*
                                -- Applicant name and add. -->
<!ELEMENT B711EP - o      (%party;)      -- Applicant name and add. for
                                for correspondence (EPO) -->
<!ELEMENT B713EP - o      (#PCDATA)     -- Applicant authorisation
                                no. Art.133(3) (EPO) -->
<!ELEMENT B712US - o      EMPTY      -- Rule 47 indicator -->
<!ELEMENT B716EP - o      (ctry)+      -- Des. Contr. States
                                for applicant (EPO) -->
<!ELEMENT B717EP - o      (ctry)+      -- Des. extension states
                                for applicant (EPO) -->
<!ELEMENT B718EP - o      (date)      -- Effective date for
                                transfer of rights (EPO) -->
<!--
<!-- ***** INVENTORS ***** -->
<!--
<!ELEMENT B720    - o      (B721+)      -- Inventor information -->
<!ELEMENT B721    - o      (%party;,B724EP?,B725EP?,B726EP?,
                                B727EP?,B728EP?,B729EP?)

```

## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.88

```

-- Inventor name and addr. -->
<!ELEMENT B724EP - o      (#PCDATA)      -- Waiver by the inventor of
-- information pursuant
-- to Rule 17(3), EPC (EPO) -->
<!ELEMENT B725EP - o      (#PCDATA)      -- The inventor has agreed
-- to waive his entitlement
-- to designation (EPO) -->
<!ELEMENT B726EP - o      (#PCDATA)      -- Origin of applicant's
-- rights if not inventor:
-- as employee (EPO) -->
<!ELEMENT B727EP - o      (#PCDATA)      -- Origin of applicant's
-- rights if not inventor:
-- under agreement (EPO) -->
<!ELEMENT B728EP - o      (#PCDATA)      -- Origin of applicant's
-- rights if not inventor:
-- as co-inventor (EPO) -->
<!ELEMENT B729EP - o      (#PCDATA)      -- Origin of applicant's
-- rights if not inventor: as
-- successor in title (EPO) -->
<!-- -->
<!-- ***** GRANTEES ***** -->
<!-- -->
<!ELEMENT B730 - o      (B731,B732US?)+ -- Grantee information -->
<!ELEMENT B731 - o      (%party;,(B736EP?,B737EP?,B738EP?)* ) --
-- Grantee name and address -->
<!ELEMENT B732US - o      (#PCDATA)      -- Assignee type code -->
<!ELEMENT B736EP - o      (ctry)+ -- Designated states for
-- grantee (EPO) -->
<!ELEMENT B737EP - o      (ctry)+ -- Designated extension
-- states for grantee (EPO) -->
<!ELEMENT B738EP - o      (date) -- Effective date for
-- transfer of rights (EPO) -->
<!-- -->
<!-- ***** REPRESENTATIVES ***** -->
<!-- -->
<!ELEMENT B740 - o      (B741+) -- Attorney, agent,
-- representative info. -->
<!ELEMENT B741 - o      (%party; ,B742EP?) -- Attorney name and addr. -->
<!ELEMENT B742EP - o      (#PCDATA)      -- General author. no.(EPO) -->
<!-- -->
<!-- ***** -->
<!-- -->
<!ELEMENT B745 - o      (B746,B747*,B748US?) -- Persons acting
-- upon the document -->
<!ELEMENT B746 - o      (%nam;) -- Primary examiner name -->
<!ELEMENT B747 - o      (%nam;) -- Assistant examiner name -->
<!ELEMENT B748US - o      (#PCDATA)      -- Art group/unit (USPTO) -->
<!-- -->
<!-- ***** OPPOSITION DATA ***** -->
<!-- -->
<!ELEMENT B780 - o      ((B781)*,(B787|B788|B789)? ) -- Opposition data -->
<!ELEMENT B781 - o      ((dnum,date,kind),(%party;),B784?,
-- (B785|B786)? ) -- Opponent data -->
<!ELEMENT B784 - o      (%party;) -- Attorney or agent info. -->
<!ELEMENT B785 - o      (date) -- Oppo. deemed not
-- to have been filed -->
<!ELEMENT B786 - o      (date) -- Opposition inadmissible -->
<!ELEMENT B787 - o      (date) -- Date of reject. of oppo. -->
<!ELEMENT B788 - o      (date) -- Date of term. of oppo. -->
<!ELEMENT B789 - o      (#PCDATA)      -- No opposition filed -->
<!-- -->
<!-- ***** LICENCE DATA ***** -->
<!-- -->

```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.89

```
<!ELEMENT B790 - o (B791)* -- Licensee data -->
<!ELEMENT B791 - o ((dnum,date,kind?),(%party;),(B794?,B796?))
-- Licence data,
-- name and address -->
<!ELEMENT B794 - o (%party;) -- Attorney or agent info. -->
<!ELEMENT B796 - o (ctry)+ -- Design. ctry for license -->
<!--
<!-- ***** DATA RELATED TO INTERNATIONAL CONVENTIONS *
<!--
<!ELEMENT B800 - o (B810?,B820?,B830?,B840?,B844EP?,B850?,B860?,B870?,
B880?,B890?)+
>
<!ELEMENT B810 - o (ctry)+ -- Designated states - PCT -->
<!ELEMENT B820 - o (ctry)+ -- PCT elected states -->
<!ELEMENT B830 - o (B831,B832?,B833?) -- Micro. deposit info. -->
<!ELEMENT B831 - o (#PCDATA) -- Deposit file number -->
<!ELEMENT B832 - o (#PCDATA) -- Authority where
deposit was made -->
<!ELEMENT B833 - o (date) -- Date of deposit -->
<!--
<!ELEMENT B840 - o (ctry)+ -- Design. contract. states -->
<!ELEMENT B844EP - o (B845EP)+ -- States to which the patent
is extended (EPO) -->
<!ELEMENT B845EP - o (ctry,date?,B846EP?) -- Extended state data (EPO)-->
<!ELEMENT B846EP - o (date) -- End date (withdrawal) -->

<!ELEMENT B850 - o (date) -- Date PCT Art. 22/39 fulf.-->
<!--
<!ELEMENT B860 - o (B861,B862?,B863?,B864?)
-- PCT or reg. filing info. -->
<!ELEMENT B861 - o (%doc;) -- Document identification -->
<!ELEMENT B862 - o (#PCDATA) -- Filing language (ISO 639)-->
<!ELEMENT B863 - o (date) -- PCT section 371 date -->
<!ELEMENT B864 - o (date) -- PCT section 102(e) date -->
<!--
<!ELEMENT B870 - o (B871,B872?) -- PCT or region. publ.info.-->
<!ELEMENT B871 - o (%doc;) -- Document identification -->
<!ELEMENT B872 - o (#PCDATA) -- PCT pub. lang. (ISO 639) -->
<!--
<!ELEMENT B880 - o (%doc;) -- Deferred publ. of s.rep. -->
<!--
<!ELEMENT B890 - o (B891,B892?) -- CMEA agreement -->
<!ELEMENT B891 - o (%doc;) -- Havana Agreement doc.id. -->
<!ELEMENT B892 - o (date) -- Havana Agreement date
property rights -->
<!--
<!ELEMENT B900 - o (B910?) -- Miscellaneous -->
<!ELEMENT B910 - o (date) -- Date PCT application
no longer has effect -->
<!--
<!-- ***** TAGS USED IN COMMON BY SEVERAL ELEMENTS ***
<!--
<!ELEMENT cit - o (#PCDATA,((%pcit;)|(%ncit;)),rel*)*
>
<!ELEMENT rel - o (#PCDATA) -- Identifies relevant
spot in citation -->
<!--
<!-- Components of a patent document citation (PCIT)
<!-- RECOMMENDED: use <CIT> as start and end tag when citations are
<!-- within the body of the patent, ie. within <P>- as opposed to in <SDOSR>
<!--
<!-- extdoc Citation identification:
<!-- must include doc. number <DNUM>
<!-- nam Citation applicant or patentee -->
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.90

```
<!ELEMENT pic      - o      (#PCDATA)          -- IPC of citation      -->
<!ELEMENT pnc      - o      (#PCDATA)          -- National class. of cit. -->
<!--      rel              Relevant passage, defined above      -->
<!--
<!-- Components of a non-patent citation (NCIT)
<!--
<!ELEMENT artcit - o      ((%authgrp;)?,atl?,sbt?,(jnl|cng|bookid),
                           pp?,issn?,cdn?)
>
<!--
<!--      authgrp              Article information      -->
<!--      Author group, defined below      -->
<!--
<!ELEMENT atl      - o      (#PCDATA)          -- Article title      -->
<!ELEMENT sbt      - o      (#PCDATA)          -- Article subtitle    -->
<!--
<!ELEMENT jnl      - o      (jtl,sbt?,jabt?,pnm?,date,vid?,ino?,ano?)
>
<!--
<!--      Journal reference      -->
<!ELEMENT jtl      - o      (#PCDATA)          -- Journal title      -->
<!--      sbt              Subtitle, defined previously      -->
<!ELEMENT jabt     - o      (#PCDATA)          -- Journal abbreviated title-->
<!--      pnm              Publisher's name (defined under Bookid)-->
<!--      date              Publication date      -->
<!ELEMENT vid      - o      (#PCDATA)          -- Volume identification -->
<!ELEMENT ino      - o      (#PCDATA)          -- Journal issue number  -->
<!ELEMENT ano      - o      (#PCDATA)          -- Abstract number      -->
<!--
<!ELEMENT pp       - o      (#PCDATA|(ppf,ppl?)) -- Page numbers      -->
<!ELEMENT ppf      - o      (#PCDATA)          -- First page number    -->
<!ELEMENT ppl      - o      (#PCDATA)          -- Last page number     -->
<!--
<!ELEMENT issn     - o      (#PCDATA)          -- ISSN      -->
<!ELEMENT cdn      - o      (#PCDATA)          -- International coden  -->
<!--
<!--      CONFERENCE GROUP / CITATION
<!ELEMENT cng      - o      (cnm,date?,cnn?,cnp?,cns?)
>
<!--
<!--      Conference Proceedings      -->
<!ELEMENT cnm      - o      (#PCDATA)          -- Conference name      -->
<!--      date              Conference date      -->
<!ELEMENT cnn      - o      (#PCDATA)          -- Conference number    -->
<!ELEMENT cnp      - o      (#PCDATA)          -- Conference place     -->
<!ELEMENT cns      - o      (#PCDATA)          -- Conference sponsor   -->
<!--
<!--      BOOK CITATION
<!ELEMENT bookcit - o      (%authgrp;,bookid,part?,sect?,pp?)
                           -- book info.
<!--      authgrp              Author group, defined below      -->
<!--      bookid              Book identification group, see below -->
<!ELEMENT part     - o      (#PCDATA)          -- Part of book      -->
<!ELEMENT sect     - o      (#PCDATA)          -- Section of book    -->
<!--      pp              Page numbers, defined above      -->
<!--      rel              Relevant passage, defined above      -->
<!--
<!ELEMENT bookid - o      (ti,sbt?,edn?,msn?,mst?,ano?,pnm?,date,vid?,
                           no?,ed?,isbn?,cdn?) -- book identification -->
<!--      ti              Title      -->
<!--      sbt              Subtitle (defined under journal)      -->
<!--      edn              Editor's name and address-->
<!--      msn              Monographic series number-->
<!--      mst              Monographic series title -->
<!--      ano              Abstract number, defined above      -->
<!ELEMENT pnm      - o      (%party;)          -- Publisher's name and add.-->
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.91

```
<!--      date      Publication date      -->
<!--      vid      Vol. id., defined above -->
<!ELEMENT no      - o      (#PCDATA)      -- Book number      -->
<!ELEMENT ed      - o      (#PCDATA)      -- Edition statement  -->
<!ELEMENT isbn     - o      (#PCDATA)      -- ISBN              -->
<!--      cdn      Inter. coden,
                  defined above              -->
<!--
<!ELEMENT dbasecit - o      (dbn, pnm?, dbs?, srt?, date?)
>
<!--
<!ELEMENT dbn      - o      (#PCDATA)      Database information group -->
<!--      pnm      Database publisher or service -->
<!ELEMENT dbs      - o      (#PCDATA)      -- Section of database -->
<!ELEMENT srt      - o      (#PCDATA)      -- Search terms      -->
<!--      date      Publication date      -->
<!--
<!ELEMENT othcit   - o      (#PCDATA)      -- Other reference
                  (paragraph form)        -->
<!--
<!--      Components of the author group (AUTHGRP) -->
<!ELEMENT author   - o      (%party;)      -- Author name and address -->
<!ELEMENT coauth   - o      (%party;)      -- Co-author's name and add. -->
<!ELEMENT collab   - o      (%party;)      -- Collaborator's
                  name and address        -->
<!--
<!--      Components of a name (nam) -->
<!--
<!ELEMENT ttl      - o      (#PCDATA)      -- Title (e.g., Mr., Mrs.) -->
<!ELEMENT fnm      - o      (#PCDATA)      -- Given and middle name(s)
                  or initials -->
<!ELEMENT snm      - o      (#PCDATA)      -- Family, last, surname or
                  organisation -->
<!ELEMENT syn      - o      (#PCDATA)      -- Synonym, cross reference -->
<!ELEMENT sfx      - o      (#PCDATA)      -- Suffix (e.g., II, Jr.,
                  Esq. et al.) -->
<!ELEMENT iid      - o      (#PCDATA)      -- Individual ID number
                  (e.g., US SSSN) -->
<!ELEMENT irf      - o      (#PCDATA)      -- Individual ref.
                  number(filing, etc.) -->
<!ELEMENT onm      - o      (#PCDATA)      -- Organization name      -->
<!ELEMENT oid      - o      (#PCDATA)      -- Identifying no. of org. -->
<!ELEMENT odv      - o      (#PCDATA)      -- Division of organization -->
<!ELEMENT did      - o      (#PCDATA)      -- Identifying no. of div. -->
<!--
<!--      Components of an address -->
<!--
<!ELEMENT adr      o o      ((%nam;)?,omc?,pbox?,str*,city?,
                  cnty?,state?,(ctry?&pcode?), (ead*&tel*&fax*))
>
<!--      nam      Organization name, if part of address -->
<!ELEMENT omc      - o      (#PCDATA)      -- Organization mail code -->
<!ELEMENT pbox     - o      (#PCDATA)      -- Post Office box number -->
<!ELEMENT str      - o      (#PCDATA)      -- Str., house no. or name,
                  district of city, apt number, etc. -->
<!--
<!ELEMENT city     - o      (#PCDATA)      -- City or town          -->
<!ELEMENT cnty     - o      (#PCDATA)      -- County, parish,
                  department, etc. -->
<!ELEMENT state    - o      (#PCDATA)      -- Region of country
                  (state, province) -->
<!ELEMENT ctry     - o      (#PCDATA)      -- Country (ST.3)        -->
<!ELEMENT pcode    - o      (#PCDATA)      -- Postal code or zip code -->
<!ELEMENT ead      - o      (#PCDATA)      -- Electronic address
                  (e.g., email) -->
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.92

```
<!ELEMENT tel      - o      (#PCDATA)          -- Telephone number      -->
<!ELEMENT fax      - o      (#PCDATA)          -- Fax telephone number  -->
<!--
<!--
Components of party (party)
<!--      nam      Name of person or organisation
<!--      adr      Address
<!ELEMENT dtxt     - o      (#PCDATA)          -- Descriptive text      -->
<!ELEMENT rctry    - o      (ctry)             -- Country of residence   -->
<!ELEMENT nctry    - o      (ctry)             -- Country of nationality  -->
<!--
Components of a date (date)
<!ELEMENT date     - o      (#PCDATA,time?)     -- YYYYMMDD             -->
<!ELEMENT time     - o      (#PCDATA)          -- HHMMSS (UCT)         -->
<!--
Components of a doc and extdoc (doc, extdoc)
<!ELEMENT dnum     - o      (#PCDATA,(anum?&pnum?))-- Document number      -->
<!ELEMENT anum     - o      (#PCDATA)          -- Application number    -->
<!ELEMENT pnum     - o      (#PCDATA)          -- Publication number     -->
<!--      date      Document date
<!--      ctry      Publishing country, organisation
<!--      kind      Document kind (ST.16),
<!--                  kind generally
<!ELEMENT bnum     - o      (#PCDATA)          -- Bulletin number      -->
<!--      dtxt      Descriptive text
<!--
<!-- ***** SEARCH REPORT SUBDOCUMENT *****
<!--
<!ELEMENT sdosr    - o      ((B510?,B520?,B560?,B580?)|(emi)+)
>
<!--
Search report must or may contain:
<!-- B510      IPC
<!-- B520      National classification
<!-- B561      Patent citation
<!-- B562      Non-patent citation
<!--          ** B561 and/or B562 are required if B560 present
<!-- B563      Category of cited document
<!-- B564      Claims to which relevant
<!-- B561EP    Number of copies of citation (EPO)
<!-- B565      Date of search
<!-- B565EP    Date of draw. up and despatch (EPO)
<!-- B566      Date of mailing search report
<!-- B566EP    Date of despatch of corr. to S.R. (EPO)
<!-- B567      Patent office carrying out search
<!-- B568      Publication of search report
<!-- B569      Search report examiner
<!-- B580      Field of search IPC
<!-- cit      Citation - optional
<!-- THE ABOVE TAGS TO BE USED - OR THE SEARCH REPORT AS AN EMI
]
>
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.93

### ANNEX C

#### PATENT CHARACTER ENTITY REFERENCES (NON-ISO)

The following character entity references are referenced in the DTD above. This is a non-exhaustive list of entity references which may appear in patent documents – many more are possible, and, for data exchange, must be declared to receiving offices. The entity references below, plus the ISO entity references, allow all characters contained in WIPO Standard ST.31 to be included in a patent document instance.

<!-- (C) Special characters in Patent Information not in ISO. Permission to copy in any form is granted for use with conforming SGML systems and applications as defined in ISO 8879, provided this notice is included in all copies. -->

<!-- Character entity set. Naming and reference to this file may be system dependent.

Typical invocation:

```
<!ENTITY % PATSPEC SYSTEM "patspent.ent">
%PATSPEC;-->

<!ENTITY anq      SDATA "[anq      ]" --Approx. but not actually equal to  -->
<!ENTITY dlowbar  SDATA "[dlowbar  ]" --Double underscore                 -->
<!ENTITY Ehac     SDATA "[Ehac     ]" --Equals with hacek; equiangular      -->
<!ENTITY guilder  SDATA "[guilder  ]" --Dutch guilder                     -->
<!ENTITY iis      SDATA "[iis      ]" --Includes in set                    -->
<!ENTITY iss      SDATA "[iss      ]" --Included in set                    -->
<!ENTITY ldurule  SDATA "[ldurule  ]" --Left - and +45 degree rule         -->
<!ENTITY lhdurule SDATA "[lhdurule ]" --Left horizontal,- & +45 degree rule -->
<!ENTITY litre    SDATA "[litre    ]" --Litre                             -->
<!ENTITY lint     SDATA "[lint     ]" --Lower integral                     -->
<!ENTITY lparstr  SDATA "[lparstr  ]" --Left parenthesis, stroke        -->
<!ENTITY lsqbstr  SDATA "[lsqbstr  ]" --Left square bracket, stroke     -->
<!ENTITY min      SDATA "[min      ]" --Minutes                             -->
<!ENTITY ngtneq   SDATA "[ngtneq   ]" --Neither greater than nor equiv. to -->
<!ENTITY ngtnlt   SDATA "[ngtnlt   ]" --Neither greater than nor less than -->
<!ENTITY nltneg   SDATA "[nltneg   ]" --Neither less than nor equivalent to -->
<!ENTITY nltngt   SDATA "[nltngt   ]" --Neither less than not greater than -->
<!ENTITY omicron  SDATA "[omicron  ]" --Small omicron Greek                -->
<!ENTITY Ovbar    SDATA "[Ovbar    ]" --Double overscore                 -->
<!ENTITY parl     SDATA "[parl     ]" --Parallelogram                     -->
<!ENTITY peseta   SDATA "[peseta   ]" --Peseta                             -->
<!ENTITY rdurule  SDATA "[rdurule  ]" --Right - and +45 degree rule         -->
<!ENTITY rhdurule SDATA "[rhdurule ]" --Right horizontal,- & +45 degree rule-->
<!ENTITY rparstr  SDATA "[rparstr  ]" --Right parenthesis, stroke        -->
<!ENTITY rsqbstr  SDATA "[rsqbstr  ]" --Right square bracket, stroke     -->
<!ENTITY sbplus   SDATA "[sbplus   ]" --Subscript plus                    -->
<!ENTITY sec      SDATA "[sec      ]" --Seconds                             -->
<!ENTITY sinew    SDATA "[sinew    ]" --Sinus wave                       -->
<!ENTITY sl0      SDATA "[sl0      ]" --Slash zero                         -->
<!ENTITY squslash SDATA "[squslash ]" --Square slash, cancelled box      -->
<!ENTITY sub0     SDATA "[sub0     ]" --Subscript 0                       -->
<!ENTITY sub1     SDATA "[sub1     ]" --Subscript 1                       -->
<!ENTITY sub2     SDATA "[sub2     ]" --Subscript 2                       -->
<!ENTITY sub3     SDATA "[sub3     ]" --Subscript 3                       -->
<!ENTITY sub4     SDATA "[sub4     ]" --Subscript 4                       -->
<!ENTITY sub5     SDATA "[sub5     ]" --Subscript 5                       -->
<!ENTITY sub6     SDATA "[sub6     ]" --Subscript 6                       -->
<!ENTITY sub7     SDATA "[sub7     ]" --Subscript 7                       -->
<!ENTITY sub8     SDATA "[sub8     ]" --Subscript 8                       -->
<!ENTITY sub9     SDATA "[sub9     ]" --Subscript 9                       -->
<!ENTITY submin   SDATA "[submin   ]" --Subscript minus                    -->
<!ENTITY sup0     SDATA "[sup0     ]" --Superscript 0                     -->
<!ENTITY sup4     SDATA "[sup4     ]" --Superscript 4                     -->
<!ENTITY sup5     SDATA "[sup5     ]" --Superscript 5                     -->
<!ENTITY sup6     SDATA "[sup6     ]" --Superscript 6                     -->
<!ENTITY sup7     SDATA "[sup7     ]" --Superscript 7                     -->
<!ENTITY sup8     SDATA "[sup8     ]" --Superscript 8                     -->
```



## HANDBOOK ON INDUSTRIAL PROPERTY INFORMATION AND DOCUMENTATION

Ref.: Standards – ST.32

page: 3.32.94

---

|                   |                  |                        |     |
|-------------------|------------------|------------------------|-----|
| <!ENTITY sup9     | SDATA "[sup9     | ]" --Superscript 9     | --> |
| <!ENTITY supa     | SDATA "[supa     | ]" --Superscript a     | --> |
| <!ENTITY supand   | SDATA "[supand   | ]" --Superscript AND   | --> |
| <!ENTITY supcomma | SDATA "[supcomma | ]" --Superscript comma | --> |
| <!ENTITY supmin   | SDATA "[supmin   | ]" --Superscript minus | --> |
| <!ENTITY spplus   | SDATA "[supplus  | ]" --Superscript plus  | --> |
| <!ENTITY uint     | SDATA "[uint     | ]" --Upper integral    | --> |